

PRODUCT LINE CATALOG

Rosewill®

THE BEST CHOICE IN VALUE



WWW.ROSEWILL.COM

© 2004-2009 Rosewill Inc. All rights reserved

Table of Contents

Accessories

Adapters.....	3
Card Reader.....	6
Enclosure Case.....	8
Cooling Device.....	12
USB Hub.....	18
PC Tools Kits.....	20
Other Tools.....	22
Thermal Grease.....	24

Case

ATX Mid Tower.....	25
Micro ATX	31
Micro ATX Slim.....	31
Mini ATX Tower.....	32
Server Chassis	33

Cables

Audio Cable.....	34
Video Cable	36
VGA Cable	37
Networking Cable	39
USB Cable	51
Other Cable.....	53

Controllers Card

Raid Card.....	58
----------------	----

Home Video

HDMI.....	61
Headsets.....	62
TV Brackets.....	63

Power Supply

ATX.....	66
SFX.....	73

Input Device

Keyboard.....	74
Mouse.....	75
KVM.....	76
WebCam.....	77
Add-On-Card.....	77
Headphone.....	80

Notebook Accessories

Notebook Bag.....	81
Notebook Cooling.....	82
Notebook Holder.....	83
Notebook Adapter.....	84
PCMCIA Card	84
Express Card	86
External CD/DVD Drive.....	86
Travel Kits	86

Monitor Accesories

Monitor Mounting Kits.....	87
Cleaning Kits.....	87

Networking

Wired Networking	89
Wireless Networking.....	92

Remanufactured Toner

Remanufactured Toner.....	97
---------------------------	----

Raid Sub System

Server Raid System	113
--------------------------	-----

Adapters

FEATURES

SPECIFICATIONS



RCW-H9003

This bi-directional video adapter is designed to convert composite RCA to S-Video or viceversa. The Y/C signal separation circuitry provides a bright, crisp picture from DVD, VCD, laser disc, VCR, camcorder and multimedia PC.

Model No.	RCW-H9003
Type	Bi-Directional RCA to S-Video
Color	Blue
Connectors	2
Terminal Gender	F-M



RCW-H9013

Adapts 3.5mm stereo plug to two RCA jacks. Ideal when you want to connect a portable device to your home stereo or when you want to adapt your home stereo to 3.5mm record input on computer sound card or portable devices.

Model No.	RCW-H9013
Type	3.5mm stereo to RCA
Color	Black
Connectors	3
Terminal Gender	M-2F



RCW-H9016

RCA Female to RCA Female. 2-piece kit for splicing together composite audio cables. Gold plating connectors provide maximum corrosion resistance for error-free data transfer. This two piece connector kit is constructed with gold plating that provides low-loss signal transfers and resists deterioration.

Model No.	RCW-H9016
Type	RCA Coupler
Color	Black & Red
Connectors	4
Terminal Gender	M-F



RCW-H9015

Ideal for connecting a digital source to a DVI-D display. Pure digital connection with no signal degradation. Gold plating contacts for worry-free performance. Ideal for Satellite, DVD, HDTV, Plasma, LCD and DLP

Model No.	RCW-H9015
Type	DVI to HDM
Color	Black
Connectors	2
Terminal Gender	M-F



RCW-618

Allows IDE and SATA devices simultaneously to be connected on a USB port
For Hard Drives, CD-ROM, CD-RW, DVD-ROM, DVD-RW
USB2.0 and USB1.1/1.0 compliant
Supports ATA/ATAPI-6 Spec 1.0 and SATA I or SATAII
USB2.0 up to 480 mbps transfer rate
Hot Plug and Play
Compact & Portable design
USB cable attachable

Model No.	RCW-618
Interface	SATA & IDE to USB2.0
External Interface	USB2.0
Driver Type	IDE -- 2.5" or 3.5" or 5.25" Optical Device SATA -- 2.5" or 3.5" Optical Device
Material	PC Plastic
O.S. Support	Windows 98SE/2000/ME/XP/Vista

Adapters

FEATURES

SPECIFICATIONS



RC-USB-PS2-BG

USB PS/2 for SUN Microsystems platforms, refer to below table, support two PS/2 devices (Keyboard and Mouse) and converts to the USB Interface, support standard PS/2 Mouse driver needed, no power adapter is needed, support UHCI and OHCI USB Interface, Cypress chipset provides more comparability to all kinds of PC hardware. Please attach the correct port to mouse and keyboard or they might not work properly, green port is for mouse and the other one is for keyboard
Please note: RC-USB-PS2-BG might not be compatible with some version of KVM

Model No.	RC-USB-PS2-BG
Type	USB to PS/2
Length	6ft
Color	Beige
USB	Type A Male
PS/2	MD-6 Female x 2
OS Support	Windows 98/ME/2000/XP/Vista
Interface Support	UHCI and OHCI USB Interface
Connectors	1 x USB A 2 x mini-DIN 6 pin sockets



RCW-615

Single chip USB to Parallel host to host communication USB full speed communication and bus powered USB Printer Class Specification 1.1 compliant RCW-615 is designed for connecting parallel printer only and can be compatible with various parallel printers IEEE-1284 1994 (bi-directional parallel interface) specification compliant
 RCW-615 can plug and play without any driver in Windows 2000 / XP / Vista.

Model No.	RCW-615
Type	USB to DB25
USB	Type A Male
Cable Length	6ft
OS Support	Windows 98/SE/ME/2000/XP/ Vista
Data Transfer Rate	Full speed 12Mbps Low speed 1.5Mbps



RCW-616

Works for ALL LAPTOPS HARD DRIVE including DELL, SONY, IBM, Toshiba, HP, COMPAQ, Fujitsu and much more Easily create Ghost images of your laptop (keep in mind that it is much harder to create Ghost Images from laptop itself), transfer data from laptop drive to a desktop drive the quickest way, the best accessory for laptop data backup and recovery, this adapter allows you to connect a laptop hard drive to a desktop IDE cable, the laptop hard drive can then be detected and used as a regular IDE drive. Please be careful of the direction of fitting RCW-616 to your ATA device. You could bend and damage the pins on it by improper installation

Model No.	RCW-616
Connectors	44-pin Female to 40-pin IDE Male
Use	Connects your 2.5in notebook IDE hard drive to a 40-pin IDE cable
Warranty	1 Year



RCW-617

Supports automatic, manual mode
 Over 230bps data transfer rate
 Supports remote wake-up and power management 96 byte buffer each for upstream and downstream data flow
 Easy installation
 Works with cellular phones, PDA, digital cameras, modems, and ISDN terminal adapters
 Free your RS-232 ports for other users
 No IRQs need

Model No.	RCW-617
Type	USB to DB9 (RS-232)
Cable Length	1ft
OS Support	Windows 95/98/98SE/ME/2000/XP/Vista Mac OS 8.6-10.3



RCW-608

Compliance with Gen1 of Serial ATA II Electrical Specification 1.0, support SATA Spread-Spectrum Clock, support SATA II Asynchronous Signal Recovery (Hot Plug) feature Compliance with USB 2.0 electrical specification, support USB High-Speed and Full-Speed Operation, compliance with USB Mass Storage Class, Bulk-Only Transport Specification, support ATA/ATAPI PACKET command set, support ATA/ATAPI LBA48 addressing mode, support 12MHz external crystal, support external NVRAM for Vendor Specific VID/PID, Manufacture, Product String of USB Device Controller, 2.5" & 3.5" Silicone protection case Included (Black or Blue color may vary)

Model No.	RCW-608
Interface	SATA & IDE to USB 2.0
Driver Type	IDE -- 2.5" or 3.5" or 5.25" Optical Device SATA -- 2.5" or 3.5" Optical Device
Material	PC Plastic
O.S. Support	Windows 98SE/2000/ME/XP/Vista
Package	Cable, CD Driver, Power Adaptor
Power Source	External Power Adapter Input: AC 100-240V, 50-60Hz Output: DC +12V/1.5A

Adapters

FEATURES

SPECIFICATIONS



RCW-306

Adapts one 5.25in power connector into one Serial ATA power connector
Designed for Serial ATA Hard Drives, CD-ROMs, CD-RWs, Tape Drives, Fans, etc
Serial ATA power connector with latch to have right contact with the devices

Model No.	RCW-306
Type	Power Cable
Length	15cm
Color	Multi color
Connectors	2 Connectors
Specifications	Serial ATA II Power adapter cable, 5.25" M-15P Serial ATA II F with latch, 15 cm
Warranty	1 Year



RCW-702

Extension for Connectors of DVI-D 24-pin Male
Dual link digital signaling allows for high speed transmission up to 9.9Gbps
Gold-plated contacts provide full conductivity with no data loss
Supports hot plugging of DVI display devices
PC and Mac compatible
Resolutions up to 2048 x 1536
Supports digital signals
Compatible with flat panel displays, digital CRT displays, projectors, and HDTV

Model No.	RCW-702
Type	Adapter
Specifications	Adapter, DVI -I (24+5) F-F, with dust cover
Warranty	1 Year



RCW-701

Adapts to an existing VGA cable for use with a DVI plug
Gold-plated contacts provide full conductivity with no data loss
Supports hot plugging of DVI display devices
PC and Mac compatible
Resolutions up to 1600 x 1200
Supports analog signals
Compatible with flat panel displays, digital CRT displays, projectors, and HDTV
Meets DVI DDWG Standard

Model No.	RCW-701
Type	Adapter
Specifications	Adapter, DVI -A (24+5) F- VGA HD15 M, with dust cover
Warranty	1 Year



RCW-700

Adapts to an existing VGA cable for use with a DVI plug
Gold-plated contacts provide full conductivity with no data loss
Supports hot plugging of DVI display devices
PC and Mac compatible
Resolutions up to 1600 x 1200
Supports analog signals
Compatible with flat panel displays, digital CRT displays, projectors, and HDTV
Meets DVI DDWG Standard

Model No.	RCW-700
Type	USB2.0 & IDE (External USB2.0)
Specifications	Adapter,DVI -A (24+5) M- VGA HD15 F, with dust cover
Warranty	1 Year



RC-202

Convert Internal SATA 2 ports to external e-SATA Ports connection at PCI bracket

Model No.	RC-202
1. Cable:	(26AWG/1P+A)*2+4D, AWM style 2725 80 degree 30V VW-1 Conductor: 26AWG solid tinned copper Isolator: FOAM PE or FOAM PP Wrapping: Hot melt aluminum mylar spirally wrapped Drain Wire: 28AWG solid tinned Copper Jacket: 80C PVC OD 2.2mm*7.80mm+/-0.2
2. Connector:	Housing: Temperature polyester & Glass fiber, UL 94V-0 Terminal: Copper alloy Cover: ABS, UL 94V-0 Plating: 15 u" gold plated over 50u" nickel.
3. High Frequency Character:	Impedance: 100+/-15 ohms...
For complete specs go to: www.rosewill.com	

Accessories

Adapters

FEATURES



SPECIFICATIONS



RC-206

Convert Internal SATA 2 ports to External connection at PCI bracket

Model No. RC-206
1. Cable: (26AWG/1P+A)*2+4D, AWM style 2725 80 degree 30V VW-1 Conductor: 26AWG solid tinned copper
 Isolator: FOAM PE or FOAM PP Wrapping: Hot melt aluminum mylar spirally wrapped Drain Wire: 28AWG solid tinned Copper Jacket: 80C PVC OD 2.2mm*7.80mm+/-0.2
2. Connector: Housing: Temperature polyester & Glass fiber, UL 94V-0 Terminal: Copper alloy Cover: ABS, UL 94V-0 Plating: 15 u" gold plated over 50u" nickel.
3. High Frequency Character: Impedance: 100+/-15 ohms...
 For complete specs go to: www.rosewill.com

Card Reader

/ External



RCR-TT-EA001-W

Ultra Slim Size
 High Speed USB 2.0 Interface
 Data Transfer Rate Up to 480 Mb/S
 Plug & Play
 Supports SDHC
 Adapter Free For Small Memory Cards
 Compatible With Windows 98 / SE / ME / 2000 / XP / VISTA

Model No. RCR-TT-EA001-W
Slots 6
Installation Type External
Interface USB 2.0
Color White
Support - Memory Stick Yes
Support - MMC Yes
Support - SD Yes
Compatibility MMC Micro , SD/MMC , MICRO SD , M2 , MS



RCR-EA001W

Hi-Speed USB 2.0 backwards compatible with all USB 1.1 ports, all five memory slots are activated, which allows you to copy data between the different memory cards at the same time, max Speed will be up to 480Mb/sec, Plug & play and Hot Swapping, Windows 98/98SE/2000/XP and Mac OS 9.x/Mac, driver-free device for Windows 2000/XP/Vista, plug into USB port directly without any driver

Model No. RCR-EA001W
Slots 5
Installation Type External
Interface USB 2.0
Color White
Compatibility **CF Slot :** CF I, CF II, EXTREME III CF, EXTREME CF, ULTRA II CF, HS CF, XS-XS CF, CF PRO, CF ELITE PRO, CF PRO II, IBM MD, HITACHI MD, MAGIC STORE **SD Slot :** SD, MINI SD, HS MINI SD, EXTREME SD, EXTREME III SD, SDHC class 2/4/6, ULTRA II SD, SD-ULTRA-X, ULTRA
 For complete specs go to: www.rosewill.com



RCR-EA001B

Hi-Speed USB 2.0 backwards compatible with all USB 1.1 ports, all five memory slots are activated, which allows you to copy data between the different memory cards at the same time, max Speed will be up to 480Mb/sec, Plug & play and Hot Swapping, Windows 98/98SE/2000/XP and Mac OS 9.x/Mac, driver-free device for Windows 2000/XP/Vista. Plug into USB port directly without any driver

Model No. RCR-EA001B
Slots 5
Installation Type External
Interface USB 2.0
Color Black
Compatibility **CF Slot :** CF I, CF II, EXTREME III CF, EXTREME CF, ULTRA II CF, HS CF, XS-XS CF, CF PRO, CF ELITE PRO, CF PRO II, IBM MD, HITACHI MD, MAGIC STORE **SD Slot :** SD, MINI SD, HS MINI SD, EXTREME SD, EXTREME III SD, SDHC class 2/4/6, ULTRA II SD, SD-ULTRA-X, ULTRA
 For complete specs go to: www.rosewill.com



RSD-CR106 Black

Color: Black
 True plug & play, and hot swapping
 View, edit, and copy photos/data/music
 USB 2.0 speed-Fast data/files access and transfer rate up to 480Mbps
 No driver is needed for Windows ME, 2000,XP,Mac OS 9.X
 Compatible with PC & Mac
 With LED status indicator for file access

Model No. RSD-CR106 Black
Installation Type External
Interface USB 2.0
Color Black
Compatibility Support SD1.1, SD2.0(SDHC) , MMC, RS-MMC and MiniSD, Micro SD,MMC Micro (With Adapter)
Support-MMC Yes
Support-SD Yes

Card Reader / EXTERNAL

FEATURES

SPECIFICATIONS



RSD-CR106_Blue

True plug & play, and hot swapping
View, edit, and copy photos/data/music
USB 2.0 speed-Fast data/files access and transfer rate up to 480Mbps
No driver is needed for Windows ME, 2000,XP,Mac OS 9.X
Compatible with PC & Mac
With LED status indicator for file access

Model No.	RSD-CR106 Blue
Installation Type	External
Interface	USB 2.0
Color	Blue
Compatibility	Support SD1.1, SD2.0(SDHC), MMC, RS-MMC and MiniSD, Micro SD,MMC Micro (With Adapter)
Support-MMC	Yes
Support-SD	Yes



RME-001

Hot-Swappable Supported, compliant to USB 2.0
Compatible with SDHC
LED working indicator light
Compact and streamline design on its shape
For Micro SD Card only
Supports WIN2000/XP/VISTA, MAC OS V9.2 or higher

Model No.	RME-001
Slots	1
Installation Type	External
Interface	USB 2.0
Color	White
Compatibility	Supports Micro Secure Digital Card (Micro SD) / T-Flash Card
Support-SD	Yes

/ Card Reader / Internal



RCR-IC002

Supports 74 different types of memory cards
With two face plates (silver/black)
Supports SDHC
Supports data transfer between memory slots except for (Micro SD/M2 Slot and SD/MMC Slot) and (Micro SD/M2 Slot and MS Slot)

Model No.	RCR-IC002
Type	All-in-One
Slots	5
Installation Type	Internal
Interface	USB2.0
Installation Type	3.5" Internal Drive Bay
Support:	Compact Flash, Memory Stick, MMC, SD



RCR-FD201

High Speed USB2.0 transmission
All-in-one card reader
Fully compliant with USB 2.0 specification
Color: Black
Support Windows 2000/ME/XP; Linux 2.4; Mac. OS 9x or higher

Model No.	RCR-FD201
Installation Type	3.5" Internal Drive Bay
Compatibility	Compact Flash, Memory Stick Pro, Memory Stick Pro Duo, Secure Digital, SDHC, Mini SD Multimedia Card, RSMMC
Slots	2
Interface	USB2.0
Installation	3.5" Internal Drive Bay
Support:	Compact Flash, Memory Stick, MMC, SD
Dimensions:	5.66" x 3.99" x 1.00"



RCR-IC001

Supports high speed USB 2.0
Easy plug and play and hot swapping for dynamic insert in/remove from four memory card slots
Internal memory card reader for 3.5" bay
With USB port

Model No.	RCR-IC001
Slots	4
Installation Type	Internal
Interface	USB2.0
Support:	Compact Flash, Memory Stick, MMC, SD
Dimensions:	5.66" x 3.99" x 1.00"

Accessories



Card Reader / INTERNAL

FEATURES

SPECIFICATIONS



RCR-102

High Speed USB2.0 transmission
52-in-1 card reader
Fully compliant with USB 2.0 specification
USB port x 1
Support Windows 98/98SE/2000/ME/XP; Linux 2.4; Mac OS 9x or higher

Model No.	RCR-102
USB Port	1 Port
Installation Type	Internal
Interface	USB 2.0
Operating System Supported:	Windows 98/98SE/2000/ME/XP Linux 2.4 Mac OS 9x or higher 3.5" Internal Drive Bay
Power Supply	Supplied by USB Port
Size	4.04" x 3.88" x 1.0"

Enclosure

/ 2.5" IDE to USB



RX81U-ES-25B

Easy Installation & portable
Fully compliant with USB 2.0 & USB 1.1
Transfer Rate: High-Speed up to 480 Mbps data transfer rate
Supports 2.5" IDE Hard Disk Drives
LED indicates Power and Active status
Powered by USB port.
Operating System Support:
W98SE/ME/2000/XP/VistaMac OS 9.2 or higher
Drive Capacity Support: 250GB

Model	RX81U-ES-25B
Size	2.5"
Internal Interface	IDE
External Interface	USB 2.0(Transfer Rates Up To 480 Mbps)
Material	Aluminum & plastic
Fan	w/o fan
Color	Black
Bay	One bay
Dimensions	130 x 75 x 15mm
Connectors	USB mini B Female



RX234

HDD Support: Up to 160GB
LED indicator: Green
OS Supports
Win2000/ME/XP/VISTA
Mac OS 8.6/9.x/10.x and above
Linux kernel after 2.4.1.0

Model	RX234
Size	2.5"
Internal Interface	IDE
External Interface	USB 2.0
Material	Aluminum
Fan	w/o fan
Color	Black
Bay	One bay
Connectors	USB mini B Female



RX81U-ES-25A

Easy Installation & portable
Fully compliant with USB 2.0 & USB 1.1
Transfer Rate: High-Speed up to 480 Mbps data transfer rate
Supports 2.5" SATA Hard Disk Drives
LED indicates Power and Active status
Powered by USB port
Hot-swappable
Drive Capacity support: 250GB
Operation System support:
Windows 98SE/ME/2000/XP/Vista, Mac OS 9.2 or higher

Model	RX81U-ES-25A
Size	2.5"
Internal Interface	IDE
External Interface	USB 2.0
Material	Aluminum & plastic
Fan	w/o fan
Color	Black
Bay	One bay
Dimensions	130 x 75 x 15mm

/ 3.5" & 2.5" SATA to USB & eSATA



RX355-X2 BK

Internal metal shielding plus two 50mm Cooling fans to provide the excellent heat dissipation
BLUE LED indicators for Power & HDD activity
eSATA connection provides excellent transfer speed
Simple HDD installation
Support up to 1.5TB HDD
Two 50mm Cooling Fans
Complies with SATA I/II, speed up to 3Gbps
Power On / Off switch
Supports Win 2000/ME/XP/VISTA, and Mac OS 9.x/ 10.x and above, Linux kernel after 2.4.1.0

Model	RX355-X2 BK
Size	3.5"
Internal Interface	SATA I/II
External Interface	USB2.0 & eSATA
Material	ABS Cover and internal metal shielding
Fan	2 x 50 mm cooling fan
Color	Black
Bay	One bay
Dimensions	8.86" x 5.69" x 2.68"

Enclosure / Enclosure / 3.5" IDE to USB

FEATURES

SPECIFICATIONS



RX35-AT-IU SLV

Light and small design for easy portability
Aluminum material provides excellent heat dissipation.
Supports transfer rates up to 480 Mbps with USB 2.0
LED indicates Power / HDD status
Compliant with USB 2.0 Backward Compatible W/USB 1.1
Supports Windows 98SE, ME, 2000, XP, Vista and Mac OS 8.6+

Model	RX35-AT-IU SLV
Size	3.5"
Internal Interface	IDE
External Interface	USB 2.0
Material	Aluminum
Fan	w/o fan
Color	Silver
Bay	One bay
Dimensions	7.60" x 4.45" x 1.22"



RX35-AT-IU BLK

Light and small design for easy portability
Aluminum material provides excellent heat dissipation.
Supports transfer rates up to 480 Mbps with USB 2.0
LED indicates Power / HDD status
Compliant with USB 2.0 Backward Compatible W/ USB 1.1
Supports Windows 98SE, ME, 2000, XP, Vista and Mac OS 8.6+

Model	RX35-AT-IU BLK
Size	3.5"
Internal Interface	IDE
External Interface	USB 2.0
Material	Aluminum
Fan	w/o fan
Color	Black
Bay	One bay
Dimensions	7.60" x 4.45" x 1.22"



RX355-U

Built-in with integrated 80 mm ultra silent cooling fan provides excellent heat dissipation.
Fan control for the 80mm cooling fan.
LED indicator, support up to 750 GB HDD.

Model	RX355-U
Size	3.5"
Internal Interface	3.5"IDE
External Interface	USB 2.0 (Speed up to 480 Mbps)
Material	Aluminum
Fan	Yes
Color	Black
Bay	One bay
Dimensions	220(L) x 130(W) x 65(H) mm

/ Enclosure / 3.5" SATA



R2-JBOD

Material Full Aluminum Cover, metal tray
Fan 1 x 50mm cooling fan (Internal Tray)
Specifications Support up to 2x 1TB HDD
Support JBOD & BIG Mode
USB Supports Win 2000/ME/XP/VISTA, and Mac OS 9.x/10.x and above, Linux kernel after 2.4.1.0

Model	R2-JBOD
Size	3.5"
Internal Interface	SATA I/II
External Interface	USB 2.0
Material	Full Aluminum Cover
Fan	Internal 50mm Cooling Fan
Color	Black
Bay	Two bay
Dimensions	229 (L) x124 (W) x33 (H) mm

/ Enclosure / 3.5" SATA to USB



RX35-AT-SU BLK

can support update to 1.5TB
Light and small design for easy portability
Aluminum material provides excellent heat dissipation.
Supports transfer rates up to 480 Mbps with USB 2.0
LED indicates Power / HDD status
Compliant with USB 2.0 Backward Compatible With USB 1.1
Supports Windows 98SE, ME, 2000, XP, Vista and Mac OS 8.6+

Model	RX35-AT-SU BLK
Size	3.5"
Internal Interface	SATA
External Interface	USB 2.0
Material	Aluminum
Fan	w/o fan
Color	Black
Bay	One bay
Dimensions	7.60" x 4.45" x 1.22"

Enclosure / 3.5" SATA to 1394a/b & USB & eSATA

FEATURES

SPECIFICATIONS



RX81-MP-SC-SLV

Real plug and play
Hot-swappable connection
can support update to 1.5TB
OS requirement:
Windows 98SE/ME/2000/XP/Vista
Linux 2.4.1.0 or above
Mac OS 8.6 above
Please check to make sure the motherboard supports
HOT-SWAP function. Otherwise, the hot swappable function won't be work as well. (Please refer back to motherboard user guide)

Model	RX81-MP-SC- SLV
Size	3.5"
Internal Interface	SATA
External Interface	USB 2.0 & 1394 & eSATA
Material	Aluminum with internal metal chassis for optimized heat dissipation
Fan	w/o fan
Color	Silver
Bay	One bay
Dimensions	8.86" x 5.31" x 1.37"



RX81-MP-SC- BLK

Real plug and play
Hot-swappable connection
can support update to 1.5TB
OS requirement:
Windows 98SE/ME/2000/XP/Vista
Linux 2.4.1.0 or above
Mac OS 8.6 above
Please check to make sure the motherboard supports
HOT-SWAP function. Otherwise, the hot swappable function won't be work as well. (Please refer back to motherboard user guide)

Model	RX81-MP-SC- BLK
Size	3.5"
Internal Interface	SATA
External Interface	USB 2.0 & 1394 & eSATA
Material	Aluminum with internal metal chassis for optimized heat dissipation
Fan	w/o fan
Color	Black
Bay	One bay
Dimensions	8.86" x 5.31" x 1.37"



RX81-Stray

Tray Module Compatible with the following: RX81-US,
RX82-U(JBOD)
Aluminum Design
Compatible Hard Drives: 3.5" SATA I / SATA II Hard Drives
Hard Drive Not Included
Regulatory Certifications :FCC, RoHS
Please check to make sure the motherboard supports
HOT-SWAP function. Otherwise, the hot swappable function won't be work as well. (Please refer back to motherboard user guide)

Model	RX81-STRAY
Size	3.5"
Internal Interface	SATA I / SATA II
Material	Aluminum
Fan	w/o fan
Color	Silver/Black
Bay	One bay
Dimensions	6.8" x 4.2" x 1.0"



RX82-U

Support Up to 1 TB HDD x 2, 2 hard drives which can support vary brands of SATA 1 or SATA 2 and users could choose hard drives of their favor or use the original one. By installing two 500GB hard drives could get 1 TB capacity. Hot-swappable tray module gives the user with convenience of replace hard disk and is not necessary to buy many of unrequisited of external devices. Build in with 70 Watts universal power supply which providing sufficient power resources to avoid the burden that brings by the adapter externally. This device can support JBODMode. OS requirement: Windows 98SE/ME/2000 /XP/Vista, Linux 2.4.1.0 or above, Mac OS 8.6 above

Model	RX82-U
Size	3.5"
Internal Interface	SATA I/II
External Interface	USB 2.0(Transfer Rates Up To 480 Mbps)
Material	Aluminum
Fan	4cm Ball Bearing Fan
Color	Silver/Black
Bay	Two bay
Dimensions	4.8" x 8.1" x 4.1"



RX81-US

can support up to 1.5TB
Support 3.5" SATA/II HDD
USB 2.0 & eSATA combo Host interfaces.
The mobile tray enables the HDD Hot Swap. One case for more HDDs, cost-saving and place-saving.
Full aluminium case and air holes ensure the cooling and silent operation.
Compact size for easy transportation.
Universal power adapter : 100-240V.
Addition Tray is available (RX81-STRAY)
Regulatory Certifications:FCC, RoHS

Model	RX81-US
Size	3.5"
Internal Interface	SATA
External Interface	SATA & USB 2.0
Material	Aluminum
Fan	w/o fan
Color	Black
Bay	One bay
Dimensions	34 (B) x 190 (T) x 134 (H) mm

Enclosure / 3.5" SATA to eSATA & USB

FEATURES

SPECIFICATIONS



RX-358-S-BLK

Support up to 1.5TB HDD
 Power On/Off for internal cooling fan
 USB Supports Win 2000/ME/XP/VISTA, and Mac OS 9.x/10.x and above, Linux kernel after 2.4.1.0
 Power Adapter, 100-240 VAC(47Hz~63Hz), 12V/2A output
 Full Aluminum Cover, metal tray

Model	RX-358-S-BLK
Size	3.5"
Internal Interface	SATA I/II
External Interface	USB2.0 & eSATA
Material	Full Aluminum Cover, metal tray
Fan	1 x 80mm cooling fan (Internal Tray)
Color	Black
Bay	One bay
Dimensions	(LxWxH) 7.59" x 4.92" x 1.77"



RX-358-S-SLV

Support up to 1.5TB HDD
 Power On/Off for internal cooling fan
 USB Supports Win 2000/ME/XP/VISTA, and Mac OS 9.x/10.x and above, Linux kernel after 2.4.1.0
 Power Adapter, 100-240 VAC(47Hz~63Hz), 12V/2A output

Model	RX-358-S-SLV
Size	3.5"
Internal Interface	SATA I/II
External Interface	USB2.0 & eSATA
Material	Full Aluminum Cover, metal tray
Fan	1 x 80mm cooling fan (Internal Tray)
Color	Silver
Bay	One bay
Dimensions	(LxWxH) 7.59" x 4.92" x 1.77"

Cooling Device / CPU Cooler / Z Series for AMD

FEATURES

SPECIFICATIONS



RCX-Z80-AL

Other Features:

Huge dimensions of aluminum fins for excellent heat dissipation

Compatibility:

Socket 754 / 939 / 940 / AM2

Model	RCX-Z80-AL
Heatsink Material	Aluminum
Fan Size	80mm
Bearing Type	Sleeve
RPM	2500 RPM
Air Flow	33.21 CFM
Noise Level	22.41 dBA



RCX-Z940-LX

Other Features:

3 embedded heat pipes for excellent heat dissipation
92mm fan

Automatic PWM fan speed control

Copper base

Compatibility:

AMD Athlon 64 FX (Socket 939, 940, AM2)

AMD Athlon 64 X2 (Socket 939, AM2)

AMD Athlon 64 (Socket 754, 939, AM2)

AMD Sempron (Socket 754, 939, AM2)

Model	RCX-Z940-LX
Heatsink Material	Hi-grade aluminum fins, 3 embedded copper heatpipes and copper base
Fan Size	92mm
Bearing Type	Ball



RCX-Z1

Other Features:

92mm silent fan with fan guard ,Huge dimension copper base, Stick together power cable

Fan controller included, pure aluminum heatsink

Simple installation for AMD, anodizing for Aluminum Alloy with huge dimension copper base.

Compatibility :

AMD Athlon 64 FX (Socket 939, 940, AM2)

AMD Athlon 64 X2 (Socket 939, AM2)

AMD Athlon 64 (Socket 754, 939, AM2)

AMD Sempron (Socket 754, 939, AM2)

Model	RCX-Z1
Heatsink Material	Anodizing For Aluminum Alloy with huge dimension copper base
Fan Size	92mm
Bearing Type	Long life ball bearing for over 75000/hrs
RPM	1700 - 3100 RPM
Air Flow	33 - 57.2 CFM
Noise Level	18 - 33.4 dBA



RCX-Z100

Other Features:

92mm quiet fan

Huge dimension copper base

Stick together power cable

Pure aluminum heatsink

Compatibility:

AMD Athlon XP3400+ (Socket A - 462pins)

Model	RCX-Z100
Heatsink Material	Pure aluminum heatsink w/full copper base
Fan Size	92mm
Bearing Type	One ball bearing for over 45000/hrs life
RPM	2200 RPM
Air Flow	44 CFM
Noise Level	22.5 dBA



RCX-Z940-LX

Other Features:

3 embedded heat pipes for excellent heat dissipation
92mm fan

Automatic PWM fan speed control

Copper base

Compatibility:

AMD Athlon 64 FX (Socket 939, 940, AM2)

AMD Athlon 64 X2 (Socket 939, AM2)

AMD Athlon 64 (Socket 754, 939, AM2)

AMD Sempron (Socket 754, 939, AM2)

Model	RCX-Z940-LX
Heatsink Material	Hi-grade aluminum fins, 3 embedded copper heatpipes and copper base
Fan Size	92mm
Bearing Type	Ball
Noise Level	22.5 dBA

Cooling Device / CPU Cooler / Z Series for Intel

FEATURES

SPECIFICATIONS



RCX-Z300

Other Features:

92mm fan. Automatic PWM fan speed control
Copper base

Compatibility:

Intel Core 2 Extreme (Socket LGA 775)
Intel Core 2 Quad (Socket LGA 775)
Intel Core 2 Duo (Socket LGA 775)
Intel Pentium Extreme (Socket LGA 775)
Intel Pentium D (Socket LGA 775)
Intel Pentium 4 (Socket LGA 775)
Intel Celeron D (Socket LGA 775)

Model	RCX-Z300
Heatsink Material	Aluminum extrusion fin with copper base
Fan Size	92mm
Bearing Type	Ball



RCX-Z775-LX

Other Features:

3 embedded heat pipes for excellent heat dissipation
92mm fan, Automatic PWM fan speed control. Copper base

Compatibility:

Intel Core 2 Extreme (Socket LGA 775)
Intel Core 2 Quad (Socket LGA 775)
Intel Core 2 Duo (Socket LGA 775)
Intel Pentium Extreme (Socket LGA 775)
Intel Pentium D (Socket LGA 775)
Intel Pentium 4 (Socket LGA 775)
Intel Celeron D (Socket LGA 775)

Model	RCX-Z775-LX
Heatsink Material	Hi-grade aluminum fins, 3 embedded copper heatpipes and copper base
Fan Size	92mm
Bearing Type	Ball



RCX-Z2

Other Features:

Supporting PWM up to CFM 44.264 and 3.19 mm H2O.
New heatpipe technology with 52 fine-fin aluminium heat-sink, copper base and three copper heatpipes.

Compatibility:

Intel Core 2 Extreme (Socket LGA 775)
Intel Core 2 Quad (Socket LGA 775)
Intel Core 2 Duo (Socket LGA 775)
Intel Pentium Extreme (Socket LGA 775)
Intel Pentium D (Socket LGA 775)
Intel Pentium 4 (Socket LGA 775)
Intel Celeron D (Socket LGA 775)

Model	RCX-Z2
Heatsink Material	Aluminum fin, Copper base and three heatpipes.
Fan Size	7 blades 80mm reverse ball bearing cooler
Bearing Type	Ball
RPM	500 - 3400 \pm 10% RPM
Air Flow	Up to 44.264 CFM
Noise Level	17 - 34.2 dB(A)
LED Light	Special 4 Bright Blue LED on the fan core



RCX-Z775-EX

Other Features:

92mm two ball bearing long life fan for over 80000 hours
Powerful fan providing 46.2CFM and 2.9mm H2O max air flow

Compatibility :

Intel Core 2 Extreme (Socket LGA 775)
Intel Core 2 Quad (Socket LGA 775)
Intel Core 2 Duo (Socket LGA 775)
Intel Pentium Extreme (Socket LGA 775)
Intel Pentium D (Socket LGA 775)
Intel Pentium 4 (Socket LGA 775)
Intel Celeron D (Socket LGA 775)

Model	RCX-Z775-EX
Heatsink Material	Hi-grade aluminum fins, 3 embedded copper heatpipes and copper base
Fan Size	92mm
Bearing Type	2 Ball
RPM	800 - 2100 \pm 10% RPM
Air Flow	16.5 - 46.2 CFM
Noise Level	21 - 27.45 dBA



RCX-Z200

92mm ball bearing long life fan for over 45000 hours
Powerful fan providing 48.4CFM and 1.85mm H2O max air flow

20.25dBA hyper low noise

Huge dimension of aluminum fins and full copper base to increase the heat transfer

Easy installation for Intel 478 socket.

Model	RCX-Z200
Heatsink Material	Pure aluminum heatsink with full copper base
Fan Size	92mm
Bearing Type	Ball
RPM	2200 \pm 10% RPM
Air Flow	48.4 CFM
Noise Level	20.25 dBA

Cooling Device / CPU Cooler / Z Series for Intel

FEATURES

SPECIFICATIONS



RCX-Z5

Compatibility:

Intel Core 2 Extreme (Socket LGA 775)
 Intel Core 2 Quad (Socket LGA 775)
 Intel Core 2 Duo (Socket LGA775)
 Intel Pentium Extreme (Socket LGA 775)
 Intel Pentium D (Socket LGA 775)
 Intel Pentium 4 (Socket LGA775)
 Intel Celeron D (Socket LGA775)
 AMD Athlon 64 FX (Socket 754, 939, AM2)
 AMD Athlon 64 X2 (Socket 754, 939, AM2)
 AMD Athlon 64 (Socket 754, 939, AM2)
 AMD Opteron (Socket 754, 939, AM2)

Model	RCX-Z5
Heatsink Material	Hi-grade aluminum fins, 4 embedded copper heat pipes and copper base
Fan Size	92mm
Bearing Type	Two Ball Bearing / FDBB
RPM	800-2400 \pm 10% RPM
Air Flow	Max 47 CFM
Noise Level	Max 23 dB(A)



RCX-Z5-Ultra

Compatibility:

Intel Core 2 Extreme (Socket LGA 775)
 Intel Core 2 Quad (Socket LGA 775)
 Intel Core 2 Duo (Socket LGA775)
 Intel Pentium Extreme (Socket LGA 775)
 Intel Pentium D (Socket LGA 775)
 Intel Pentium 4 (Socket LGA775)
 Intel Celeron D (Socket LGA775)
 AMD Athlon 64 FX (Socket 754, 939, AM2)
 AMD Athlon 64 x 2 (Socket 754, 939, AM2)
 AMD Opteron (Socket 754, 939, AM2)
 AMD Sempron (Socket 754, 939, AM2)

Model	RCX-Z5-Ultra
Heatsink Material	Hi-grade aluminum fins, 4 embedded copper heat pipes and copper base
Fan Size	92mm x 2
Bearing Type	Two Ball + Long Life Sleeve
RPM	800-2400 \pm 10% RPM + 1200 \pm 10% RPM
Air Flow	Max 47 CFM
Noise Level	Max 21 dB(A)



RCX-Z775-EX

Compatibility:

Intel Core 2 Extreme (Socket LGA 775)
 Intel Core 2 Quad (Socket LGA 775)
 Intel Core 2 Duo (Socket LGA 775)
 Intel Pentium Extreme (Socket LGA 775)
 Intel Pentium D (Socket LGA 775)
 Intel Pentium 4 (Socket LGA 775)
 Intel Celeron D (Socket LGA 775)

Model	RCX-Z775-EX
Heatsink Material	Hi-grade aluminum fins, 3 embedded copper heatpipes and copper base
Fan Size	92mm
Bearing Type	2 Ball
RPM	800 - 2100 \pm 10% RPM
Air Flow	16.5 - 46.2 CFM
Noise Level	21 - 27.45 dBA

/ Cooling Device / Case Fans



RFX-100

Black body and silver bracket exhaust system blower.
 Lo-noise of 25.24dBA that extracts hot air from the case.
 Huge air flow of 35.12 CFM Max.
 It occupies 1 PCI slot space.
 Use 4 pin power adapter.

Model	RFX-100
Compatibility	PCI Slot
Fan Size	90mm
RPM	2000 RPM
Air Flow	35.12 CFM
Noise Level	25.24 dBA
Color	Black



RFX-100B

Cool blue UV reactive exhaust system blower.
 Lo-noise of 25.24dBA that extracts hot air from the case.
 Huge air flow of 35.12 CFM Max.
 It occupies 1 PCI slot space.
 Use 4 pin power adapter.

Model	RFX-100B
Compatibility	PCI Slot
Fan Size	90mm
RPM	2000 RPM
Air Flow	35.12 CFM
Noise Level	25.24 dBA
Color	Blue

Cooling Device / Case Fan

FEATURES

SPECIFICATIONS



RFX-80

High Performance:
Operating at 1800-3000 RPM, the Rosewill RFX-80 delivers strong air flow of up to 38.08 CFM for impressive levels of heat dissipation.

Adjustable Fan Speed
A bundled fan speed controller enables control of noise and fan speed for exceptional cooling and quietness.

Model	RFX-80
Compatibility	Case
Fan Size	80mm
Bearing Type	2 Ball
RPM	1800-3000 RPM
Air Flow	23.38-38.08 CFM; 1.18-2.18mm H2O Max control by fan controller bracket
Noise Level	19.85-32.31 dBA Max
Color	Black with red blades



RFX-120

High Performance
Operating at 1200~2000 RPM, this 120mm fan delivers an air flow of up to 87.5 CFM for near peerless heat dissipation!

Adjustable Fan Speed
A bundled fan speed controller enables control of noise and fan speed for exceptional cooling and quietness.


Model	RFX-120
Compatibility	Case
Fan Size	120mm
Bearing Type	2 Ball
RPM	1200-2200 RPM
Air Flow	43.5-87.5 CFM; 1.4~3.9 mm H2O Max
Noise Level	23.5-38.15 dBA Max
Color	Black with red blades



RFX-80BL

Blue LEDs implemented for bright glowing result

Model	RFX-80BL
Compatibility	Case
Fan Size	80mm
Bearing Type	2 Ball
RPM	1700 - 3000 RPM
Air Flow	23.38 - 41.8 CFM
Noise Level	19.25 - 29 dBA
Color	Transparent



RFX-120BL

Blue LEDs implemented for bright glowing result

Model	RFX-120BL
Compatibility	Case
Fan Size	120mm
Bearing Type	2 Ball
RPM	1200 - 2200 RPM
Air Flow	43.5 - 87.5 CFM
Noise Level	23.5 - 38.15 dBA
Color	Transparent



RFA-80-K

Delivers superior performance that keeps power usage and noise level at it's lowest

Model	RFA-80-K
Compatibility	Case
Fan Size	80mm
Bearing Type	Sleeve
RPM	2500 RPM
Air Flow	33.21 CFM
Noise Level	22.41 dBA
Color	Black

Cooling Device / Case Fans

FEATURES

SPECIFICATIONS



RFA-80-BL

4 Blue LEDs implemented for bright glowing result

Model	RFA-80-BL
Compatibility	Case
Fan Size	80mm
Bearing Type	Sleeve
RPM	2500 RPM
Air Flow	33.21 CFM
Noise Level	22.41 dBA
Color	Black



RFA-80-RL

4 Red LEDs implemented for bright glowing result

Model	RFA-80-RL
Compatibility	Case
Fan Size	80mm
Bearing Type	Sleeve
RPM	2500 RPM
Air Flow	33.21 CFM
Noise Level	22.41 dBA
Color	Red



RFA-80-WL

4 White LEDs implemented for bright glowing result

Model	RFA-80-WL
Compatibility	Case
Fan Size	80mm
Bearing Type	Sleeve
RPM	2500 RPM
Air Flow	33.21 CFM
Noise Level	22.41 dBA
Color	Transparent



RFA-120-K

Delivers superior performance that keeps power usage and noise level at it's lowest

Model	RFA-120-K
Compatibility	Case
Fan Size	120mm
Bearing Type	Sleeve
RPM	2000 RPM
Air Flow	74.48 CFM
Noise Level	29.28 dBA
Color	Black



RFA-120-BL

4 Blue LEDs implemented for bright glowing result

Model	RFA-120-BL
Compatibility	Case
Fan Size	120mm
Bearing Type	Sleeve
RPM	2000 RPM
Air Flow	74.48 CFM
Noise Level	29.28 dBA
Color	Blue

Cooling Device / Case Fan

FEATURES

SPECIFICATIONS



RFA-120-RL

4 Red LEDs implemented for bright glowing result

Model	RFA-120-RL
Compatibility	Case
Fan Size	120mm
Bearing Type	Sleeve
RPM	2000 RPM
Air Flow	74.48 CFM
Noise Level	29.28 dBA
Color	Red



RFA-120-WL

4 White LEDs implemented for bright glowing result

Model	RFA-120-WL
Compatibility	Case
Fan Size	120mm
Bearing Type	Sleeve
RPM	2000 RPM
Air Flow	74.48 CFM
Noise Level	29.28 dBA
Color	Transparent

USB Hub / 4 Ports USB Hub

FEATURES

SPECIFICATIONS



RHB-220

Backward Compatible with USB 1.1.
For bus -powered mode, the USB provide 500mA for all downstream & hub.
Plug the A-type connector into the PC host port.
Connect USB devices to the Hub downstream 1-4.
This USB HUB is a 4-port device used to bridge the USB interfaced peripherals to your desktop or laptop by providing four downstream ports. This device complies with USB Spec. V1.1 and V2.0. It offers you the flexibility of 3 data rates. The 12Mbps (full speed), 1.5Mbps (low-speed) and 480Mbps for high-speed device.

Model	RHB-220
Type	USB
Standards	USB 2.0/1.1
Ports	1 x Type-A Upstream, 4 xType-A Downstream
Transfer Rate	1.5/12/480Mbps
Power Input	5V DC
OS Support	Win 98SE /Me / 2000 / XP / Vista, Linux, MAC OS 8.6 or above/OS x.



RHUB-210

40 Times Faster Than The USB 1.1
Four Independent, Fully Functional, Downstream Ports
Hot Swappable Plug-n-Play
PC Power Management
Compatible with Windows 98SE, 2000, ME, XP, Vista
32/64bit
Mac OS 8.6 to 9.x, Mac OS X or greater

Model	RHUB-210
Chipset	NEC 101
Bus Interface	USB 2.0
Connectors	4 x Typa A USB ports
Accessories	1 x Manual, 1 x USB Cable, AC Power Adapter
Data Transfer Rate	1.5/12/480Mbps
Power Supply	5V,2A
OS Supports	PC:Windows 98SE, 2000, ME, XP, Vista 32/64bit , Mac:Mac OS 8.6 to 9.x, Mac OS X or greater

/ USB Hub / 7 Ports USB Hub



RHB-320W

Compliant with USB Specification Rev. 2.0 (Data Rate 1.5/12/480 Mbps)
Backward Compatible to USB 1.1
7 (Max.) downstream facing parts high-speed (480Mbps), full-speed(12Mbps), and low-speed (1.5Mbps) transaction.
Supports self-powered mode & Switching Adapter.
Plug & play and Hot Swapping

Model	RHB-320W
Color	White
Type	USB
Standards	USB 2.0/1.1
Ports	1 x Upstream, 7 x Downstream
Transfer Rate	1.5/12/480Mbps
Power Input	5V,2A (Using USB bus-powered)



RHB-320

Compliant with USB Specification Rev. 2.0 (Data Rate 1.5/12/480 Mbps)
Backward Compatible to USB 1.1
7 (Max.) downstream facing parts high-speed (480Mbps), full-speed(12Mbps), and low-speed (1.5Mbps) transaction.
Supports self-powered mode & Switching Adapter.
Plug & play and Hot Swapping

Model	RHB-320
Color	Black
Type	USB
Standards	USB 2.0/1.1
Ports	1 x Upstream, 7 x Downstream
Transfer Rate	1.5/12/480Mbps
Power Input	5V,2A (Using USB bus-powered)



RHB-320R

Compliant with USB Specification Rev. 2.0 (Data Rate 1.5/12/480 Mbps)
Backward Compatible to USB 1.1
7 (Max.) downstream facing parts high-speed (480Mbps), full-speed(12Mbps), and low-speed (1.5Mbps) transaction.
Supports self-powered mode & Switching Adapter.
Plug & play and Hot Swapping

Model	RHB-320R
Color	Red
Type	USB
Standards	USB 2.0/1.1
Ports	1 x Upstream, 7 x Downstream
Transfer Rate	1.5/12/480Mbps
Power Input	5V,2A (Using USB bus-powered)

USB Hub / USB Hub / 7 Ports USB Hub

FEATURES

SPECIFICATIONS



RHUB-310W

Compliant with USB Specification Rev. 2.0 (Data Rate 1.5/12/480 Mbps)
 Backward Compatible to USB 1.1
 7 (Max.) downstream facing ports high-speed (480Mbps), full-speed (12Mbps), and low-speed (1.5Mbps) transaction.
 Supports self-powered mode & DC Adapter.
 Supports Over-current detection and individual power control.
 Compatible with Windows 98se, windows me, windows 2000, windows XP & windows VISTA
 -Mac OS 8.6 + -Linux

Model	RHUB-310W
Color	Black & White
Power Mode	Self-power mode / DC adaptor
USB Connectors	A-type downstream*7, mini B-type upstream*1
Data Transfer Rate	1.5/12/480Mbps
OCP	Yes, (USB 500 mA)
Power Supply	5V, 2A
Dimension	94.5X45.5X15.5mm w/out stand 50X50X103mm w/ stand



RHUB-310R

Compliant with USB Specification Rev. 2.0 (Data Rate 1.5/12/480 Mbps)
 Backward Compatible to USB 1.1
 7 (Max.) downstream facing ports high-speed (480Mbps), full-speed (12Mbps), and low-speed (1.5Mbps) transaction.
 Supports self-powered mode & DC Adapter.
 Supports Over-current detection and individual power control.
 Compatible with Windows 98se, windows me, windows 2000, windows XP & windows VISTA
 -Mac OS 8.6 + -Linux

Model	RHUB-310R
Color	Red
Power Mode	Self-power mode / DC adaptor
USB Connectors	A-type downstream*7, mini B-type upstream*1
Data Transfer Rate	1.5/12/480Mbps
OCP	Yes, (USB 500 mA)
Power Supply	5V, 2A
Dimension	94.5X45.5X15.5mm w/out stand 50X50X103mm w/ stand



RHUB-310

Compliant with USB Specification Rev. 2.0 (Data Rate 1.5/12/480 Mbps)
 Backward Compatible to USB 1.1
 7 (Max.) downstream facing ports high-speed (480Mbps), full-speed (12Mbps), and low-speed (1.5Mbps) transaction.
 Supports self-powered mode & DC Adapter.
 Supports Over-current detection and individual power control.
 Compatible with Windows 98se, windows me, windows 2000, windows XP & windows VISTA
 -Mac OS 8.6 + -Linux

Model	RHUB-310
Color	Black
Power Mode	Self-power mode / DC adaptor
USB Connectors	A-type downstream*7, mini B-type upstream*1
Data Transfer Rate	1.5/12/480Mbps
OCP	Yes, (USB 500 mA)
Power Supply	5V, 2A
Dimension	94.5X45.5X15.5mm w/out stand 50X50X103mm w/ stand



RHUB-300

40 Times Faster Than The USB 1.1
 Seven Independent, Fully Functional, Downstream Ports
 Hot Swappable Plug-n-Play
 Power & USB enabled indicator LED
 No device drivers required for Hub installation
 Compatible with Windows 98SE, 2000, ME, XP, Vista
 32/64bit
 Mac OS 8.6 to 9.x, Mac OS X or greater

Model	RHUB-300
Color	Black
Type	USB
Standards	USB2.0/1.1
Ports	1 x Upstream, 7 x Downstream
Transfer Rate	480Mbps
Dimension	100x67x25mm (without power adapter)
Weight	80g, Power Adapter 560g
Color	Black
Data Transfer Rate	1.5/12/480Mbps
Power Supply	5V, 2A

PC Tool Kits

FEATURES

SPECIFICATIONS



RTK-090

The 90-Piece Professional Computer Tool Kit provides you with everything needed to fix and upgrade electronic devices.

All tools are demagnetized to prevent systems and magnetic media from damage.

Model RTK-090

Reversible Ratchet Driver with 50-Piece Bit & Socket Set

- 3 Way Ratchet Handle
- 6 Precision Screwdriver Set
- 4 Electronic Combination Wrench Set
- 4 1/2" Side Cutter
- 5" Long Nose Pliers
- 5" Wire Cutter / Stripper
- Black Zipper Case

For complete specs go to: www.rosewill.com



RTK-008

The 8-Piece Professional Networking Tool Kit provides you with everything needed to fix and upgrade Networking devices.

Model RTK-008

Plug Boots (Red x 4, Blue x 4, Black x 4, White x 4)

Modular Plugs (8P x 6, 6P x 13)

RJ11/RJ45 Cable Tester, Cable Stripper

Screwdriver with Bits

- Flat Bit
- Phillips Bit
- Screwdriver Handle
- Punch Down Tool (110/88)
- Ratchet Crimper



RTK-015

The 15-Piece Standard Computer Tool Kit is designed with all essential tools needed to fix and upgrade electronic devices.

All tools are demagnetized to prevent systems and magnetic media from damage.

Model RTK-015

- Screwdriver

- Reversible Screwdriver

- Reversible Screwdriver Handle

- Nut Driver

- Cable Tie: 10 PCS

- IC Insertion-Extraction Clipper

- Tweezers

- Black Zipper Case

For complete specs go to: www.rosewill.com



RTK-025

The 25-Piece Premium Computer Tool Kit is designed with the most popular tools needed to fix and upgrade electronic devices.

All tools are demagnetized to prevent systems and magnetic media from damage.

Model RTK-025

1. Long nose pliers 4.5"

2. Diagonal pliers 4.5"

3. Tweezers

4. 1/4" sockets (1/4":4-6-8-10mm)

5. Screwdriver bit

6. Extension bar 1/4"x3"

7. Bit holder

8. Mini screwdrivers Ph #1, #0, (-) 1.4, 2.0, 2.4, 3.0

9. Zipper bag



RTK-045

The 45-Piece Premium Computer Tool Kit is designed with the most popular tools needed to fix and upgrade electronic devices.

All tools are demagnetized to prevent systems and magnetic media from damage.

Model RTK-045

Reversible Ratchet Driver with 21-Piece Bit & Socket Set

- Ratchet Handle

- 6" #1 Phillips Screwdriver

- Reversible 1/8" & #0 Mini Screwdriver (With Pocket Chip)

- 9 Hex Key Set:

- 5" Long Nose Pliers

- 5" Wire Cutter / Stripper

- Black Zipper Case

For complete specs go to: www.rosewill.com

PC Tool Kits

FEATURES

SPECIFICATIONS



RTK-010

Workstation Repair Tool Kit allows you to perform all of the basic repairs on computers and workstations

Model RTK-010

- 6" Precision Wire Stripper
- 3pcs Soldering Aid Set
- Stainless Steel Tweezers
- 5" Stainless Steel Long Nose Plier
- Screwdrivers
- 6pcs Precision Screwdriver Set
- 10pcs Mini Electronic Combination Wrench Set
- PU Carrying Case

For complete specs go to: www.rosewill.com



RTK-011

Rosewill Field Service Engineer Tool Kit is designed for a wide range of electronic equipment and is very popular with service engineers.

Model RTK-011

- Soldering Iron
- Solder Core
- 5" Side Cutter Plier
- 6" Long Nose Plier
- 6" Line's Man Plier
- 10pcs Mini Electronic Combination Wrench Set
- Electrical Test Screwdriver
- 6pcs Precision Screwdriver Set

For complete specs go to: www.rosewill.com



RTK-009

Workstation Repair Tool Kit allows you to perform all of the basic repairs on computers or electronic devices

Model RTK-009

- 5" Long Nose Plier
- Micro Cutting Plier
- Cable Stripper
- Solder Core
- 6" Precision Wire Stripper
- Utility Knife
- Tweezers
- 6 pcs Precision Screwdriver set

For complete specs go to: www.rosewill.com



RTK-145

The 145-Piece Standard Computer Tool Kit is designed with more than the essential tools needed to fix and upgrade computer or electronic devices.

Model RTK-145

- Reversible ratch handle- 33 Pcs security bit group
- 5" Long nose pliers
- 6 pcs. Precision screwdriver set
- 4 1/2" Side Cutter
- Phillips screwdriver bit
- 5 pcs. socket
- 45 pcs. terminals
- Vacuum cleaner

For complete specs go to: www.rosewill.com

Other Tools

FEATURES

SPECIFICATIONS



RTK-002

Protect Your PC from Static Electricity
Adjustable Strap Fits Your Wrist Comfortably
Extra-long Coiled Cord for Wide Range of Movement

Model RTK-002
Resistance: <10K Ohm (Wrist Strap)
1M Ohm \pm 10% (Cord)
Length of Grounding Cord: 6 Feet



RTK-006

Verify cable continuity easily.
Features with auto or manual scan for pin-out indicators
Can test the correct pin configuration of 10Base-T, 10Base-2 Ethernet, RJ11/RJ45 modular cables, 258A, TIA-568A/568B cables
Test the cable 1,000 feet away that are on wall plate or patch cable with remote kit (remote kit included)
Test the grounding.
Power switch for saving battery power.
One year warranty

Model RTK-006
Powered by: one 9V battery (not included)
Electrical consumption: 25mA
Dimensions: 100mm \times 105mm \times 2.9mm (3.9" \times 4.1" \times 1.1")
Weight: 165g



RTT-001

Dual Instant Temperature Detecting
Accurate Dual Thermal Sensors
Super Backlight LCD Monitor
Fancy Silver Laser Faceplate
Wide Range Application
Long Lifetime Lithium Battery
Power Saving Design
Accessories
Thermal sensor : 1 set, Length x 1 M
Tape : 16.0 x 10.0 mm x 2 pcs
Velcro tape : 42.0 x 34.0 x 1 pc

Model RTT-001
Dimensions : 78.0 x 42.0 x 13.0mm
Detecting Range : 0 ~ 120 °C / 32 ~ 248° F
Monitor : Backlight LCD
Battery : CR2032
Weight : 30g



RTK-T05

Test 5 types of cables (RJ-45/RJ-11/BNC/USB/1394)
Simple one button tester
Ergonomic portable handheld design
Tests installed wiring or patch cables
Remote unit stores in Main unit
600 ft tester distance (RJ-45/RJ-11/BNC)
Convenient battery access
LEDs indicate connections and faults
Beeper provides audible annunciation of tester results
Tests shielded (STP) or unshielded (UTP) LAN cables
Test shields in 1394 and USB cables

Model RTK-T05
Cable Tested
(a) UTP and STP LAN cables Terminated in RJ-45 male connectors. (EIA/TIA 568)
(b) RJ-11 Cables with male connectors, 2 to 6 conductors installed.
(c) 1394 cables with type 1 plugs on both ends.
(d) USB cable with Type 1 flat plug on one end and type B square plug on other end.
(e) BNC cables with male connectors.
Faults Indicated: No connection, Short, Open, Cross.



RTK-001

Protect Your PC from Static Electricity
Adjustable Strap Fits Your Wrist Comfortably
Extra-long Coiled Cord For Wide Range of Movement
Suitable for Clean Room

Model RTK-001
Specifications:
Material: T.P.R. Plastic
Application: Class 100 - 1000 (Clean Room)
Molding: Snap and Plug-PVC Molding
Resistance:
1K- 100K Ohm (Wrist Strap)
1 \pm 10% M Ohm (Cord)
Length of Grounding Cord: 6 Feet

Other Tools

FEATURES

SPECIFICATIONS



RTK-T05

- For 8P/RJ-45 and 6P/RJ-12, RJ-11
- Built-in cutter and stripper for flat cable
- Ratchet mechanism
- Comfortable dual-color handle

Model RTK-005
 Body : S45C (HRC 45±3)
 Handle : Gray=PP, Black=TPR
 Application: 8P/RJ-45 and 6P/RJ-12, RJ-11



RTK-007

Verify cable continuity, open, short and miss-wire easily.
 Features with auto or manual scan for pin-out indicators
 Can test the correct pin configuration of 10Base-T, 10Base-2 Ethernet, RJ-11/RJ-12/RJ-45 modular cables, 258A, TIA-568A/568B, and Token Ring cables
 Test the cable 1,000 feet away that are on wall plate or patch cable with remote kit (remote kit included)
 Test the grounding.
 Power switch for saving battery power.
 One year warranty

Model RTK-007
 Powered by: one 9V battery (not included)
 Electrical consumption: 22mA
 Dimensions:
 Main: 104mm × 63mm × 29mm (4.1" × 2.5" × 1.1")
 Remote: 104mm × 30.5mm × 29mm (4.1" × 1.2" × 1.1")
 Weight: 195g(Kit) / 45g(Remote)



RTK-004

RTK-004 is a professional punch down/termination tool with 110/88 and 66 blades that enable installers to make reliable connections on a variety of wire termination blocks. A simple push on the handle inserts and cuts termination in one operation. Adjustable high/low actuation setting accommodates termination requirements. A spare blade can be kept in a storage chamber in the handle.

Model RTK-004
 Material: Blade: SAE4140 (HRC 45),
 Body: ABS
 Application: For seating wire into terminal blocks or cut off wire end after terminated.
 Hi-low adjust pressure (Hi: 15±2kg, Low: 10±2kg)
 Blade Type: 110/88 and 66
 Overall Length: 146mm (w/o Blade)
 Weight: 180g

Thermal Grease

FEATURES

SPECIFICATIONS



RCX-TC050

Designed for high-powered systems and the heat they generate. Ideal for CPUs and other PC components

Model

RCX-TC050

Specifications

Color: Gray
 Viscosity: Non-flowing
 Thermal Conductivity: 9.24 W/mK
 Operating Temperature: 0 ~ 200 °C
 Volume: 5g (0.01 lbs.)



RCX-TC001

Designed for high-powered systems and the heat they generate. Ideal for CPUs and other PC components

Model

RCX-TC001

Specifications

Color: Gray
 Viscosity: 76cPs
 Thermal Conductivity: 2.4 W/mK
 Operating Temperature: -45 ~ 240°C
 Volume: 5g (0.01 lbs.)



RCX-TC060

Nano Silver
 Instant Conductivity
 Ultimate Performance

Model

RCX-TC060

Thermal Conductivity

> 9.24 W/mK

Specific Resistance

> 2.5

Operating Temp.

-50°C~240°C

Weight

6g

ATX Mid Tower

FEATURES

SPECIFICATIONS



TU-155

Ideal for high performance Intel & AMD Systems
20+4Pin main connector power supply with SATA connector
X shape clear side panel
Lighted blue power switch
Thermally optimized for Prescott & Athlon 64 processors
Advanced air guide design
USB/audio ports accessible from front to front USB/audio ports accessible
Virtually tool-less for 5.25" easy assembly

Model	TU-155
Type	ATX Mid Tower
Color	Black
Case Material	0.8mm SGCC Steel
With Power Supply	Yes
Power Supply	400W ATX12V Version 2.2
Motherboard Compat.	Micro ATX, ATX size up to 12.5" x 10.5"
Cooling System	1 x 80mm Blue LED Rear Fan
Front Ports	USB, HD&AC97, 1394
Dimensions	8.4" x 8.2" x 17.2" (Bezel Not Included)
Weight	24 lbs.



R103A

Sturdy construction with steel
Ease of serviceability & upgrade
Virtually tool-less, precise & easy assembly

Model	R103A
Type	ATX Mid Tower
Color	Black
Case Material	SGCC Steel
With Power Supply	Yes
Power Supply	350W
Motherboard Compat.	ATX/ m-ATX
Front Ports	2 x USB 2.0 Ports
Dimensions	18." x 8" x 16" (Bezel Not Included)



R804BK

Ideal for Intel & AMD Systems
Advanced Air Guide design
PCI Vent Holes
USB and Audio Ports accessible from front
Total of 10 drive bays(4+2+4)
Ease of serviceability & upgrade

Model	R804BK
Type	ATX Mid Tower
Color	Black
Case Material	SECC Cold Rolled Steel
With Power Supply	Yes
Power Supply	350W ATX 12V Power Supply
Motherboard Compat.	Micro ATX, ATX
Cooling System	1 x 80mm Rear Fan
Front Ports	2 x USB/ 2 Audio (AC97 & HD plugs)
Dimensions	7.5" x 16.3" x 16.75" (W x H x D)



R805BS

Ideal for Intel & AMD Systems
Advanced Air Guide design
PCI Vent Holes
USB and Audio Ports accessible from front
Total of 10 drive bays(4+2+4)
Ease of serviceability & upgrade

Model	R805BS
Type	ATX Mid Tower
Color	Black / Silver
Case Material	SECC Cold Rolled Steel
With Power Supply	Yes
Power Supply	350W ATX 12V Power Supply
Motherboard Compat.	Micro ATX, ATX
Cooling System	1 x 80mm Rear Fan
Front Ports	2 x USB/ 2 Audio (AC97 & HD plugs)
Dimensions	7.5" x 16.3" x 16.75" (W x H x D)



R604TBLK-N

Ideal for Intel & AMD Systems
Advanced Air Guide design
PCI Vent Holes
USB and Audio Ports accessible from front
Total of 10 drive bays(4+2+4)
Ease of serviceability & upgrade

Model	R604TBLK-N
Type	ATX Mid Tower
Color	Black / Silver
Case Material	0.6mm SECC Steel
With Power Supply	Yes
Power Supply	450W Dual Fan Power supply
Motherboard Compat.	Micro ATX, ATX
Cooling System	1 x 120mm Rear Fan
Front Ports	2 x USB 2.0 Ports, 2 x Audio Ports
Dimensions	18.6" x 17.0" x 8.0"

ATX Mid Tower

FEATURES

SPECIFICATIONS



R604TSB-N

Thermally Advantaged Chassis for high performance Intel & AMD Systems
 Advantaged Air Guide & PCI express venting Hole (CAG 1.1)
 Easy-Clean Air Filter in front panel
 Tool-Free Kit for easy installation of 5.25" & 3.5" devices
 Vertical sliding HDD cage
 1x 120mm Rear Fan
 Front I/O Ports (2 x USB, 2 x Audio)
 Smooth edges to provide greater safety for users

Model	R604TSB-N
Type	ATX Mid Tower
Color	Black / Silver
Case Material	0.6mm SECC Steel
With Power Supply	Yes
Power Supply	450W Dual Fan Power supply
Motherboard Compat.	Micro ATX, ATX
Cooling System	1 x 120mm Rear Fan
Front Ports	2 x USB 2.0 Ports, 2 x Audio Ports
Dimensions	7.1" x 16.2" x 18.6 (W x H x D) (Bezel Not Included)



R5604

Thermally Advantaged Chassis for high performance Intel & AMD Systems
 Easy-clean Filters in left side panel and front panel
 Advantaged Air Guide & PCI express venting Hole (CAG 1.1)
 Sliding rail design for easy installation of 5.25" device & HDD
 Screw-less add on cards assembly
 No screws needed to secure the left side panel
 Lockable left side panel, Smooth edges to provide greater safety for users
 Accessory Box

Model	R5604
Type	ATX Mid Tower
Color	Black
Case Material	0.8mm Japanese Cold Rolled Steel
With Power Supply	No
Motherboard Compat.	Standard ATX / Micro ATX
Cooling System	1 x 120mm Rear Fan, 1 x 120mm Front Fan
Front Ports	USB,HD&AC97,IEEE1394
Dimensions	7.9" x 17.3" x 19.4" (W x H x D) (Bezel Not Included)



R5604-BK

Thermally Advantaged Chassis for high performance Intel & AMD Systems
 Easy-clean Filters in left side panel and front panel
 Advantaged Air Guide & PCI express venting Hole (CAG 1.1)
 Sliding rail design for easy installation of 5.25" device & HDD. Screw-less add on cards assembly
 No screws needed to secure the left side panel
 Lockable left side panel
 Smooth edges to provide greater safety for users
 Accessory Box

Model	R5604-BK
Type	ATX Mid Tower
Color	Black / Silver
Case Material	0.8mm Japanese Cold Rolled Steel
With Power Supply	No
Motherboard Compat.	Standard ATX / Micro ATX
Cooling System	2x 120mm Rear/Front Fan
Front Ports	USB,HD&AC97,IEEE1394
Dimensions	7.9" x 17.3" x 19.4" (W x H x D) (Bezel Not Included)



R5604-BK

Thermally Advantaged Chassis for high performance Intel & AMD Systems
 Easy-clean Filters in left side panel and front panel
 Advantaged Air Guide & PCI express venting Hole (CAG 1.1)
 Sliding rail design for easy installation of 5.25" device & HDD. Screw-less add on cards assembly
 No screws needed to secure the left side panel
 Lockable left side panel. Smooth edges to provide greater safety for users
 Door opening angel up to 270 degrees
 Adjustable Air Inflow. Accessory Box

Model	R5601-BK
Type	ATX Mid Tower
Color	Black
Case Material	0.8mm Japanese Cold Rolled Steel
With Power Supply	No
Motherboard Compat.	Standard ATX / Micro ATX
Cooling System	2x 1 x 120mm Front/Rear Fan
Front Ports	USB,HD&AC97,IEEE1394
Dimensions	7.9" x 17.3" x 19.4" (W x H x D) (Bezel Not Included)



R5717 SL

Thermally Advantaged Chassis for high performance Intel & AMD Systems
 Advantaged Air Guide & PCI express venting Hole (CAG 1.1)
 Easy-Clean Air Filter in front panel
 Tool-Free Kit for easy installation of 5.25" & 3.5" devices
 Vertical sliding HDD cage
 1x 120mm Rear Fan
 Front I/O Ports (2 x USB, 2 x Audio)
 Smooth edges to provide greater safety for users

Model	R5717 SL
Type	ATX Mid Tower
Color	Black / Silver
Case Material	0.7mm SECC Steel
With Power Supply	Yes
Power Supply	450W
Motherboard Compat.	Micro ATX, ATX
Cooling System	1 x 120mm Rear Fan
Front Ports	2 x USB 2.0 Ports, 2 x Audio Ports
Dimensions	7.6" x 16.2" x 18.6 (W x H x D) (Bezel Not Included)

ATX Mid Tower

FEATURES

SPECIFICATIONS



R5717-P BK

Thermally Advantaged Chassis for high performance Intel & AMD Systems
 Advantaged Air Guide & PCI express venting Hole (CAG 1.1). Easy-Clean Air Filter in front panel
 Sliding rail design for easy installation of 5.25" device and Sliding 3.5" cage
 Vertical sliding HDD cage
 1x 120mm Rear Fan
 Front I/O Ports (2x USB, 2x Audio) Smooth edges to provide greater safety for users

Model	R5717-P BK
Type	ATX Mid Tower
Color	Black
Case Material	0.7mm SECC Steel
With Power Supply	No
Motherboard Compat.	Micro ATX, ATX
Cooling System	1 x 120mm Rear Fan
Front Ports	2 x USB 2.0 Ports, 2 x Audio Ports
Dimensions	7.6" x 16.2" x 18.6 (W x H x D) (Bezel Not Included)



R5717-P SL

Thermally Advantaged Chassis for high performance Intel & AMD Systems
 Advantaged Air Guide & PCI express venting Hole (CAG 1.1)
 Easy-Clean Air Filter in front panel
 Sliding rail design for easy installation of 5.25" device
 Vertical sliding HDD cage
 Extreme Cooling: 3 x 120mm Fan + 1x 80mm Fan
 Front I/O Ports (2x USB, 2x Audio - AC97 & HD Audio)
 Smooth edges to provide greater safety for users

Model	R5717-P SL
Type	ATX Mid Tower
Color	Silver/Grey
Case Material	0.7mm SECC Steel
With Power Supply	No
Motherboard Compat.	Micro ATX, ATX
Cooling System	1 x 80mm Slim Fan (Side) for HDD 1 x 120mm Rear/ 1 x 120mm Front/ 1 x 120mm Top Fan
Front Ports	2 x USB 2.0 Ports, 2 x Audio Ports
Dimensions	8" x 17" x 18.5" (W x H x D)



R604-P BK

Thermally Advantaged Chassis for high performance Intel & AMD Systems
 Advantaged Air Guide & PCI express venting Hole (CAG 1.1)
 Easy-Clean Air Filter in front panel
 Tool-Free Kit for easy installation of 5.25" & 3.5" devices
 Vertical sliding HDD cage
 Smooth edges to provide greater safety for users

Model	R604-P BK
Type	ATX Mid Tower
Color	Black
Case Material	0.6mm SECC Steel
With Power Supply	No
Motherboard Compat.	Micro ATX, ATX
Cooling System	1 x 120mm Rear Fan
Front Ports	2 x USB 2.0 Ports, 2 x Audio Ports
Dimensions	7.1" x 16.2" x 18.6 (W x H x D) (Bezel Not Included)



R6426-P BK

Ideal for Intel & AMD Systems
 Advanced air guide design

Model	R6426-P BK
Type	ATX Mid Tower
Color	Black
Case Material	SGCC Steel
With Power Supply	No
Motherboard Compat.	Micro ATX, ATX
Cooling System	1 x 120mm Rear Fan
Front Ports	2 x USB 2.0 Ports, 2 x Audio Ports
Dimensions	7.1" x 16.2" x 18.6" (W x H x D)



R218-P-BK

Ideal for Intel & AMD Systems
 Advanced air guide design
 PCI-E venting Hole

Model	R218-P-BK
Type	ATX Mid Tower
Color	Black
Case Material	0.5mm SECC Steel
With Power Supply	No
Motherboard Compat.	Micro ATX, ATX
Cooling System	1 x 120mm Rear Fan
Front Ports	USB, Audio
Dimensions	7.5" x 16.3" x 17.5" (W x H x D) (Bezel Not Included)

ATX Mid Tower

FEATURES

SPECIFICATIONS



R220-P-BK

Ideal for Intel & AMD Systems
Advanced air guide design
PCI-E venting Hole

Model	R220-P-BK
Type	ATX Mid Tower
Color	Black
Case Material	0.5mm SECC Steel
With Power Supply	No
Motherboard Compat.	Micro ATX, ATX
Cooling System	1 x 120mm Rear Fan
Front Ports	USB, Audio
Dimensions	7.5" x 16.3" x 17.5" (W x H x D) (Bezel Not Included)



R230-P-BK

Ideal for Intel & AMD Systems
Advanced air guide design
PCI-E venting Hole

Model	R230-P-BK
Type	ATX Mid Tower
Color	Black
Case Material	0.5mm SECC Steel
With Power Supply	No
Motherboard Compat.	Micro ATX, ATX
Cooling System	1 x 120mm Rear Fan
Front Ports	USB, Audio
Dimensions	7.5" x 16.3" x 17.5" (W x H x D) (Bezel Not Included)



R5605-BK

Special mesh design provides the superior airflow and maximum cooling performance.
Easy assembly for quick maintain and upgrade.
Easy-clean Filters in left side panel and front panel
Sliding rail design for easy installation of 5.25" device & HDD
Screw-less add on cards assembly
No screws needed to secure the left side panel
Lockable left side panel
Smooth edges to provide greater safety for users

Model	R5605-BK
Type	ATX Mid Tower
Color	Black
Case Material	Sturdy Janpanese Cold Rolled Steel
With Power Supply	No
Motherboard Compat.	Micro ATX, ATX
Cooling System	1 x 120mm front fan, 1 x 120mm rear fan
Front Ports	USB,HD&AC97,IEEE1394
Dimensions	7.9" x 17.9" x 16.9" (W x H x D) (Bezel Not Included) 19.8" in Depth with Panel.



R891SL

Ideal for Intel & AMD Systems
Advanced Air Guide design
PCI Vent Holes
USB and Audio Ports accessible from front
Total of 10 drive bays(4+2+4)
Ease of serviceability & upgrade

350W ATX 12V Power Supply

Model	R891SL
Type	ATX Mid Tower
Color	Black/Silver
Case Material	SECC Cold Rolled Steel
With Power Supply	Yes
Motherboard Compat.	Micro ATX, ATX
Cooling System	1 x 80mm Rear Fan
Front Ports	2 x USB/ 2 Audio (AC97 & HD plugs)
Dimensions	7.5" x 16.3" x 16.75" (W x H x D).



R909SL

Ideal for Intel & AMD Systems
Advanced Air Guide design
PCI Vent Holes
USB and Audio Ports accessible from front
Total of 10 drive bays(4+2+4)
Ease of serviceability & upgrade

Model	R909SL
Type	ATX Mid Tower
Color	Black/Silver
Case Material	SECC Cold Rolled Steel
With Power Supply	Yes
Motherboard Compat.	Micro ATX, ATX
Cooling System	1 x 120mm Rear Fan
Front Ports	2 x USB/ 2 Audio (AC97 & HD plugs)
Dimensions	7.5" x 16.3" x 16.75" (W x H x D)
Power Supply	- ATX12V 350W with P4 support, 20+4 pin Main Connector & 1x SATA Connector

ATX Mid Tower

FEATURES

SPECIFICATIONS



R222-P-BK

Ideal for Intel® & AMD® Systems
 Advantaged Air Guide
 PCI express venting Hole
 1x 120mm Rear Fan
 Front I/O Ports (2x USB Port, Audio In/Out Port)

Model	R222-P-BK
Type	ATX Mid Tower
Color	Black
Case Material	Steel
With Power Supply	No
Motherboard Compat.	ATX
Cooling System	1 x 120mm Rear Fan
Front Ports	USB, Audio
Dimensions	7.5" x 16.3" x 16.75" (W x H x D)



RPS-01-W BK

Conqueror Series:
 Ideal for high performance Intel® & AMD® Systems
 Thermally optimized for Prescott® & AthlonT64 processors
 Modern, attractive front panel styling
 Mid-size tower chassis for all around integration
 Maximum air intake design-perforated front bezel.
 Two front loaded HDD cages for up to 6 hard disk drives
 Each HDD cage attached with 1x120mm blue LED fan acts as a air duct to take air in more efficiently for Hard drives, graphic card or CPU.
 Advanced cooling systems

Model	RPS-01-W BK
Type	ATX Mid Tower
Color	Black
Case Material	Steel
With Power Supply	No
Motherboard Compat.	Standard ATX ,Micro ATX
Cooling System	2 x 120mm blue LED intake front fans,1200rpm, 1 x 120mm Exhaust rear fan,1200rpm
Front Ports	USB, Audio, IEEE 1394
Dimensions	7.9" x 18" x 19.7(Bezel Not Included)



RPS-01-W SL

Conqueror Series:
 Ideal for high performance Intel® & AMD® Systems
 Thermally optimized for Prescott® & AthlonT64 processors
 Modern, attractive front panel styling
 Mid-size tower chassis for all around integration
 Maximum air intake design-perforated front bezel.
 Two front loaded HDD cages for up to 6 hard disk drives
 Each HDD cage attached with 1x120mm blue LED fan acts as a air duct to take air in more efficiently for Hard drives, graphic card or CPU.
 Advanced cooling systems:

Model	RPS-01-W SL
Type	ATX Mid Tower
Color	Black/Silver
Case Material	Steel
With Power Supply	No
Motherboard Compat.	Standard ATX ,Micro ATX
Cooling System	2 x 120mm blue LED intake front fans, 1200rpm, 1 x 120mm Exhaust rear fan,1200rpm
Front Ports	USB, Audio, IEEE 1394
Dimensions	7.9" x 18" x 19.7"(Bezel Not Included)



TU-155-P

Ideal for high performance Intel & AMD Systems
 X shape clear side panel
 Lighted blue power switch
 Thermally optimized for Prescott & Athlon 64 processors
 Advanced air guide design
 Virtually tool-less for 5.25" easy assembly
 Thumb screws for side panel
 Easy serviceability & upgrade

Model	TU-155-P
Type	ATX Mid Tower
Color	Black
Case Material	0.8mm SGCC Steel
With Power Supply	No
Motherboard Compat.	Micro ATX, ATX size up to 12.5" x 10.5"
Cooling System	1 x 80mm Blue LED Rear Fan
Front Ports	USB,HD&AC97,1394
Dimensions	18.4" x 8.2" x 17.2"(Bezel Not Included)
Front Ports	USB,HD&AC97,1394
Side Panel	Yes



R223-P-BK

Features Ideal for Intel & AMD Systems
 Advantaged Air Guide
 PCI express venting Holes
 1 x120mm Rear Exhaust Fan,(Option)1 x 120mm Front Intake Fan
 Front I/O Ports (2x USB, MIC In/Audio Out)

Model	R223-P-BK
Type	ATX Mid Tower
Color	Black
Case Material	SECC Cold Rolled Steel
With Power Supply	No
Motherboard Compat.	Micro ATX, ATX
Cooling System	1 x 120mm rear fan
Front Ports	USB, Audio
Dimensions	7.5" x 16.3" x 17.5" (W x H x D).

ATX Mid Tower

FEATURES

SPECIFICATIONS



R226-P-BK

Ideal for Intel & AMD Systems
Advanced Air Guide design
PCI Vent Holes
Built-in 1x 120mm Rear Fan, (Option)1x 120mm Front Fan
High-gloss Finish Bezel
Front I/O Ports (2x USB, MIC In/Audio Out)

Model	R226-P-BK
Type	ATX Mid Tower
Color	Black
Case Material	SECC Cold Rolled Steel
With Power Supply	No
Motherboard Compat.	Micro ATX, ATX
Cooling System	1 x 120mm Rear Fan
Front Ports	USB, Audio
Dimensions	7.5" x 16.3" x 17.5" (W x H x D)



RZLS-142A-P YE

Wind Ryder Series:
Ideal for high performance Intel® & AMD® Systems
Thermally optimized for Prescott® & AthlonT64 processors
Front and rear 120mm fans and mesh front panel for high-efficiency ventilation
Tool-less HDD racks provide for easy assembly
One-piece top lock guard for PCI Slot
0.6mm thick side panel with thumb screw
Adjustable with filter for side fan duct

Model	RZLS-142A-P YE
Type	ATX Mid Tower
Color	Yellow
Case Material	0.6mm thick SGCC steel body
With Power Supply	No
Motherboard Compat.	Micro ATX, ATX
Cooling System	1 x120mm Front intake Fan 1 x120mm Rear exhaust Fan
Front Ports	2 x USB/ 2 Audio (AC97 & HD plugs)
Dimensions	18.25" x 7.25" x 16.5" (D x W x H) (Bezel Not Included)



RZLS-142A-P BK

Wind Ryder Series:
Ideal for high performance Intel® & AMD® Systems
Thermally optimized for Prescott® & AthlonT64 processors
Front and rear 120mm fans and mesh front panel for high-efficiency ventilation
Tool-less HDD racks provide for easy assembly
One-piece top lock guard for PCI Slot
0.6mm thick side panel with thumb screw
Adjustable with filter for side fan duct

Model	RZLS-142A-P BK
Type	ATX Mid Tower
Color	Black
Case Material	0.6mm thick SGCC steel body
With Power Supply	No
Motherboard Compat.	Micro ATX, ATX
Cooling System	1 x120mm Front intake Fan 1 x120mm Rear exhaust Fan
Front Ports	2 x USB/ 2 Audio (AC97 & HD plugs)
Dimensions	18.25" x 7.25" x 16.5" (D x W x H) (Bezel Not Included)



TU-155 II 500

Ideal for high performance Intel & AMD Systems
20+4Pin main connector power supply with SATA connector. HD & AC97 plugs. X shape clear side panel
Lighted blue power switch. Thermally optimized for Prescott & Athlon 64 processors. Advanced air guide design
USB/audio ports accessible from front to front USB/audio ports accessible. Virtually tool-less for 5.25" easy assembly
Thumb screws for side panel. Easy serviceability & upgrade
Power Supply: 500W ATX12V Version 2.2 with Dual 80mm Ball Bearing Fan & 2 x 6Pin PCI-E Connectors

Model	TU-155 II 500
Type	ATX Mid Tower
Color	Black
Case Material	0.8mm SGCC Steel
With Power Supply	Yes
Motherboard Compat.	Micro ATX, ATX size up to 12.5" x 10.5"
Cooling System	1 x 80mm Blue LED Rear Fan
Front Ports	USB, IEEE 1394, Audio - HD & AC97 plugs
Dimensions	18.4" x 8.2" x 17.2" (Bezel Not Included)



RPS-01-WB500P

Conqueror Series:
Ideal for high performance Intel & AMD Systems
Thermally optimized for Prescott & AthlonT64 processors
Modern, attractive front panel styling
Mid-size tower chassis for all around integration
Maximum air intake design-perforated front bezel.
Two front loaded HDD cages for up to 6 hard disk drives
Power Supply: 500W, ATX12V V2.3

Model	RPS-01-WB500P
Type	ATX Mid Tower
Color	Black
Case Material	Steel
With Power Supply	Yes
Motherboard Compat.	Standard ATX, Micro ATX
Cooling System	2 x 120mm blue LED intake front fans, 1200rpm, 1 x 120mm Exhaust rear fan, 1200rpm
Front Ports	USB, Audio, IEEE 1394
Dimensions	7.9" x 18" x 19.7" (Bezel Not Included)

ATX Mid Tower

FEATURES

SPECIFICATIONS



R901-P BK

Thermally Advantaged Chassis for high performance Intel & AMD Systems
 Advantaged Air Guide & PCI express venting Hole (CAG 1.1)
 Easy-Clean Air Filter in front panel
 Extreme Cooling: 3 x 120mm Fan
 Front I/O Ports (2x USB, AC97 & HD Audio)
 Smooth edges to provide greater safety for users
 * For 3.5" Hard Drive installation in drive cage, please use a magnetic screwdriver

Model	R901-P BK
Type	ATX Mid Tower
Color	Black
Case Material	0.7mm SECC Steel
With Power Supply	No
Motherboard Compat.	Micro ATX, ATX
Cooling System	1 x 120mm Rear Fan 1 x 120mm Front Fan 1 x 120mm Top Fan
Front Ports	2 x USB 2.0 Ports. AC97 & HD Audio Ports
Dimensions	8" x 17" x 18.5" (Bezel Not Included)



R5730-P BK

Thermally Advantaged Chassis for high performance Intel & AMD Systems
 Advantaged Air Guide & PCI express venting Hole (CAG 1.1)
 Easy-Clean Air Filter in front panel
 Sliding rail design for easy installation of 5.25" device
 Sliding bi-directional 3.5" cage with absorbing vibration design
 Extreme Cooling: 3 x 120mm Fan + 1x 80mm Fan
 Front I/O Ports (2 x USB, AC97 & HD Audio)
 Smooth edges to provide greater safety for users

Model	R5730-P BK
Type	ATX Mid Tower
Color	Black
Case Material	0.7mm SECC Steel
With Power Supply	No
Motherboard Compat.	Micro ATX, ATX
Cooling System	1 x 120mm Rear Fan 1 x 120mm Front Fan 1 x 120mm Top Fan
Front Ports	2 x USB 2.0 Ports. AC97 & HD Audio Ports
Dimensions	8" x 17" x 18.5" (Bezel Not Included)

/ Case / Micro ATX Slim Case



R379-SM

Removable drive cage
 Thermally optimized
 Excellent EMI shielding
 Can be used as a tower or desktop
 Power Supply: PSU ATX12V Flex 300W

Model	R379-SM
Type	MicroATX Slim Case
Color	Black/ Silver
Case Material	0.8mm SGCC Steel
With Power Supply	Yes
Motherboard Compat.	Micro ATX/ Flex ATX
Cooling System	1 x 80mm top fan
Front Ports	2 x USB/ 2 Audio (AC97 & HD plugs)
Dimensions	15.8" x 12.8" x 3.9" (Bezel Not Included)

/ Case / Micro ATX



R363-M-BK

Ultra High Gloss Finished on entire case
 Sturdy construction with SGCC steel
 Excellent EMI shielding
 Virtually tool-less assembly
 Ease of serviceability & upgrade
 Air guide & PCI vent holes
 Padlock loop
 Side panel with Thumb screws
 Power Supply: 400W

Model	R363-M-BK
Type	MicroATX Mid Tower
Color	Black
Case Material	SGCC Steel
With Power Supply	Yes
Motherboard Compat.	Micro ATX/ Flex ATX
Cooling System	1 x 90mm rear fan
Front Ports	2 x USB 2.0 Front Access Port 2 x Audio Port
Dimensions	14.3" x 7.2" x 15.4" (W x H x D) (Bezel Not Included)16.5" in D with Panel



R102-P-BK

Ideal for Intel & AMD Systems
 Advanced Air Guide design
 PCI Vent Holes
 Built-in 1 x 120mm Rear Exhaust Fan, (Option) 1 x 120mm Front Intake Fan
 Front I/O Ports (2 x USB, MIC In/Audio Out)

Model	R102-P-BK
Type	MicroATX Mid Tower
Color	Black
Case Material	SECC Steel
With Power Supply	No
Motherboard Compat.	MicroATX
Cooling System	1 x 120mm Rear Fan
Front Ports	USB, Audio
Dimensions	7.5" x 13.8" x 15.0" (W x H x D)

Micro ATX

FEATURES

SPECIFICATIONS



R101-P-BK

Ideal for Intel & AMD Systems
Advanced Air Guide design
PCI Vent Holes
Built-in 1x 120mm Rear Exhaust Fan, (Option)1x 120mm Front Intake Fan
Front I/O Ports (2x USB, MIC In/Audio Out)

Model	R101-P-BK
Type	MicroATX Mid Tower
Color	Black
Case Material	SECC Steel
With Power Supply	No
Motherboard Compat.	MicroATX
Cooling System	1 x 120mm Rear Fan
Front Ports	USB, Audio
Dimensions	7.5" x 13.8" x 15.0" (W x H x D)



R115-P BK

Ideal for Intel & AMD Systems
Advanced Air Guide design
PCI Vent Holes
Built-in 1x 120mm Rear Exhaust Fan, (Option)1x 120mm Front Intake Fan
Front I/O Ports (2x USB, MIC In/Audio Out)

Model	R115-P BK
Type	MicroATX Mid Tower
Color	Black
Case Material	SECC Steel
With Power Supply	No
Motherboard Compat.	MicroATX
Cooling System	1 x120mm Rear exhaust Fan
Front Ports	USB, Mic In & Audio Out
Dimensions	15" x 7.5" x 13.8" (W x H x D)



R105-P BK

Ideal for Intel & AMD Systems
Advanced Air Guide design
PCI Vent Holes
Built-in 1x 120mm Rear Exhaust Fan, (Option)1x 120mm Front Intake Fan
Front I/O Ports (2x USB, MIC In/Audio Out)

Model	R105-P BK
Type	MicroATX Mid Tower
Color	Black
Case Material	SECC Steel
With Power Supply	No
Motherboard Compat.	MicroATX
Cooling System	1 x120mm Rear exhaust Fan
Front Ports	USB, Mic In & Audio Out
Dimensions	15" x 7.5" x 13.8" (W x H x D)

/ Case / Mini ITX Tower



RS-MI-01 BK

Ideal for high performance Intel® & AMD® Systems
Thermally optimized for Prescott® & AthlonT64 processors
Modern, attractive front panel styling
Mini ITX chassis with 250W PSU
HD & AC97 Front Audio Ports

Model	RS-MI-01 BK
Type	Mini-ITX Tower
Color	Black
Case Material	Steel
With Power Supply	Yes
Power Supply	250W
Motherboard Compat.	Mini-ITX
Front Ports	USB2.0 x2 Audio x2 (AC97 & HD plug)
Dimensions	8.7" x 5.1" x 13"

Server Chassis

FEATURES

SPECIFICATIONS



RSV-Z4000

RSV-Z4000 is an excellent design of server rackmount chassis. It is well made by 1.2 mm Japanese steel to protect the whole system. It can carry external 3.5" HDD x3/ internal 3.5" HDD x2/ 5.25" device x6 (which can also switch to carry 3.5" HDD x6)/ external optical slim drive x1 (which can also switch to 3.5" HDD x1) totally.

Expansion:

6 External 5.25" Drive Bays, 3 External 3.5" Drive Bays,
2 Internal 3.5" Drive Bays, 7 Expansion Slots, 1 External
Slim Drive Bays

Model	RSV-Z4000
Chassis Type	Rackmount
Color	Black
Case Material	SECC 1.2mm thickness
Motherboard Comp.	12" x 13" E-ATX form factor (SSI, EEB 3.5V; CEB)
Form Factor	4U
Front Ports	dual USB port
Dimensions	19.0" x 22.0" x 7.0"
80mm Fans	2 max (coming with 1 in box already)
120mm Fans	2 max (coming with 1 in box already)



RSV-X4000

It can carry external 3.5" HDD x7/ 5.25" device x3/ external optical slim drive x1 totally.

Cooling design can carry front 120 mm sleeve cooling fan x1 and back 80 mm two ball bearing cooling fan x2
Front door with key lock for better security.

Special design of fixing 7 PCI card in the system.

Dual USB 2.0 connector in front panel.

Expansion:

3 External 5.25" Drive Bays, 7 External 3.5" Drive Bays,
7 Expansion Slots,
External Slim Drive Bays: 1 x Slim CD-ROM

Model	RSV-X4000
Chassis Type	Rackmount
Color	Black
Case Material	SECC 1.2mm thickness
Motherboard Comp.	12" x 13" E-ATX form factor (SSI, EEB 3.5V; CEB)
Form Factor	4U
Front Ports	dual USB port
Dimensions	21.1" x 16.9" x 7.0"
80mm Fans	Back two ball bearing fan x2
120mm Fans	Front sleeve bearing fan x1



RSV-V4000

It can carry external 3.5" HDD x3/ 5.25" device x3 (or switch to 3.5" device x5) totally during fit with 12" x 10.6" CEB form factor, it also support 12" x 13" EEB form factor then it can carry 5.25" device x 2 or use HDD bracket to switch to 3.5" / HDD x1.

Dual USB 2.0 connector in front panel.

Expansion:

3 External 5.25" Drive Bays, 1 External 3.5" Drive Bays,
2 Internal 3.5" Drive Bays, 7 Expansion Slots

Model	RSV-V4000
Chassis Type	Rackmount
Color	Black
Case Material	SECC 1.2mm thickness
Motherboard Comp.	12" x 13" E-ATX form factor (SSI, EEB 3.5V; CEB)
Form Factor	4U
Front Ports	dual USB port
Dimensions	19.0" x 18.8" x 7.0"
120mm Fans	2 x Front balling fan

Audio Cable

FEATURES

SPECIFICATIONS



RCW-H9040

Rosewill RCW-H9040 enables you to connect your iPod with color display (iPod photo), iPod (5th generation) and select models of digital camcorders (Sony, Canon, JVC, Samsung) with TV Out function to your TV or entertainment system, enjoying pictures, slideshows and videos on a large screen.

Important: This cable doesn't support all iPod/MP3 players or all camcorders.

Model	RCW-H9040
Type	Combination AV Cables
Length	6 Feet
Connector Number	4
Terminal Gender	M - 3M
Specifications	3.5mm Stereo Plug to 3 RCA Output Plugs
	Gold-Plated Connectors, OD: 3.5mm
Color	Black



RCW-H9009

Are specifically designed for quality computer audio applications. The 3.5mm cable connects the PC sound card, portable CD player or any mini-stereo audio device with 3.5mm jacks to multimedia speakers.

-Connectors: 3.5mm Stereo Male to 3.5mm Stereo Male

-Fully molded connectors provide strain relief

-Foil shielded to prevent EMI/RFI interference

Application: Connects PC sound card, portable CD player or any mini-stereo audio device with 3.5mm jacks to multimedia speakers

Model	RCW-H9009
Type	Stereo Audio Cable
Length	6 Feet
Connectors	2
Terminal Gender	M - M
Color	Black



RCW-H9008

Are specifically designed for quality computer audio applications. The 3.5mm cable connects the PC sound card, portable CD player or any mini-stereo audio device with 3.5mm jacks to multimedia speakers.

-Connectors: 3.5mm Stereo Male to 3.5mm Stereo Male

-Fully molded connectors provide strain relief

-Foil shielded to prevent EMI/RFI interference

Application: Connects PC sound card, portable CD player or any mini-stereo audio device with 3.5mm jacks to multimedia speakers

Model	RCW-H9008
Type	Stereo Audio Cable
Length	6 Feet
Connectors	2
Terminal Gender	M - M
Color	Black



RCW-H9006

This Cable allows connection of audio equipment with RCA, including CD players, MP3 players, AV receivers, and speakers. Our superior design ensures maximum signal transfer and reduces interference for a natural, more accurate sound.

-Connects your audio equipment with RCA jacks, including CD players, MP3 players, AV receivers, and speakers.

- Gold-Plated connectors and contacts provide maximum conductivity and prevent corrosion

Aluminum undermold shield ensures optimum signal integrity.

Model	RCW-H9006
Type	Digital Coaxial Audio Cable
Length	6 Feet
Connectors	2
Terminal Gender	M - M
Color	Black



RCW-H9007

This Cable allows connection of audio equipment with RCA, including CD players, MP3 players, AV receivers, and speakers. Our superior design ensures maximum signal transfer and reduces interference for a natural, more accurate sound.

-Connects your audio equipment with RCA jacks, including CD players, MP3 players, AV receivers, and speakers

-Gold-Plated connectors and contacts provide maximum conductivity and prevent corrosion

-Aluminum undermold shield ensures optimum signal integrity

Model	RCW-H9007
Type	Digital Coaxial Audio Cable
Length	6 Feet
Connectors	2
Terminal Gender	M - M
Color	Black

Audio Cable

FEATURES

SPECIFICATIONS



RCW-H9005

Extend the distance of your existing 3.5mm audio cables. 3.5mm Audio Cables are used to connect the 3.5mm jack from CD players, stereos, speakers, PC/TV tuners and other audio devices.

- Connectors: 3.5mm Stereo Male to 3.5mm Stereo Female
- Fully molded connectors provide excellent strain relief
- Shielded to prevent EMI/RFI interference

Use: Extends the distance of your existing 3.5mm Audio Cable

Model	RCW-H9005
Type	3.5mm Extension Cable
Length	6 Feet
Connectors	2
Terminal Gender	F-M
Color	Black



RCW-H9010

Audio Y Adapter Cables allow you to split a signal or adapt from one connection to another. Gold terminals ensure long lasting, corrosion-free connections.

Fully molded connectors provide excellent strain relief

Model	RCW-H9010
Type	3.5mm Stereo Splitter
Length	6 Feet
Connectors	3
Terminal Gender	M-2F
Color	Black



RCW-H9001

Optical cables transfer the signal using light; thus completely eliminating any chance for RFI, EMI or ground loop interference. Connect your DVD, CD, Satellite Receiver, Game console or other digital audio equipment for clear, full detailed sound.

TOSLINK to TOSLINK

- Low-Loss MPPA core ensures low distortion
- Non-slip rubber grip connector provides for easy install.
- Ultra-flexible PVC jacket makes installation easy
- Protective plastic cover protects lens from dust, dirt, and other material.

Model	RCW-H9001
Type	Digital Optical Audio Cables
Length	6 Feet
Connectors	2
Terminal Gender	M-M
Color	Black



RCW-H9004

Extend the distance of your existing 3.5mm audio cables. 3.5mm Audio Cables are used to connect the 3.5mm jack from CD players, stereos, speakers, PC/TV tuners and other audio devices.

Model	RCW-H9004
Type	3.5mm Stereo Male to 3.5mm Stereo Female
Length	12 Feet
Connectors	2
Terminal Gender	F-M
Color	Black



RCW-932

High performance A/V cable can be used as a Hi-Fi interconnect, component video, or coaxial digital (SPDIF) connection cable. Delivers superb clarity, definition and detail. Metal connectors and gold plated contacts for excellent signal transfer and ensure data integrity, corrosion-resistant connection available. Wire and connectors are carefully matched to virtually eliminate echoing and cancellation by highly pure copper shielding, guaranteeing high-speed, error-free data transmission.

Model	RCW-932
Type	Analog RCA Audio Cables
Length	12 Feet
Connectors	4
Specifications	2 RCA M - 2 RCA M
Color	Black(with black mesh)

Audio Cable

FEATURES

SPECIFICATIONS



RCW-931

High performance A/V cable can be used as a Hi-Fi interconnect, component video, or coaxial digital (SPDIF) connection cable .
Delivers superb clarity, definition and detail.
Metal connectors and gold plated contacts for excellent signal transfer and ensure data integrity, corrosion-resistant connection available.
Wire and connectors are carefully matched to virtually eliminate echoing and cancellation by highly pure copper shielding, guaranteeing high-speed, error-free data transmission.

Model	RCW-931
Type	Analog RCA Audio Cables
Length	6 Feet
Connectors	4
Specifications	2 RCA M - 2 RCA M
Color	Black(with black mesh)



RCW-930

High performance A/V cable can be used as a Hi-Fi interconnect, component video, or coaxial digital (SPDIF) connection cable .
Delivers superb clarity, definition and detail.
Metal connectors and gold plated contacts for excellent signal transfer and ensure data integrity, corrosion-resistant connection available.
Wire and connectors are carefully matched to virtually eliminate echoing and cancellation by highly pure copper shielding, guaranteeing high-speed, error-free data transmission.

Model	RCW-930
Type	Analog RCA Audio Cables
Length	12 Feet
Connectors	4
Specifications	2 RCA M - 2 RCA M
Color	Black



RCW-929

High performance A/V cable can be used as a Hi-Fi interconnect, component video, or coaxial digital (SPDIF) connection cable .
Delivers superb clarity, definition and detail.
Metal connectors and gold plated contacts for excellent signal transfer and ensure data integrity, corrosion-resistant connection available.
Wire and connectors are carefully matched to virtually eliminate echoing and cancellation by highly pure copper shielding, guaranteeing high-speed, error-free data transmission.

Model	RCW-929
Type	Analog RCA Audio Cables
Length	6 Feet
Connectors	4
Specifications	2 RCA M - 2 RCA M
Color	Pearl Black

/ Cables / Video Cable



RCW-914

High performance video component cable (RYW) suitable to any component enabled device, such as plasma TV, projectors, etc.
Delivers superb clarity, definition and detail.
Metal connectors and gold plated contacts for excellent signal transfer and ensure data integrity, corrosion-resistant connection available.
Wire and connectors are carefully matched to virtually eliminate echoing and cancellation by highly pure copper shielding, guaranteeing high-speed, error-free data transmission

Model	RCW-914
Type	Component Cables
Length	12 Feet
Connectors	6
Specifications	3 RCA M - 3 RCA M
Color	Black(with black mesh)



RCW-913

High performance video component cable (RYW) suitable to any component enabled device, such as plasma TV, projectors, etc.
Delivers superb clarity, definition and detail.
Metal connectors and gold plated contacts for excellent signal transfer and ensure data integrity, corrosion-resistant connection available.
Wire and connectors are carefully matched to virtually eliminate echoing and cancellation by highly pure copper shielding, guaranteeing high-speed, error-free data transmission

Model	RCW-913
Type	Component Cables
Length	6 Feet
Connectors	6
Specifications	3 RCA M - 3 RCA M
Color	Black(with black mesh)

Video Cable

FEATURES

SPECIFICATIONS



RCW-912

High performance video component cable (RYW) suitable to any component enabled device, such as plasma TV, projectors, etc.
Delivers superb clarity, definition and detail.
Metal connectors and gold plated contacts for excellent signal transfer and ensure data integrity, corrosion-resistant connection available.
Wire and connectors are carefully matched to virtually eliminate echoing and cancellation by highly pure copper shielding, guaranteeing high-speed, error-free data transmission

Model	RCW-912
Type	Component Cables
Length	12 Feet
Connectors	6
Specifications	3 RCA M - 3 RCA
Color	Peal Black



RCW-911

High performance video component cable (RYW) suitable to any component enabled device, such as plasma TV, projectors, etc.
Delivers superb clarity, definition and detail. Metal connectors and gold plated contacts for excellent signal transfer and ensure data integrity, corrosion-resistant connection available.
Wire and connectors are carefully matched to virtually eliminate echoing and cancellation by highly pure copper shielding, guaranteeing high-speed, error-free data transmission.

Model	RCW-911
Type	Component Cables
Length	6 Feet
Connectors	6
Specifications	3 RCA M - 3 RCA
Color	Peal Black

/ Cables / VGA Cable



RC-25-VG-MM-BK

Constructed from premium grade double-shielded twisted pairs and triple-shielded coax
Ferrites protect from EMI / RFI interference
Accommodates cable runs up to 100 feet without a booster (for most cases)
Ideal for video presentation devices, home theater and HDTV applications, classroom environments, POS, server rooms and more applications

Model	RC-25-VG-MM-BK
Type	VGA
Length	25 Feet
Connectors	2
Specifications	VGA Coaxial cable, UL 2919 28AWG (3C+ 7), HD15M-HD15M, W/2 Ferrite cores, with white dust cover
Color	Black



RC-25-VG-MF-BK

Constructed from premium grade double-shielded twisted pairs and triple-shielded coax
Ferrites protect from EMI / RFI interference
Accommodates cable runs up to 100 feet without a booster (for most cases)
Ideal for video presentation devices, home theater and HDTV applications, classroom environments, POS, server rooms and more applications

Model	RC-25-VG-MF-BK
Type	VGA
Length	25 Feet
Connectors	2
Specifications	VGA Coaxial cable, UL 2919 28AWG (3C+ 7), HD15M-HD15F, W/2 Ferrite cores, with white dust cover
Color	Black



RCW-805

Constructed from premium grade double-shielded twisted pairs and triple-shielded coax
Ferrites protect from EMI/RFI interference
Accommodates cable runs up to 100 feet without a booster (for most cases)
Ideal for video presentation devices, home theater and HDTV applications, classroom environments, POS, server rooms and more applications

Model	RCW-805
Type	VGA
Length	15 Feet
Connectors	2
Specifications	High Quality VGA Coaxial cable, UL 2919 28AWG (3C+ 7), HD15M-HD15m, Metal hood, Beige, W/2 Ferrite cores, 15 ft, with white dust cover
Color	Black

VGA Cable

FEATURES

SPECIFICATIONS



RCW-804

Constructed from premium grade double-shielded twisted pairs and triple-shielded coax
 Ferrites protect from EMI/RFI interference
 Accommodates cable runs up to 100 feet without a booster (for most cases)
 Ideal for video presentation devices, home theater and HDTV applications, classroom environments, POS, server rooms and more applications

Model	RCW-804
Type	VGA
Length	15 Feet
Connectors	2
Specifications	High Quality VGA Coaxial cable, UL 2919 28AWG (3C+ 7), HD15M-HD15F, Metal hood, Beige, 2 Ferrite cores, with dust cover
Color	Beige



RCW-803

Constructed from premium grade double-shielded twisted pairs and triple-shielded coax
 Ferrites protect from EMI/RFI interference
 Accommodates cable runs up to 100 feet without a booster (for most cases)
 Ideal for video presentation devices, home theater and HDTV applications, classroom environments, POS, server rooms and more applications

Model	RCW-803
Type	VGA
Length	10 Feet
Connectors	2
Specifications	High Quality VGA Coaxial cable, UL 2919 28AWG (3C+ 7), HD15M-HD15M, Beige, 2 Ferrite cores, with dust cover
Color	Beige



RCW-802

Constructed from premium grade double-shielded twisted pairs and triple-shielded coax
 Ferrites protect from EMI/RFI interference
 Accommodates cable runs up to 100 feet without a booster (for most cases)
 Ideal for video presentation devices, home theater and HDTV applications, classroom environments, POS, server rooms and more applications

Model	RCW-802
Type	VGA
Length	6 Feet
Connectors	2
Specifications	High Quality VGA Coaxial cable, UL 2919 28AWG (3C+ 7), HD15M-HD15M, Black, W/2 Ferrite cores, with dust cover
Color	Black



RCW-801

Constructed from premium grade double-shielded twisted pairs and triple-shielded coax
 Ferrites protect from EMI/RFI interference
 Accommodates cable runs up to 100 feet without a booster (for most cases)
 Ideal for video presentation devices, home theater and HDTV applications, classroom environments, POS, server rooms and more applications

Model	RCW-801
Type	VGA
Length	10 Feet
Connectors	2
Specifications	UL 2919 28AWG (3C+ 7) HD15 Male to HD15 Female 2 Ferrite cores
Color	Beige



RCW-800

Constructed from premium grade double-shielded twisted pairs and triple-shielded coax
 Ferrites protect from EMI/RFI interference
 Accommodates cable runs up to 100 feet without a booster (for most cases)
 Ideal for video presentation devices, home theater and HDTV applications, classroom environments, POS, server rooms and more applications

Model	RCW-800
Type	VGA
Length	6 Feet
Connectors	2
Specifications	High Quality VGA Coaxial cable, UL 2919 28AWG (3C+ 7), HD15M-HD15F, Black, with Ferrite cores, with dust cover
Color	Black

Network Cable

FEATURES

SPECIFICATIONS



RCW-717

Each cable is fully tested and quality inspected, ensuring all EIA/TIA Cat 6 TIA/EIA- 568-B-2.1, draft 9 standards are met. Drastically reduce both impedance and structural return loss (SRL) as compared to standard 100 Mhz wire, which ensures error-free transmission!

Connector: gold plated RJ-45 Male to Male
Conductor: 24 AWG Stranded Copper, PVC Jacket
Designed For: Network Adapters, Hubs, Switches, Routers, DSL/Cable Modems, Patch Panels and other twisted-pair applications

Model	RCW-717
Cat	6 (Crossover)
Length	3 Feet
Connectors	2
Color	Yellow to Gray



RCW-720

Supports up to 2x 16550 Fast Uart serial port
Easy Plug and Play installation
Automatically selects IRQ & IO address
Supports IRQ sharing
Built in 16C550 compatible UART with 16byte transmit-receive FIFO
Multi – card capability – allow for upgrade with additional serial or parallel cards
For 5V PCI slot only

Model	RCW-720
Cat	6 (Crossover)
Length	14 Feet
Connectors	2
Color	Yellow to Gray



RCW-551

Each cable is fully tested and quality inspected, ensuring all EIA/TIA Cat 6 TIA/EIA- 568-B-2.1, draft 9 standards are met. Drastically reduce both impedance and structural return loss (SRL) as compared to standard 100 Mhz wire, which ensures error-free transmission!

Connector: gold plated RJ-45 Male to Male
Conductor: 24 AWG Stranded Copper, PVC Jacket
Designed For: Network Adapters, Hubs, Switches, Routers, DSL/Cable Modems, Patch Panels and other twisted-pair applications
Perfect for Gigabit, Fast Ethernet, and Ethernet appl.

Model	RCW-551
Cat	6
Length	1 Feet
Connectors	2
Color	Blue



RCW-552

Each cable is fully tested and quality inspected, ensuring all EIA/TIA Cat 6 TIA/EIA- 568-B-2.1, draft 9 standards are met. Drastically reduce both impedance and structural return loss (SRL) as compared to standard 100 Mhz wire, which ensures error-free transmission!

Connector: gold plated RJ-45 Male to Male
Conductor: 24 AWG Stranded Copper, PVC Jacket
Designed For: Network Adapters, Hubs, Switches, Routers, DSL/Cable Modems, Patch Panels and other twisted-pair applications
Perfect for Gigabit, Fast Ethernet, and Ethernet appl.

Model	RCW-552
Cat	6
Length	3 Feet
Connectors	2
Color	Blue



RCW-553

Each cable is fully tested and quality inspected, ensuring all EIA/TIA Cat 6 TIA/EIA- 568-B-2.1, draft 9 standards are met. Drastically reduce both impedance and structural return loss (SRL) as compared to standard 100 Mhz wire, which ensures error-free transmission!

Connector: gold plated RJ-45 Male to Male
Conductor: 24 AWG Stranded Copper, PVC Jacket
Designed For: Network Adapters, Hubs, Switches, Routers, DSL/Cable Modems, Patch Panels and other twisted-pair applications
Perfect for Gigabit, Fast Ethernet, and Ethernet appl.

Model	RCW-553
Cat	6
Length	7 Feet
Connectors	2
Color	Blue

Network Cable

FEATURES

SPECIFICATIONS



RCW-554

Each cable is fully tested and quality inspected, ensuring all EIA/TIA Cat 6 TIA/EIA- 568-B-2.1, draft 9 standards are met. Drastically reduce both impedance and structural return loss (SRL) as compared to standard 100 Mhz wire, which ensures error-free transmission!

Connector: gold plated RJ-45 Male to Male
 Conductor: 24 AWG Stranded Copper, PVC Jacket
 Designed For: Network Adapters, Hubs, Switches, Routers, DSL/Cable Modems, Patch Panels and other twisted-pair applications
 Perfect for Gigabit, Fast Ethernet, and Ethernet appl.

Model	RCW-554
Cat	6
Length	10 Feet
Connectors	2
Color	Blue



RCW-555

Each cable is fully tested and quality inspected, ensuring all EIA/TIA Cat 6 TIA/EIA- 568-B-2.1, draft 9 standards are met. Drastically reduce both impedance and structural return loss (SRL) as compared to standard 100 Mhz wire, which ensures error-free transmission!

Connector: gold plated RJ-45 Male to Male
 Conductor: 24 AWG Stranded Copper, PVC Jacket
 Designed For: Network Adapters, Hubs, Switches, Routers, DSL/Cable Modems, Patch Panels and other twisted-pair applications
 Perfect for Gigabit, Fast Ethernet, and Ethernet appl.

Model	RCW-555
Cat	6
Length	14 Feet
Connectors	2
Color	Blue



RCW-556

Each cable is fully tested and quality inspected, ensuring all EIA/TIA Cat 6 TIA/EIA- 568-B-2.1, draft 9 standards are met. Drastically reduce both impedance and structural return loss (SRL) as compared to standard 100 Mhz wire, which ensures error-free transmission!

Connector: gold plated RJ-45 Male to Male
 Conductor: 24 AWG Stranded Copper, PVC Jacket
 Designed For: Network Adapters, Hubs, Switches, Routers, DSL/Cable Modems, Patch Panels and other twisted-pair applications
 Perfect for Gigabit, Fast Ethernet, and Ethernet appl.

Model	RCW-556
Cat	6
Length	25 Feet
Connectors	2
Color	Blue



RCW-557

Each cable is fully tested and quality inspected, ensuring all EIA/TIA Cat 6 TIA/EIA- 568-B-2.1, draft 9 standards are met. Drastically reduce both impedance and structural return loss (SRL) as compared to standard 100 Mhz wire, which ensures error-free transmission!

Connector: gold plated RJ-45 Male to Male
 Conductor: 24 AWG Stranded Copper, PVC Jacket
 Designed For: Network Adapters, Hubs, Switches, Routers, DSL/Cable Modems, Patch Panels and other twisted-pair applications
 Perfect for Gigabit, Fast Ethernet, and Ethernet appl.

Model	RCW-557
Cat	6
Length	50 Feet
Connectors	2
Color	Blue



RCW-558

Each cable is fully tested and quality inspected, ensuring all EIA/TIA Cat 6 TIA/EIA- 568-B-2.1, draft 9 standards are met. Drastically reduce both impedance and structural return loss (SRL) as compared to standard 100 Mhz wire, which ensures error-free transmission!

Connector: gold plated RJ-45 Male to Male
 Conductor: 24 AWG Stranded Copper, PVC Jacket
 Designed For: Network Adapters, Hubs, Switches, Routers, DSL/Cable Modems, Patch Panels and other twisted-pair applications
 Perfect for Gigabit, Fast Ethernet, and Ethernet appl.

Model	RCW-558
Cat	6
Length	75 Feet
Connectors	2
Color	Blue

Network Cable

FEATURES

SPECIFICATIONS



RCW-559

Each cable is fully tested and quality inspected, ensuring all EIA/TIA Cat 6 TIA/EIA- 568-B-2.1, draft 9 standards are met. Drastically reduce both impedance and structural return loss (SRL) as compared to standard 100 Mhz wire, which ensures error-free transmission!

Connector: gold plated RJ-45 Male to Male
 Conductor: 24 AWG Stranded Copper, PVC Jacket
 Designed For: Network Adapters, Hubs, Switches, Routers, DSL/Cable Modems, Patch Panels and other twisted-pair applications

Perfect for Gigabit, Fast Ethernet, and Ethernet appl.

Model	RCW-559
Cat	6
Length	100 Feet
Connectors	2
Color	Blue



RCW-560

Each cable is fully tested and quality inspected, ensuring all EIA/TIA Cat 6 TIA/EIA- 568-B-2.1, draft 9 standards are met. Drastically reduce both impedance and structural return loss (SRL) as compared to standard 100 Mhz wire, which ensures error-free transmission!

Connector: gold plated RJ-45 Male to Male
 Conductor: 24 AWG Stranded Copper, PVC Jacket
 Designed For: Network Adapters, Hubs, Switches, Routers, DSL/Cable Modems, Patch Panels and other twisted-pair applications

Perfect for Gigabit, Fast Ethernet, and Ethernet appl.

Model	RCW-560
Cat	6
Length	1 Feet
Connectors	2
Color	Black



RCW-561

Each cable is fully tested and quality inspected, ensuring all EIA/TIA Cat 6 TIA/EIA- 568-B-2.1, draft 9 standards are met. Drastically reduce both impedance and structural return loss (SRL) as compared to standard 100 Mhz wire, which ensures error-free transmission!

Connector: gold plated RJ-45 Male to Male
 Conductor: 24 AWG Stranded Copper, PVC Jacket
 Designed For: Network Adapters, Hubs, Switches, Routers, DSL/Cable Modems, Patch Panels and other twisted-pair applications

Perfect for Gigabit, Fast Ethernet, and Ethernet appl.

Model	RCW-561
Cat	6
Length	3 Feet
Connectors	2
Color	Black



RCW-562

Each cable is fully tested and quality inspected, ensuring all EIA/TIA Cat 6 TIA/EIA- 568-B-2.1, draft 9 standards are met. Drastically reduce both impedance and structural return loss (SRL) as compared to standard 100 Mhz wire, which ensures error-free transmission!

Connector: gold plated RJ-45 Male to Male
 Conductor: 24 AWG Stranded Copper, PVC Jacket
 Designed For: Network Adapters, Hubs, Switches, Routers, DSL/Cable Modems, Patch Panels and other twisted-pair applications

Perfect for Gigabit, Fast Ethernet, and Ethernet appl.

Model	RCW-561
Cat	6
Length	7 Feet
Connectors	2
Color	Black



RCW-563

Each cable is fully tested and quality inspected, ensuring all EIA/TIA Cat 6 TIA/EIA- 568-B-2.1, draft 9 standards are met. Drastically reduce both impedance and structural return loss (SRL) as compared to standard 100 Mhz wire, which ensures error-free transmission!

Connector: gold plated RJ-45 Male to Male
 Conductor: 24 AWG Stranded Copper, PVC Jacket
 Designed For: Network Adapters, Hubs, Switches, Routers, DSL/Cable Modems, Patch Panels and other twisted-pair applications

Perfect for Gigabit, Fast Ethernet, and Ethernet appl.

Model	RCW-563
Cat	6
Length	10 Feet
Connectors	2
Color	Black

Network Cable

FEATURES

SPECIFICATIONS



RCW-564

Each cable is fully tested and quality inspected, ensuring all EIA/TIA Cat 6 TIA/EIA- 568-B-2.1, draft 9 standards are met. Drastically reduce both impedance and structural return loss (SRL) as compared to standard 100 Mhz wire, which ensures error-free transmission!
Connector: gold plated RJ-45 Male to Male
Conductor: 24 AWG Stranded Copper, PVC Jacket
Designed For: Network Adapters, Hubs, Switches, Routers, DSL/Cable Modems, Patch Panels and other twisted-pair applications
Perfect for Gigabit, Fast Ethernet, and Ethernet appl.

Model	RCW-564
Cat	6
Length	14 Feet
Connectors	2
Color	Black



RCW-565

Each cable is fully tested and quality inspected, ensuring all EIA/TIA Cat 6 TIA/EIA- 568-B-2.1, draft 9 standards are met. Drastically reduce both impedance and structural return loss (SRL) as compared to standard 100 Mhz wire, which ensures error-free transmission!
Connector: gold plated RJ-45 Male to Male
Conductor: 24 AWG Stranded Copper, PVC Jacket
Designed For: Network Adapters, Hubs, Switches, Routers, DSL/Cable Modems, Patch Panels and other twisted-pair applications
Perfect for Gigabit, Fast Ethernet, and Ethernet appl.

Model	RCW-565
Cat	6
Length	25 Feet
Connectors	2
Color	Black



RCW-566

Each cable is fully tested and quality inspected, ensuring all EIA/TIA Cat 6 TIA/EIA- 568-B-2.1, draft 9 standards are met. Drastically reduce both impedance and structural return loss (SRL) as compared to standard 100 Mhz wire, which ensures error-free transmission!
Connector: gold plated RJ-45 Male to Male
Conductor: 24 AWG Stranded Copper, PVC Jacket
Designed For: Network Adapters, Hubs, Switches, Routers, DSL/Cable Modems, Patch Panels and other twisted-pair applications
Perfect for Gigabit, Fast Ethernet, and Ethernet appl.

Model	RCW-566
Cat	6
Length	50 Feet
Connectors	2
Color	Black



RCW-567

Each cable is fully tested and quality inspected, ensuring all EIA/TIA Cat 6 TIA/EIA- 568-B-2.1, draft 9 standards are met. Drastically reduce both impedance and structural return loss (SRL) as compared to standard 100 Mhz wire, which ensures error-free transmission!
Connector: gold plated RJ-45 Male to Male
Conductor: 24 AWG Stranded Copper, PVC Jacket
Designed For: Network Adapters, Hubs, Switches, Routers, DSL/Cable Modems, Patch Panels and other twisted-pair applications
Perfect for Gigabit, Fast Ethernet, and Ethernet appl.

Model	RCW-567
Cat	6
Length	75 Feet
Connectors	2
Color	Black



RCW-568

Each cable is fully tested and quality inspected, ensuring all EIA/TIA Cat 6 TIA/EIA- 568-B-2.1, draft 9 standards are met. Drastically reduce both impedance and structural return loss (SRL) as compared to standard 100 Mhz wire, which ensures error-free transmission!
Connector: gold plated RJ-45 Male to Male
Conductor: 24 AWG Stranded Copper, PVC Jacket
Designed For: Network Adapters, Hubs, Switches, Routers, DSL/Cable Modems, Patch Panels and other twisted-pair applications
Perfect for Gigabit, Fast Ethernet, and Ethernet appl.

Model	RCW-568
Cat	6
Length	100 Feet
Connectors	2
Color	Black

Network Cable

FEATURES

SPECIFICATIONS



RCW-569

Each cable is fully tested and quality inspected, ensuring all EIA/TIA Cat 6 TIA/EIA- 568-B-2.1, draft 9 standards are met. Drastically reduce both impedance and structural return loss (SRL) as compared to standard 100 Mhz wire, which ensures error-free transmission!

Connector: gold plated RJ-45 Male to Male
 Conductor: 24 AWG Stranded Copper, PVC Jacket
 Designed For: Network Adapters, Hubs, Switches, Routers, DSL/Cable Modems, Patch Panels and other twisted-pair applications

Perfect for Gigabit, Fast Ethernet, and Ethernet appl.

Model	RCW-569
Cat	6
Length	1 Feet
Connectors	2
Color	White



RCW-570

Each cable is fully tested and quality inspected, ensuring all EIA/TIA Cat 6 TIA/EIA- 568-B-2.1, draft 9 standards are met. Drastically reduce both impedance and structural return loss (SRL) as compared to standard 100 Mhz wire, which ensures error-free transmission!

Connector: gold plated RJ-45 Male to Male
 Conductor: 24 AWG Stranded Copper, PVC Jacket
 Designed For: Network Adapters, Hubs, Switches, Routers, DSL/Cable Modems, Patch Panels and other twisted-pair applications

Perfect for Gigabit, Fast Ethernet, and Ethernet appl.

Model	RCW-570
Cat	6
Length	3 Feet
Connectors	2
Color	White



RCW-571

Each cable is fully tested and quality inspected, ensuring all EIA/TIA Cat 6 TIA/EIA- 568-B-2.1, draft 9 standards are met. Drastically reduce both impedance and structural return loss (SRL) as compared to standard 100 Mhz wire, which ensures error-free transmission!

Connector: gold plated RJ-45 Male to Male
 Conductor: 24 AWG Stranded Copper, PVC Jacket
 Designed For: Network Adapters, Hubs, Switches, Routers, DSL/Cable Modems, Patch Panels and other twisted-pair applications

Perfect for Gigabit, Fast Ethernet, and Ethernet appl.

Model	RCW-571
Cat	6
Length	7 Feet
Connectors	2
Color	White



RCW-572

Each cable is fully tested and quality inspected, ensuring all EIA/TIA Cat 6 TIA/EIA- 568-B-2.1, draft 9 standards are met. Drastically reduce both impedance and structural return loss (SRL) as compared to standard 100 Mhz wire, which ensures error-free transmission!

Connector: gold plated RJ-45 Male to Male
 Conductor: 24 AWG Stranded Copper, PVC Jacket
 Designed For: Network Adapters, Hubs, Switches, Routers, DSL/Cable Modems, Patch Panels and other twisted-pair applications

Perfect for Gigabit, Fast Ethernet, and Ethernet appl.

Model	RCW-572
Cat	6
Length	10 Feet
Connectors	2
Color	White



RCW-573

Each cable is fully tested and quality inspected, ensuring all EIA/TIA Cat 6 TIA/EIA- 568-B-2.1, draft 9 standards are met. Drastically reduce both impedance and structural return loss (SRL) as compared to standard 100 Mhz wire, which ensures error-free transmission!

Connector: gold plated RJ-45 Male to Male
 Conductor: 24 AWG Stranded Copper, PVC Jacket
 Designed For: Network Adapters, Hubs, Switches, Routers, DSL/Cable Modems, Patch Panels and other twisted-pair applications

Perfect for Gigabit, Fast Ethernet, and Ethernet appl.

Model	RCW-573
Cat	6
Length	14 Feet
Connectors	2
Color	White

Network Cable

FEATURES

SPECIFICATIONS



RCW-574

Each cable is fully tested and quality inspected, ensuring all EIA/TIA Cat 6 TIA/EIA- 568-B-2.1, draft 9 standards are met. Drastically reduce both impedance and structural return loss (SRL) as compared to standard 100 Mhz wire, which ensures error-free transmission!

Connector: gold plated RJ-45 Male to Male

Conductor: 24 AWG Stranded Copper, PVC Jacket

Designed For: Network Adapters, Hubs, Switches, Routers, DSL/Cable Modems, Patch Panels and other twisted-pair applications

Perfect for Gigabit, Fast Ethernet, and Ethernet appl.

Model	RCW-574
Cat	6
Length	25 Feet
Connectors	2
Color	White



RCW-576

Each cable is fully tested and quality inspected, ensuring all EIA/TIA Cat 6 TIA/EIA- 568-B-2.1, draft 9 standards are met. Drastically reduce both impedance and structural return loss (SRL) as compared to standard 100 Mhz wire, which ensures error-free transmission!

Connector: gold plated RJ-45 Male to Male

Conductor: 24 AWG Stranded Copper, PVC Jacket

Designed For: Network Adapters, Hubs, Switches, Routers, DSL/Cable Modems, Patch Panels and other twisted-pair applications

Perfect for Gigabit, Fast Ethernet, and Ethernet appl.

Model	RCW-576
Cat	6
Length	75 Feet
Connectors	2
Color	White



RCW-577

Each cable is fully tested and quality inspected, ensuring all EIA/TIA Cat 6 TIA/EIA- 568-B-2.1, draft 9 standards are met. Drastically reduce both impedance and structural return loss (SRL) as compared to standard 100 Mhz wire, which ensures error-free transmission!

Connector: gold plated RJ-45 Male to Male

Conductor: 24 AWG Stranded Copper, PVC Jacket

Designed For: Network Adapters, Hubs, Switches, Routers, DSL/Cable Modems, Patch Panels and other twisted-pair applications

Perfect for Gigabit, Fast Ethernet, and Ethernet appl.

Model	RCW-577
Cat	6
Length	100 Feet
Connectors	2
Color	White



RCW-578

Each cable is fully tested and quality inspected, ensuring all EIA/TIA Cat 6 TIA/EIA- 568-B-2.1, draft 9 standards are met. Drastically reduce both impedance and structural return loss (SRL) as compared to standard 100 Mhz wire, which ensures error-free transmission!

Connector: gold plated RJ-45 Male to Male

Conductor: 24 AWG Stranded Copper, PVC Jacket

Designed For: Network Adapters, Hubs, Switches, Routers, DSL/Cable Modems, Patch Panels and other twisted-pair applications

Perfect for Gigabit, Fast Ethernet, and Ethernet appl.

Model	RCW-578
Cat	6
Length	1 Feet
Connectors	2
Color	Gray



RCW-579

Each cable is fully tested and quality inspected, ensuring all EIA/TIA Cat 6 TIA/EIA- 568-B-2.1, draft 9 standards are met. Drastically reduce both impedance and structural return loss (SRL) as compared to standard 100 Mhz wire, which ensures error-free transmission!

Connector: gold plated RJ-45 Male to Male

Conductor: 24 AWG Stranded Copper, PVC Jacket

Designed For: Network Adapters, Hubs, Switches, Routers, DSL/Cable Modems, Patch Panels and other twisted-pair applications

Perfect for Gigabit, Fast Ethernet, and Ethernet appl.

Model	RCW-579
Cat	6
Length	3 Feet
Connectors	2
Color	Gray

Network Cable

FEATURES

SPECIFICATIONS



RCW-581

Each cable is fully tested and quality inspected, ensuring all EIA/TIA Cat 6 TIA/EIA- 568-B-2.1, draft 9 standards are met. Drastically reduce both impedance and structural return loss (SRL) as compared to standard 100 Mhz wire, which ensures error-free transmission!

Connector: gold plated RJ-45 Male to Male

Conductor: 24 AWG Stranded Copper, PVC Jacket

Designed For: Network Adapters, Hubs, Switches, Routers, DSL/Cable Modems, Patch Panels and other twisted-pair applications

Perfect for Gigabit, Fast Ethernet, and Ethernet appl.

Model	RCW-581
Cat	6
Length	10 Feet
Connectors	2
Color	Grey



RCW-582

Each cable is fully tested and quality inspected, ensuring all EIA/TIA Cat 6 TIA/EIA- 568-B-2.1, draft 9 standards are met. Drastically reduce both impedance and structural return loss (SRL) as compared to standard 100 Mhz wire, which ensures error-free transmission!

Connector: gold plated RJ-45 Male to Male

Conductor: 24 AWG Stranded Copper, PVC Jacket

Designed For: Network Adapters, Hubs, Switches, Routers, DSL/Cable Modems, Patch Panels and other twisted-pair applications

Perfect for Gigabit, Fast Ethernet, and Ethernet appl.

Model	RCW-582
Cat	6
Length	14 Feet
Connectors	2
Color	Grey



RCW-583

Each cable is fully tested and quality inspected, ensuring all EIA/TIA Cat 6 TIA/EIA- 568-B-2.1, draft 9 standards are met. Drastically reduce both impedance and structural return loss (SRL) as compared to standard 100 Mhz wire, which ensures error-free transmission!

Connector: gold plated RJ-45 Male to Male

Conductor: 24 AWG Stranded Copper, PVC Jacket

Designed For: Network Adapters, Hubs, Switches, Routers, DSL/Cable Modems, Patch Panels and other twisted-pair applications

Perfect for Gigabit, Fast Ethernet, and Ethernet appl.

Model	RCW-583
Cat	6
Length	25 Feet
Connectors	2
Color	Grey



RCW-584

Each cable is fully tested and quality inspected, ensuring all EIA/TIA Cat 6 TIA/EIA- 568-B-2.1, draft 9 standards are met. Drastically reduce both impedance and structural return loss (SRL) as compared to standard 100 Mhz wire, which ensures error-free transmission!

Connector: gold plated RJ-45 Male to Male

Conductor: 24 AWG Stranded Copper, PVC Jacket

Designed For: Network Adapters, Hubs, Switches, Routers, DSL/Cable Modems, Patch Panels and other twisted-pair applications

Perfect for Gigabit, Fast Ethernet, and Ethernet appl.

Model	RCW-584
Cat	6
Length	50 Feet
Connectors	2
Color	Grey



RCW-585

Each cable is fully tested and quality inspected, ensuring all EIA/TIA Cat 6 TIA/EIA- 568-B-2.1, draft 9 standards are met. Drastically reduce both impedance and structural return loss (SRL) as compared to standard 100 Mhz wire, which ensures error-free transmission!

Connector: gold plated RJ-45 Male to Male

Conductor: 24 AWG Stranded Copper, PVC Jacket

Designed For: Network Adapters, Hubs, Switches, Routers, DSL/Cable Modems, Patch Panels and other twisted-pair applications

Perfect for Gigabit, Fast Ethernet, and Ethernet appl.

Model	RCW-585
Cat	6
Length	75 Feet
Connectors	2
Color	Grey

Network Cable

FEATURES

SPECIFICATIONS



RCW-586

Each cable is fully tested and quality inspected, ensuring all EIA/TIA Cat 6 TIA/EIA- 568-B-2.1, draft 9 standards are met. Drastically reduce both impedance and structural return loss (SRL) as compared to standard 100 Mhz wire, which ensures error-free transmission!
Connector: gold plated RJ-45 Male to Male
Conductor: 24 AWG Stranded Copper, PVC Jacket
Designed For: Network Adapters, Hubs, Switches, Routers, DSL/Cable Modems, Patch Panels and other twisted-pair applications
Perfect for Gigabit, Fast Ethernet, and Ethernet appl.

Model	RCW-586
Cat	6
Length	100 Feet
Connectors	2
Color	Grey



RCW-587

Each cable is fully tested and quality inspected, ensuring all EIA/TIA Cat 6 TIA/EIA- 568-B-2.1, draft 9 standards are met. Drastically reduce both impedance and structural return loss (SRL) as compared to standard 100 Mhz wire, which ensures error-free transmission!
Connector: gold plated RJ-45 Male to Male
Conductor: 24 AWG Stranded Copper, PVC Jacket
Designed For: Network Adapters, Hubs, Switches, Routers, DSL/Cable Modems, Patch Panels and other twisted-pair applications
Perfect for Gigabit, Fast Ethernet, and Ethernet appl.

Model	RCW-587
Cat	6
Length	1 Feet
Connectors	2
Color	Red



RCW-588

Each cable is fully tested and quality inspected, ensuring all EIA/TIA Cat 6 TIA/EIA- 568-B-2.1, draft 9 standards are met. Drastically reduce both impedance and structural return loss (SRL) as compared to standard 100 Mhz wire, which ensures error-free transmission!
Connector: gold plated RJ-45 Male to Male
Conductor: 24 AWG Stranded Copper, PVC Jacket
Designed For: Network Adapters, Hubs, Switches, Routers, DSL/Cable Modems, Patch Panels and other twisted-pair applications
Perfect for Gigabit, Fast Ethernet, and Ethernet appl.

Model	RCW-588
Cat	6
Length	3 Feet
Connectors	2
Color	Red



RCW-590

Each cable is fully tested and quality inspected, ensuring all EIA/TIA Cat 6 TIA/EIA- 568-B-2.1, draft 9 standards are met. Drastically reduce both impedance and structural return loss (SRL) as compared to standard 100 Mhz wire, which ensures error-free transmission!
Connector: gold plated RJ-45 Male to Male
Conductor: 24 AWG Stranded Copper, PVC Jacket
Designed For: Network Adapters, Hubs, Switches, Routers, DSL/Cable Modems, Patch Panels and other twisted-pair applications
Perfect for Gigabit, Fast Ethernet, and Ethernet appl.

Model	RCW-590
Cat	6
Length	10 Feet
Connectors	2
Color	Red



RCW-592

Each cable is fully tested and quality inspected, ensuring all EIA/TIA Cat 6 TIA/EIA- 568-B-2.1, draft 9 standards are met. Drastically reduce both impedance and structural return loss (SRL) as compared to standard 100 Mhz wire, which ensures error-free transmission!
Connector: gold plated RJ-45 Male to Male
Conductor: 24 AWG Stranded Copper, PVC Jacket
Designed For: Network Adapters, Hubs, Switches, Routers, DSL/Cable Modems, Patch Panels and other twisted-pair applications
Perfect for Gigabit, Fast Ethernet, and Ethernet appl.

Model	RCW-592
Cat	6
Length	25 Feet
Connectors	2
Color	Red

Network Cable

FEATURES

SPECIFICATIONS



RCW-593

Each cable is fully tested and quality inspected, ensuring all EIA/TIA Cat 6 TIA/EIA- 568-B-2.1, draft 9 standards are met. Drastically reduce both impedance and structural return loss (SRL) as compared to standard 100 Mhz wire, which ensures error-free transmission!
Connector: gold plated RJ-45 Male to Male
Conductor: 24 AWG Stranded Copper, PVC Jacket
Designed For: Network Adapters, Hubs, Switches, Routers, DSL/Cable Modems, Patch Panels and other twisted-pair applications
Perfect for Gigabit, Fast Ethernet, and Ethernet appl.

Model	RCW-593
Cat	6
Length	50 Feet
Connectors	2
Color	Red



RCW-594

Each cable is fully tested and quality inspected, ensuring all EIA/TIA Cat 6 TIA/EIA- 568-B-2.1, draft 9 standards are met. Drastically reduce both impedance and structural return loss (SRL) as compared to standard 100 Mhz wire, which ensures error-free transmission!
Connector: gold plated RJ-45 Male to Male
Conductor: 24 AWG Stranded Copper, PVC Jacket
Designed For: Network Adapters, Hubs, Switches, Routers, DSL/Cable Modems, Patch Panels and other twisted-pair applications
Perfect for Gigabit, Fast Ethernet, and Ethernet appl.

Model	RCW-594
Cat	6
Length	75 Feet
Connectors	2
Color	Red



RCW-595

Each cable is fully tested and quality inspected, ensuring all EIA/TIA Cat 6 TIA/EIA- 568-B-2.1, draft 9 standards are met. Drastically reduce both impedance and structural return loss (SRL) as compared to standard 100 Mhz wire, which ensures error-free transmission!
Connector: gold plated RJ-45 Male to Male
Conductor: 24 AWG Stranded Copper, PVC Jacket
Designed For: Network Adapters, Hubs, Switches, Routers, DSL/Cable Modems, Patch Panels and other twisted-pair applications
Perfect for Gigabit, Fast Ethernet, and Ethernet appl.

Model	RCW-595
Cat	6
Length	100 Feet
Connectors	2
Color	Red



RCW-596

Each cable is fully tested and quality inspected, ensuring all EIA/TIA Cat 6 TIA/EIA- 568-B-2.1, draft 9 standards are met. Drastically reduce both impedance and structural return loss (SRL) as compared to standard 100 Mhz wire, which ensures error-free transmission!
Connector: gold plated RJ-45 Male to Male
Conductor: 24 AWG Stranded Copper, PVC Jacket
Designed For: Network Adapters, Hubs, Switches, Routers, DSL/Cable Modems, Patch Panels and other twisted-pair applications
Perfect for Gigabit, Fast Ethernet, and Ethernet appl.

Model	RCW-596
Cat	6
Length	1 Feet
Connectors	2
Color	Yellow



RCW-597

Each cable is fully tested and quality inspected, ensuring all EIA/TIA Cat 6 TIA/EIA- 568-B-2.1, draft 9 standards are met. Drastically reduce both impedance and structural return loss (SRL) as compared to standard 100 Mhz wire, which ensures error-free transmission!
Connector: gold plated RJ-45 Male to Male
Conductor: 24 AWG Stranded Copper, PVC Jacket
Designed For: Network Adapters, Hubs, Switches, Routers, DSL/Cable Modems, Patch Panels and other twisted-pair applications
Perfect for Gigabit, Fast Ethernet, and Ethernet appl.

Model	RCW-597
Cat	6
Length	3 Feet
Connectors	2
Color	Yellow

Network Cable

FEATURES

SPECIFICATIONS



RCW-598

Each cable is fully tested and quality inspected, ensuring all EIA/TIA Cat 6 TIA/EIA- 568-B-2.1, draft 9 standards are met. Drastically reduce both impedance and structural return loss (SRL) as compared to standard 100 Mhz wire, which ensures error-free transmission!
Connector: gold plated RJ-45 Male to Male
Conductor: 24 AWG Stranded Copper, PVC Jacket
Designed For: Network Adapters, Hubs, Switches, Routers, DSL/Cable Modems, Patch Panels and other twisted-pair applications
Perfect for Gigabit, Fast Ethernet, and Ethernet appl.

Model	RCW-598
Cat	6
Length	7 Feet
Connectors	2
Color	Yellow



RCW-599

Each cable is fully tested and quality inspected, ensuring all EIA/TIA Cat 6 TIA/EIA- 568-B-2.1, draft 9 standards are met. Drastically reduce both impedance and structural return loss (SRL) as compared to standard 100 Mhz wire, which ensures error-free transmission!
Connector: gold plated RJ-45 Male to Male
Conductor: 24 AWG Stranded Copper, PVC Jacket
Designed For: Network Adapters, Hubs, Switches, Routers, DSL/Cable Modems, Patch Panels and other twisted-pair applications
Perfect for Gigabit, Fast Ethernet, and Ethernet appl.

Model	RCW-599
Cat	6
Length	10 Feet
Connectors	2
Color	Yellow



RCW-703

Each cable is fully tested and quality inspected, ensuring all EIA/TIA Cat 6 TIA/EIA- 568-B-2.1, draft 9 standards are met. Drastically reduce both impedance and structural return loss (SRL) as compared to standard 100 Mhz wire, which ensures error-free transmission!
Connector: gold plated RJ-45 Male to Male
Conductor: 24 AWG Stranded Copper, PVC Jacket
Designed For: Network Adapters, Hubs, Switches, Routers, DSL/Cable Modems, Patch Panels and other twisted-pair applications
Perfect for Gigabit, Fast Ethernet, and Ethernet appl.

Model	RCW-703
Cat	6
Length	14 Feet
Connectors	2
Color	Yellow



RCW-704

Each cable is fully tested and quality inspected, ensuring all EIA/TIA Cat 6 TIA/EIA- 568-B-2.1, draft 9 standards are met. Drastically reduce both impedance and structural return loss (SRL) as compared to standard 100 Mhz wire, which ensures error-free transmission!
Connector: gold plated RJ-45 Male to Male
Conductor: 24 AWG Stranded Copper, PVC Jacket
Designed For: Network Adapters, Hubs, Switches, Routers, DSL/Cable Modems, Patch Panels and other twisted-pair applications
Perfect for Gigabit, Fast Ethernet, and Ethernet appl.

Model	RCW-704
Cat	6
Length	25 Feet
Connectors	2
Color	Yellow



RCW-705

Each cable is fully tested and quality inspected, ensuring all EIA/TIA Cat 6 TIA/EIA- 568-B-2.1, draft 9 standards are met. Drastically reduce both impedance and structural return loss (SRL) as compared to standard 100 Mhz wire, which ensures error-free transmission!
Connector: gold plated RJ-45 Male to Male
Conductor: 24 AWG Stranded Copper, PVC Jacket
Designed For: Network Adapters, Hubs, Switches, Routers, DSL/Cable Modems, Patch Panels and other twisted-pair applications
Perfect for Gigabit, Fast Ethernet, and Ethernet appl.

Model	RCW-705
Cat	6
Length	50 Feet
Connectors	2
Color	Yellow

Network Cable

FEATURES

SPECIFICATIONS



RCW-706

Each cable is fully tested and quality inspected, ensuring all EIA/TIA Cat 6 TIA/EIA- 568-B-2.1, draft 9 standards are met. Drastically reduce both impedance and structural return loss (SRL) as compared to standard 100 Mhz wire, which ensures error-free transmission!
Connector: gold plated RJ-45 Male to Male
Conductor: 24 AWG Stranded Copper, PVC Jacket
Designed For: Network Adapters, Hubs, Switches, Routers, DSL/Cable Modems, Patch Panels and other twisted-pair applications
Perfect for Gigabit, Fast Ethernet, and Ethernet appl.

Model	RCW-706
Cat	6
Length	75 Feet
Connectors	2
Color	Yellow



RCW-707

Each cable is fully tested and quality inspected, ensuring all EIA/TIA Cat 6 TIA/EIA- 568-B-2.1, draft 9 standards are met. Drastically reduce both impedance and structural return loss (SRL) as compared to standard 100 Mhz wire, which ensures error-free transmission!
Connector: gold plated RJ-45 Male to Male
Conductor: 24 AWG Stranded Copper, PVC Jacket
Designed For: Network Adapters, Hubs, Switches, Routers, DSL/Cable Modems, Patch Panels and other twisted-pair applications
Perfect for Gigabit, Fast Ethernet, and Ethernet appl.

Model	RCW-707
Cat	6
Length	100 Feet
Connectors	2
Color	Yellow



RCW-708

Each cable is fully tested and quality inspected, ensuring all EIA/TIA Cat 6 TIA/EIA- 568-B-2.1, draft 9 standards are met. Drastically reduce both impedance and structural return loss (SRL) as compared to standard 100 Mhz wire, which ensures error-free transmission!
Connector: gold plated RJ-45 Male to Male
Conductor: 24 AWG Stranded Copper, PVC Jacket
Designed For: Network Adapters, Hubs, Switches, Routers, DSL/Cable Modems, Patch Panels and other twisted-pair applications
Perfect for Gigabit, Fast Ethernet, and Ethernet appl.

Model	RCW-708
Cat	6
Length	1 Feet
Connectors	2
Color	Green



RCW-709

Each cable is fully tested and quality inspected, ensuring all EIA/TIA Cat 6 TIA/EIA- 568-B-2.1, draft 9 standards are met. Drastically reduce both impedance and structural return loss (SRL) as compared to standard 100 Mhz wire, which ensures error-free transmission!
Connector: gold plated RJ-45 Male to Male
Conductor: 24 AWG Stranded Copper, PVC Jacket
Designed For: Network Adapters, Hubs, Switches, Routers, DSL/Cable Modems, Patch Panels and other twisted-pair applications
Perfect for Gigabit, Fast Ethernet, and Ethernet appl.

Model	RCW-709
Cat	6
Length	3 Feet
Connectors	2
Color	Green



RCW-710

Each cable is fully tested and quality inspected, ensuring all EIA/TIA Cat 6 TIA/EIA- 568-B-2.1, draft 9 standards are met. Drastically reduce both impedance and structural return loss (SRL) as compared to standard 100 Mhz wire, which ensures error-free transmission!
Connector: gold plated RJ-45 Male to Male
Conductor: 24 AWG Stranded Copper, PVC Jacket
Designed For: Network Adapters, Hubs, Switches, Routers, DSL/Cable Modems, Patch Panels and other twisted-pair applications
Perfect for Gigabit, Fast Ethernet, and Ethernet appl.

Model	RCW-710
Cat	6
Length	7 Feet
Connectors	2
Color	Green

Network Cable

FEATURES

SPECIFICATIONS



RCW-712

Each cable is fully tested and quality inspected, ensuring all EIA/TIA Cat 6 TIA/EIA- 568-B-2.1, draft 9 standards are met. Drastically reduce both impedance and structural return loss (SRL) as compared to standard 100 Mhz wire, which ensures error-free transmission!

Connector: gold plated RJ-45 Male to Male
Conductor: 24 AWG Stranded Copper, PVC Jacket
Designed For: Network Adapters, Hubs, Switches, Routers, DSL/Cable Modems, Patch Panels and other twisted-pair applications. Perfect for Gigabit, Fast Ethernet, and Ethernet applications

Model	RCW-712
Cat	6
Length	14 Feet
Connectors	2
Color	Green



RCW-713

Each cable is fully tested and quality inspected, ensuring all EIA/TIA Cat 6 TIA/EIA- 568-B-2.1, draft 9 standards are met. Drastically reduce both impedance and structural return loss (SRL) as compared to standard 100 Mhz wire, which ensures error-free transmission!

Connector: gold plated RJ-45 Male to Male
Conductor: 24 AWG Stranded Copper, PVC Jacket
Designed For: Network Adapters, Hubs, Switches, Routers, DSL/Cable Modems, Patch Panels and other twisted-pair applications. Perfect for Gigabit, Fast Ethernet, and Ethernet applications

Model	RCW-713
Cat	6
Length	25 Feet
Connectors	2
Color	Green



RCW-714

Each cable is fully tested and quality inspected, ensuring all EIA/TIA Cat 6 TIA/EIA- 568-B-2.1, draft 9 standards are met. Drastically reduce both impedance and structural return loss (SRL) as compared to standard 100 Mhz wire, which ensures error-free transmission!

Connector: gold plated RJ-45 Male to Male
Conductor: 24 AWG Stranded Copper, PVC Jacket
Designed For: Network Adapters, Hubs, Switches, Routers, DSL/Cable Modems, Patch Panels and other twisted-pair applications. Perfect for Gigabit, Fast Ethernet, and Ethernet applications

Model	RCW-714
Cat	6
Length	50 Feet
Connectors	2
Color	Green



RCW-715

Each cable is fully tested and quality inspected, ensuring all EIA/TIA Cat 6 TIA/EIA- 568-B-2.1, draft 9 standards are met. Drastically reduce both impedance and structural return loss (SRL) as compared to standard 100 Mhz wire, which ensures error-free transmission!

Connector: gold plated RJ-45 Male to Male
Conductor: 24 AWG Stranded Copper, PVC Jacket
Designed For: Network Adapters, Hubs, Switches, Routers, DSL/Cable Modems, Patch Panels and other twisted-pair applications. Perfect for Gigabit, Fast Ethernet, and Ethernet applications

Model	RCW-715
Cat	6
Length	75 Feet
Connectors	2
Color	Green



RCW-716

Each cable is fully tested and quality inspected, ensuring all EIA/TIA Cat 6 TIA/EIA- 568-B-2.1, draft 9 standards are met. Drastically reduce both impedance and structural return loss (SRL) as compared to standard 100 Mhz wire, which ensures error-free transmission!

Connector: gold plated RJ-45 Male to Male
Conductor: 24 AWG Stranded Copper, PVC Jacket
Designed For: Network Adapters, Hubs, Switches, Routers, DSL/Cable Modems, Patch Panels and other twisted-pair applications. Perfect for Gigabit, Fast Ethernet, and Ethernet applications

Model	RCW-716
Cat	6
Length	100 Feet
Connectors	2
Color	Green

USB Cable

FEATURES

SPECIFICATIONS



RC-16-U-AMF-BG

Actively buffer the incoming and outgoing signals to ensure compliance with USB's 2.0 specification for electrical and timing minimums.

You can connect up to 5 active extension cables end-to-end to achieve up to 80ft extension.

Both low and high speed USB devices will function equally well with the USB Active Extension.

Model	RC-16-U-AMF-BG
Type	USB 2.0
Length	16 ft.
Connectors	2
Color	White



RCW-105

Connector: USB Type A Male to Type B Male

Transfer rates up to 480Mbps

Make plug-and-play connections for such devices as keyboards, mice, modems, printers, and other USB peripherals

PC and Mac compatible

Connect a USB peripheral to an USB Hub or USB port on PC/Mac

Compatible with USB specifications 1.0, 1.1, and 2.0

Model	RCW-105
Type	USB 2.0 Cable
Length	15 ft.
Connectors	2
Specifications	USB 2.0 AM-BM Cable, UL2725, 28/24 AWG, Beige, L: 15 ft
Color	Beige



RCW-102RT

Connector: USB Type A Male to Type B Male

Transfer rates up to 480Mbps

Make plug-and-play connections for such devices as keyboards, mice, modems, printers, and other USB peripherals

PC and Mac compatible

Connect a USB peripheral to an USB Hub or USB port on PC/Mac

Compatible with USB specifications 1.0, 1.1, and 2.0

Model	RCW-102RT
Type	USB 2.0 AB cable
Length	15 ft.
Connectors	2
Specifications	USB 2.0 Cable, AM-BM, Mold type, UL 2727, 28/24 AWG
Color	Black



101RT

Connector: USB Type A Male to Type B Male

Transfer rates up to 480Mbps

Make plug-and-play connections for such devices as keyboards, mice, modems, printers, and other USB peripherals

PC and Mac compatible

Connect a USB peripheral to an USB Hub or USB port on PC/Mac

Compatible with USB specifications 1.0, 1.1, and 2.0

Model	RCW-101RT
Type	USB 2.0 AB cable
Length	10 ft.
Connectors	2
Specifications	USB 2.0 Cable, AM-BM, Mold type, UL 2727, 28/24 AWG
Color	Black



RCW-100

Connectors: USB Type A Male to Type A Female

PC and Mac compatible

Extend the distance of your existing USB A/B cable

Model	RCW-100
Type	USB 2.0 Extension cable
Length	6 ft.
Connectors	2 connectors
Specifications	USB 2.0 Cable, AM-AF, Mold type, UL 2727, 28/24 AWG
Color	Black

USB Cable

FEATURES

SPECIFICATIONS



RCW-110

Connectors: USB A Male to USB 4-Pin Mini B Male
Provides hi-speed data transfer to 480Mbps
Compatible with PC and Mac
Ultra-flexible jacket makes installation easy
Foil and braid shield reduces interference
Matched twisted-pair wires with electrical resistance minimize crosstalk for high-speed, error-free data transfer
Compatible with USB specifications 1.0, 1.1, and 2.0

Model	RCW-110
Type	USB cable
Length	6 ft.
Connectors	2 connectors
Specifications	Mini USB 2.0 Cable, AM- 4 Pin MINI B M(Square), Black, 6 ft
Color	Black



RCW-109

Connectors: USB A Male to USB 4-Pin Mini B Male
Provides hi-speed data transfer to 480Mbps
Compatible with PC and Mac
Ultra-flexible jacket makes installation easy
Foil and braid shield reduces interference
Matched twisted-pair wires with electrical resistance minimize crosstalk for high-speed, error-free data transfer
Compatible with USB specifications 1.0, 1.1, and 2.0

Model	RCW-109
Type	USB 2.0 cable
Length	6 ft.
Connectors	2 connectors
Specifications	Mini USB 2.0 Cable, AM- 4 Pin MINI B M (Rectangular), Black, 6 ft
Color	Black



RCW-108

Connector: USB Type A Male to Type Mini B 5-pin Male (MD Type)
Transfer rates up to 480Mbps depending on USB version
Make plug and play connections with cellular phones, MP3 players, digital cameras and PDAs
PC and Mac compatible
Connect a peripheral with a 5-pin mini usb port to an USB Hub or USB port on PC/Mac
Compatible with USB specifications 1.0, 1.1, and 2.0

Model	RCW-108
Type	USB cable
Length	6 ft.
Connectors	2 connectors
Specifications	USB 2.0 AM- 5 Pin MINI B M, Black, 6 ft
Color	Black



RCW-106

Connector: USB Type A Male to Type B Male
Transfer rates up to 480Mbps
Make plug-and-play connections for such devices as keyboards, mice, modems, printers, and other USB peripherals
PC and Mac compatible
Connect a USB peripheral to an USB Hub or USB port on PC/Mac
Compatible with USB specifications 1.0, 1.1, and 2.0

Model	RCW-106
Type	USB cable
Length	10 ft.
Connectors	2 connectors
Specifications	USB 2.0 AM-BM Cable, UL2725, 28/24 AWG
Color	Transparent



RCW-104

Connector: USB Type A Male to Type B Male
Transfer rates up to 480Mbps
Make plug-and-play connections for such devices as keyboards, mice, modems, printers, and other USB peripherals
PC and Mac compatible
Connect a USB peripheral to an USB Hub or USB port on PC/Mac
Compatible with USB specifications 1.0, 1.1, and 2.0

Model	RCW-104
Type	USB cable
Length	10 ft.
Connectors	2 connectors
Color	Beige
Specifications	USB 2.0 AM-BM Cable, UL2725, 28/24 AWG, Beige, L: 10 ft

USB Cable

FEATURES

SPECIFICATIONS



RCW-103

Connector: USB Type A Male to Type B Male
Transfer rates up to 480Mbps
Make plug-and-play connections for such devices as keyboards, mice, modems, printers, and other USB peripherals
PC and Mac compatible
Connect a USB peripheral to an USB Hub or USB port on PC/Mac
Compatible with USB specifications 1.0, 1.1, and 2.0

Model	RCW-103
Type	USB cable
Length	6 ft.
Connectors	2 connectors
Specifications	USB 2.0 AM-BM Cable, UL2725, 28/24 AWG, Beige, L: 6 ft
Color	Beige



RCW-111

USB 2.0 certified cable
AM-AF
UL2725
28*1P /24* 2c AWG
Nickel plated connector

Model	RCW-111
Type	USB cable
Length	6 ft.
Connectors	2 connectors
Specifications	USB 2.0 certified cable AM-AF UL2725 28*1P /24* 2c AWG Nickel plated connector
Color	Beige

Other Cable

/ SATA / eSATA



RC-18-SA2-BK

Compliant with Serial ATA II specifications, data transfer rate as high as 3.0Gbps
Easy installation and setup
Locking latch connector guarantees proper connection to device
High Signal quality

Model	RC-18"-SA2-BK
Type	SATA II
Length	18"
Connectors	2
Specifications	SATA II
Color	Black



RC-18-SA-90-BK

Compliant with Serial ATA II specifications, data transfer rate as high as 3.0Gbps
Easy installation and setup
High Signal quality

Model	RC-18"-SA-90-BK
Type	SATA
Length	18"
Connectors	2
Specifications	Serial ATA data Cable F (90 Angled) – F (180 Angled) UL 2725
Color	Black



RC-18-SA2-90-BK

Compliant with Serial ATA II specifications, data transfer rate as high as 3.0Gbps
Easy installation and setup
High Signal quality

Model	RC-18"-SA2-90-BK
Type	SATA II
Length	18"
Connectors	2
Specifications	Serial ATA II External data Cable, 7P (Angled) -7P (Angled), UL 2725 F (90 Angled) – F (180 Angled)
Color	Black

Other Cable SATA / eSATA

FEATURES

SPECIFICATIONS



RCW-204

Compliant with Serial ATA II specifications, data transfer rate as high as 3.0Gbps
Easy installation and setup
Locking latch connector guarantees proper connection to device
High Signal quality

Model	RCW-204
Type	SATA
Length	20"
Connectors	2
Specifications	Sata II
Color	Red

/ Other Cable / DVI Cable



RCW-902

Gold-Plated Connectors:
The Rosewill RCW-902 cable features gold-plated connectors for superior signal transfer and a lifetime of maximum performance.

Dual-Link DVI Cable
This dual-link DVI cable transfers high definition video signals up to 1080p for broadcast quality digital video performance.

Model	RCW-902
Type	DVI
Length	10 ft.
Connectors	2
Specifications	DVI-I (24+5) Digital Dual Link, Male to Male UL 20276 2 Ferrite cores Molded



RCW-903

Gold-Plated Connectors
The Rosewill RCW-903 cable features gold-plated connectors for superior signal transfer and a lifetime of maximum performance.

Dual-Link DVI Cable
This dual-link DVI cable transfers high definition video signals up to 1080p for broadcast quality digital video performance.

Model	RCW-903
Type	DVI
Length	6 ft.
Connectors	2
Color	Black
Specifications	DVI-I (24+5) Digital Dual Link, Male to Male UL 20276 2 Ferrite cores Molded



RCW-904

Gold-Plated Connectors
The Rosewill RCW-904 cable features gold-plated connectors for superior signal transfer and a lifetime of maximum performance.

Dual-Link DVI Cable
This dual-link DVI cable transfers high definition video signals up to 1080p for broadcast quality digital video performance.

Model	RCW-904
Type	DVI
Length	15 ft.
Connectors	2
Color	Black
Specifications	DVI-I (24+5) Digital Dual Link, Male to Male UL 20276 2 Ferrite cores Molded



RCW-900

Gold-Plated Connectors
The Rosewill RCW-904 cable features gold-plated connectors for superior signal transfer and a lifetime of maximum performance.

Dual-Link DVI Cable
This dual-link DVI cable transfers high definition video signals up to 1080p for broadcast quality digital video performance.

Model	RCW-900
Type	DVI to VGA
Length	10 ft.
Connectors	2
Color	Black
Specifications	DVI-A (24+5) to VGA HD15 Male 2 Ferrite cores

Other Cable / DVI Cable

FEATURES

SPECIFICATIONS



RCW-401

Connectors: DVI male to DVI male
 Compatible with up to 1080p performance!
 CL2-rated for in-wall applications
 Broadcast quality digital video performance!
 Three layers of shielding: two 80%+ OFC copper braids and one 100% overlapped Mylar foil provide maximum immunity to environmental EMI and RFI
 24-karat gold-plated connectors ensure superior signal transfer and a lifetime of maximum performance
 Silver-solder construction eliminates the negative effects of dissimilar metals on the delicate video signal...

Model	RCW-401
Type	DVI
Length	6 ft.
Connectors	2
Color	Black
Specifications	Digital DVI-D Dual link cable (M/M;24+1 pin to 24+1 pin) High-density polyethylene UL 28 AWG stranded

/ Other Cable / IEEE 1394



RC-6-1394-6M-4M-BK

Compliant with IEEE 1394 specification
 Transfer speed up to 400Mbps
 Hot swappable

Model	RC-6-1394-6M-4M-BK
Type	IEEE 1394(Firewire)
Length	6 ft.
Connectors	2
Color	Black
Specifications	Connectors: 6-pin Male to 4-pin Male



RC-6-1394-6M-6M-BK

Compliant with IEEE 1394 specification
 Transfer speed up to 400Mbps
 Hot swappable

Model	RC-6-1394-6M-6M-BK
Type	IEEE 1394(Firewire)
Length	6 ft.
Connectors	2
Color	Black
Specifications	Connectors: 6-pin Male to 6-pin Male

/ Other Cable / Power Cables



RCW-301

Connector: One 4-pin Male Socket to Two 4-pin Jacket Females
 Splits one 5-1/4 power connector into two 5-1/4 power connectors
 Designed for Hard Drives, CD-ROMs, CD-RWs, Tape Drives, Fans, etc.
 UV effect wire and connectors

Model	RCW-301
Type	Power Splitter
Length	8"
Connectors	3
Color	UV Blue
Specifications	IDE 4 Pins Power Splitter 1M-2F UL 1007 18 AWG UV



RC-6-PW-24M-20F

Enable you to connect a power supply 20 pin ATX to a 24 pin ATX Connection.

Model	RC-6-PW-24M-20F
Type	Power
Length	6"
Connectors	2
Color	Multi-Color
Specifications	EATX power supply 24F to ATX 20F M motherboard, UL 1007

Other Cable / Power Cable

FEATURES

SPECIFICATIONS



RCW-300

Connector: One 4-pin Male Socket to Two 4-pin Jacket Females
Splits one 5-1/4 power connector into two 5-1/4 power connectors
Designed for Hard Drives, CD-ROMs, CD-RWs, Tape Drives, Fans, etc.

Model	RCW-300
Type	Internal Power Splitter
Length	8"
Connectors	3
Color	Multi-Color
Specifications	IDE 4 Pins Power Splitter 1M-2F UL 1007 18 AWG



RCW-311

Fan power supply cable, Molex 4 Pin T type connector

Model	RCW-311
Type	Power
Length	12"
Connectors	3
Color	Multi-Color
Specifications	IFan power supply cable, Molex 4P T type (M-F) connector - 3 pin M, 3pin F, 12", UL 1007 wire, 26 AWG



RCW-307

SATA Combo Y Cable, SATA Power & Data Connection between the device and M/B

Model	RCW-307
Type	Power
Length	15cm / 75cm
Connectors	3
Color	Multi-Color
Specifications	Serial ATA combin cable, data and power in one cable, length of power cable, 15 cm, data cable, 75 cm M-F



RCW-309

Fan power supply cable, 3 pin fan extension with UV tube

Model	RCW-309
Type	Fan Power Cables
Length	12"
Connectors	2
Specifications	Fan power supply cable, 3 pin fan extension, 12", w/UV tube, UL 1007 wire, 26AWG



RCW-308

Fan power supply cable, 3 pin fan extension

Model	RCW-308
Type	Fan Power Cables
Length	12"
Connectors	2
Specifications	Fan power supply cable, 3 pin fan extension, UL 1007 wire, 26AWG

Other Cable / Power Cable

FEATURES

SPECIFICATIONS



RCW-310

Connector: One 4-pin Male Socket to Two 4-pin Jacket Females
Splits one 5-1/4 power connector into two 5-1/4 power connectors
Designed for Hard Drives, CD-ROMs, CD-RWs, Tape Drives, Fans, etc.

Model	RCW-310
Type	Fan Power Cables
Length	12"
Connectors	3
Color	Multi-Color
Specifications	Fan power Y cable, 1M-2F, 3 pin fan splitter, 12", UL 1007 wire, 26AWG



RCW-302

Enable you to connect your high speed Serial ATA drives to your power chain with this 4 Pin Molex to Dual 15 Pin Serial ATA power adapter. This power connector can be used with both 3.5" and 2.5" Serial ATA devices.
Adapts one 5.25in power connector into two Serial ATA power connector
Designed for Serial ATA Hard Drives, CD-ROMs, CD-RWs, Tape Drives, Fans, etc

Model	RCW-302
Type	Power Splitter
Length	8"
Connectors	3
Color	Multi-Color
Specifications	4 Pins Molex to Dual 15pin Serial ATA power adapter UL 1007 18 AWG



RC-6-PW-4P-2SA

4 pin Molex to Dual 15 pin Serial ATA power splitter

Model	RC-6-PW-4P-2SA
Type	Power
Length	6"
Connectors	3
Color	Multi-Color
Specifications	Dual Serial ATA Power Splitter, UL 1007 18 AWG, 4 pin Molex to Dual 15pin Serial ATA power adapter



RC-8-PW-4P-2SA

4 pin Molex to Dual 15 pin Serial ATA power splitter (Angled)

Model	RC-8-PW-4P-2SA
Type	Power
Length	8"
Connectors	3
Color	Multi-Color
Specifications	Dual Serial ATA Power Splitter, UL 1007 18 AWG, 4 pin Molex to Dual 15pin (Angled) Serial ATA power adapter



RCW-305

Adapts one 5.25in power connector into one Serial ATA power connector
Designed for Serial ATA Hard Drives, CD-ROMs, CD-RWs, Tape Drives, Fans, etc

Model	RCW-305
Type	Power
Length	6"
Connectors	2
Color	Multi-Color
Specifications	Serial ATA I, II Power adapter cable 5.25" M-15P Serial ATA F (black)

Other Cable / Power Cable

FEATURES

SPECIFICATIONS



RCW-303

Connector: 24-pin female to 20-pin male
Designed for all ATX-style power supplies

Model	RCW-303
Type	Power
Length	7.8"
Connectors	2
Specifications	EATX power supply 24P F to ATX 20P M motherboard, UL wires

Controllers Card

/ Raid Card



RC-208

Chipset: Silicon Image Sil 0680
Compliant with UltraDMA6 ATA/133 specifications
Compliant with PCI v2.2 Plug-n-Play
Provides two independent Ultra ATA channels
Full ACPI power management support
Supports Ultra DMA 0-6 and Multi-word DMA 0-2
Supports hard drives larger than 137GB
CRC(Cyclical Redundancy Check) error-checking provides data verification and achieves flawless data transfer
Works with various brand, capacity hard disk drives and ATAPI devices

Model	RC-208
Type	IDE
Dimension	790x195x320 mm
Interface	PCI
Internal Connectors	2 x ATA 133
Transfer Rate	up to 133MB/sec
Operating Systems Supported	Windows® 98SE/ME/NT 4.0/2000/XP/ Server 2003/ Vista 32 & 64bit



RC-220

Includes Low Profile and Regular size PCI Brackets
You can hang your external enclosure by eSATA to RC-220
Two external eSATA connector.
Includes Low Profile and Regular size PCI Brackets.
48 bits LBA can Break Capacity-Limit to Support HDD larger than 137GB.
Dual high speed Serial ATA interface ports, each supporting 1st generation Serial ATA data rates 1.5Gb/s and fully compliant with Serial ATA 1.0a specifications.
Two Pin header on board for LED connection.
Jumper enable / disable on board SATA BIOS.

Model	RC-220
Type	SATA
Dimension	4.7" x 1.8"
Interface	PCI
Internal Connectors	2 x ATA 133
Transfer Rate	Up to 1.5Gb/s
Operating Systems Supported	Completely with drivers for Windows 98, Windows Millennium, Windows NT 4.0, Windows 2000, Windows 2003 and XP Supports 64bit / 32bit Windows Vista



RC-209-EX

Enterprise-class Throughput - With Ultra/150 Command Queuing technology that optimizes the sequence of data transfers to the hard drive from the host, resulting in higher performance in enterprise applications.
Rugged - Enterprise-class mechanical platform with high-end bearings and actuator.
Unsurpassed Reliability - 1,200,000 hours MTB
RC209-EX with Silicon 3114 can support 4 SATA channels at one time. It can work as a RAID 0/1/0+1/5 HDD controller card or an un-RAID extension card for SATA device (HDD or SATA optical drive)

Model	RC-209-EX
Type	SATA
External Ports	2 x eSATA 1.5G
Interface	PCI 2.3, 32bit, 33/66Mhz
Internal Connectors	2 x ATA 133
Transfer Rate	Up to 1.5Gb/s
Raid	Supports RAID0(striping), RAID1 (mirroring), RAID5(Parity RAID), RAID 0+1(mirroring+striping) and Concaten.
Operating Systems Supported	W2000,XP/2003 32/64bit,Vista 32/64bit



RC-200

Silicon Image Sil 0680
Compliant with UltraDMA6 ATA/133 specifications
Compliant with PCI v2.2 Plug-n-Play
Provides two independent Ultra ATA channels
Full ACPI power management support
Supports Ultra DMA 0-6 and Multi-word DMA 0-2
Supports hard drives larger than 137GB
Supports RAID 0(Striping), RAID1(Mirroring) and RAID 0+1 (Mirror+Striping)
CRC(Cyclical Redundancy Check) error-checking provides data verification and achieves flawless data transfer

Model	RC-200
Type	IDE
Internal Connectors	2 x ATA 133
Interface	PCI
Raid	RAID 0,1,0+1 JBOD
Operating Systems Supported	W2000,XP/2003 32/64bit,Vista 32/64bit

Raid Card

FEATURES

SPECIFICATIONS



RC-215

Chipset: VIA 6421
 Complinat with Serial ATA 1.0 specification.
 Compatible with ATA/ATAPI-6 specifications .
 Compliant with PCI Specification Rev. 2.2.
 Supports all UDMA and PIO modes.
 Supports ACPI .
 Supports the Scatter/Gather function for the DMA/UDMA function.
 Supports PCI power management V1.0 to reduce power consumption.
 Dual independent DMA channels.

Model	RC-215
Type	SATA / IDE
Internal Connectors	2 x SATA 150 + 1 x ATA 133
Interface	PCI
Transfer Rate	Up to 1.5Gb/s
Raid	RAID 0,1,0+1 JBOD
Operating Systems Supported	W2000,XP/2003 32/64bit,Vista 32/64bit



RC-218

Marvell 88SX7042 chipset
 Compliant with PCI Express Base Specification 1.0a
 Compliant with Serial ATA 1.0 specification with support for full complement of SATA II optional features
 Supports SATA II Native Command Queuing (NCQ)
 Provides four independent channels to support up to four Serial ATA drive
 You can select booting from HDD connecting to motherboard or RC-218 (if you want to install a new system from HDD connecting to RC-218, you need a floppy drive to process the installation).

Model	RC-218
Type	SATA II
Transfer Rate	Up to 3Gb/s
External Ports	2 x eSATA
Internal Connectors	4 x SATA II
Interface	PCI Express x4 (x8 and x16 slot compatible)
Operating Systems Supported	Windows 2000, XP/2003/Vista 32/64 bit



RC-213

RC-213 supports Silicon Image "Multilane" function which can work with a Multilane device.
 Multilane is a multi SATA port device which can connect multi SATA input into one SATA output.
 This means RC-213 can connect totally 5 SATA devices by a multilane device with RAID 0/1/0+1/5
 If you use RC-213 without connecting any multilane devices, you can only connect totally 2 SATA device with RAID 0/1..

Model	RC-213
Type	SATA II
Transfer Rate	Up to 3Gb/s
External Ports	1 x eSATA
Internal Connectors	1 x SATA II
Interface	PCI Express
Raid	RAID 0/1/0+1/5
Operating Systems Supported	Windows Sever NT/2003/2000/XP/ Vista 32/64bit



RC-219

RC-213 supports Silicon Image "Multilane" function which can work with a Multilane device.
 Multilane is a multi SATA port device which can connect multi SATA input into one SATA output.
 This means RC-213 can connect totally 5 SATA devices by a multilane device with RAID 0/1/0+1/5
 If you use RC-213 without connecting any multilane devices, you can only connect totally 2 SATA device with RAID 0/1..

Model	RC-219
Type	SATA II
Transfer Rate	Up to 3Gb/s
External Ports	2 x eSATA
Interface	PCI Express
Operating Systems Supported	Completely with drivers for Windows NT, Windows 2000, Windows XP and Windows Server 2003 Supports 64bit / 32bit Windows Vista,Mac OS X v10.4 Non-booting driver supported by SiliconImage Sil3132.,Linux 32bit / 64bit drivers supported for Fedora Core2, Fedora Core3RHEL...



RC-212

Chipset: VIA 6421
 Bus Interface: PCI bus 32 bit
 Rosewill special design of "Magic Switch": RC212 has 2 external and 2 internal SATA ports. You can activate two SATA ports randomly by jumper depending on you need.
 Two modes for RAID (0/1/0+1) or expanding card for ATA/ATAPI/SATA device (Un-RAID) for your needs.

Model	RC-212
Type	SATA / IDE
Transfer Rate	SATA 1.0: up to 150MB/Sec
External Ports	2 x SATA 150
Interface	PCI
Raid	SATA 150 + ATA 133 : Supports Raid 0, 1, 0+1, JBOD, un-RAID mode
Operating Systems Supported	Windows 98SE/ ME/ NT 4.0/2000/XP /Vista 32/64bit/Home Server/Server 2003/ Server 2008

Raid Card

FEATURES

SPECIFICATIONS



RC-201

PCI Interface
Compliant with PCI Specification, revision 2.2.
Integrated PCI DMA engines.
32 bit, 33/66MHz fully compliant PCI host interface.
Sufficient power current 1.5A5V and 2A12V to supply External Device
High Speed Serial ATA Interface
Two special shielded and durable SATA1 connectors for plugging more than 1,000 times
Dual high speed Serial ATA interface ports, each supporting 1st generation Serial ATA data rates (1.5Gb/s).

Model	RC-201
Type	SATA
Internal Connectors	2 x SATA 150
Transfer Rate	1.5Gb/s
Interface	PCI
Raid	RAID 0/1 JBOD
Operating Systems Supported	Windows 98SE/ ME/ NT 4.0/2000/XP/ Vista32/64bit



RC-214

RC-214 supports Silicon Image "Multilane" function which can work with a Multilane device.
Multilane is a multi SATA port device which can connect multi SATA input into one SATA output.
This means RC-214 can connect totally 5 SATA devices by a multilane device.
If you use RC-214 without connecting any multilane devices, you can only connect totally 2 SATA device.

Model	RC-214
Type	SATA II
External Ports	1 x eSATA
Internal Connectors	1 x SATA II
Interface	PCI Express
Transfer Rate	Up to 3Gb/s
Operating Systems Supported	Windows Sever NT/2003/2000/XP/Vista, Windows Server 2003 and 2008 32/64bit



RC-215

Chipset: VIA 6421
Complinat with Serial ATA 1.0 specification.
Compatible with ATA/ATAPI-6 specifications .
Compliant with PCI Specification Rev. 2.2.
Supports all UDMA and PIO modes.
Supports ACPI .
Supports the Scatter/Gather function for the DMA/UDMA function .
Supports PCI power management V1.0 to reduce power consumption
Dual independent DMA channels.

Model	RC-215
Type	SATA / IDE
Internal Connectors	2 x SATA 150 + 1 x ATA 133
Interface	PCI
Transfer Rate	Up to 1.5Gb/s
Operating Systems Supported	Windows 98SE/ME/NT4.0/2000/XP/Vista



RC-216

Compliant with one-lane 2.5Gb/s PCI Express specification
Compliant with Serial ATA 1.0 specification
Supports Native Command Queue (NCQ) on SATA ports
Provides three independent channels to connect two SATA and one PATA hard disk drive
Supports up to UDMA6 transfer mode of PATA
Supports up to 4 storage device connection
RC-216 can connect 2 SATA 3G and 2 ATA 133 HDD max.
You can construct RAID 0/1/0+1/JBOD with 4 HDD.
If you don't set any RAID to this card, it will work as an unRAID card to hook up more HDD to your system.

Model	RC-216
Type	SATA II
Internal Connectors	2 x SATA II + 1 x ATA 133
Interface	PCI Express
Transfer Rate	Up to 3Gb/s
Raid	RAID 0,1,0+1 JBOD
Operating Systems Supported	Windows 2000, Windows XP/2003/Vista 32/64 bit



RC-210

Provides one external E-SATA port and one internal SATA port
Chipset: Silicon Image Sil 3512
Attention: Need a floppy driver on PC if you want to install a new OS into a fresh HD attaching to this card (fresh installation)

Note: RC-210 might not work with some models of SATA optical drive such as DVD burner

Model	RC-210
Type	SATA
Internal Connectors	1 x SATA 150
Interface	PCI
Transfer Rate	1.5 Gb/s (150 MB/s)
Dimensions	4.7" x 1.8"
Operating Systems Supported	Windows 2000, Windows XP/2003/Vista 32/64 bit

Controllers Card



Raid Card

FEATURES

SPECIFICATIONS



RC-211

Chipset: Silicon Image Sil 3132
48 bits LBA can Break Capacity-Limit to Support HDD larger than 137GB
Supports 1-lane 2.5Gbps PCI Express
Hot-plug capability
Fully compliant with Serial ATA 1.0 specifications
Supports two independent Serial ATA channels
Independent Link, Transport, and data FIFO
Independent command fetch, scatter/gather, and command execution

Model	RC-211
Type	SATA II
Internal Connectors	2 x SATA II
Interface	PCI Express
Transfer Rate	3.0Gbps
Raid	RAID 0/1 JBOD
Operating Systems Supported	Windows 2000 / XP / 2003 Server / Vista 32&64bit



RC-217

Provides 2 Brackets to Support Low profile PCI and Regular size PCI in one card
48 bits LBA can Break Capacity-Limit to Support HDD larger than 137GB
Fully compliant with Serial ATA 1.0a and Serial ATA II Extensions to Serial ATA 1.0a Specifications revision 1.1
Hot-plug capability
Supports Serial ATA Generation 2 transfer rate of 3.0 Gb/s
Supports SATA II First-party DMA commands for Native Command Queuing (NCQ)
Supports Serial ATA II Port Multiplier 1.0 Specifications

Model	RC-217
Type	SATA II
Internal Connectors	4 x SATA II
Interface	4 x SATA II
Transfer Rate	Up to 3Gb/s
Raid	RAID 0/1/5/10
Operating Systems Supported	Windows Sever NT/2003/2000/XP/Vista ,Windows Server 2003 and 2008 32/64bit

Home Video

/ HDMI Cable



RCW-H9034

HDMI V1.3a increases the single-link bandwidth to 340MHz (10.2Gbps) and provides maximum capacity for true HDTV resolution up to 1080P and above;
Greater cable bandwidth delivers lossless surround sound and stunning HD video quality today and tomorrow;
HDMI V1.3a broadens color space and supports xvYCC, offering dramatically more colors than standard RGB;
HDMI official Licensed HDMI cable, which passes HDMI ATC testing and supports HDMI CEC(Consumer Electronics Control); Compliant with RoHS standard

Model	RCW-H9034
Type	HDMI
Length	3.3 feet
Connectors	2 High-Speed HDMI cable - V1.3a, Cat. 2 26AWG; OD: 8.5mm
Color	Black/Red
Specifications	2 Gold-Plated HDMI Connectors with durable metal shielding (M - M); Black PVC wrapped with Mesh



RCW-H9035

HDMI V1.3a increases the single-link bandwidth to 340MHz (10.2Gbps) and provides maximum capacity for true HDTV resolution up to 1080P and above;
Greater cable bandwidth delivers lossless surround sound and stunning HD video quality today and tomorrow;
HDMI V1.3a broadens color space and supports xvYCC, offering dramatically more colors than standard RGB;
HDMI official Licensed HDMI cable, which passes HDMI ATC testing and supports HDMI CEC(Consumer Electronics Control); Compliant with RoHS standard

Model	RCW-H9035
Type	HDMI
Length	6 feet
Connectors	2 High-Speed HDMI cable - V1.3a, Cat. 2 26AWG; OD: 8.5mm
Color	Black/Red
Specifications	2 Gold-Plated HDMI Connectors with durable metal shielding (M - M); Black PVC wrapped with Mesh



RCW-H9036

HDMI V1.3a increases the single-link bandwidth to 340MHz (10.2Gbps) and provides maximum capacity for true HDTV resolution up to 1080P and above;
Greater cable bandwidth delivers lossless surround sound and stunning HD video quality today and tomorrow;
HDMI V1.3a broadens color space and supports xvYCC, offering dramatically more colors than standard RGB;
HDMI official Licensed HDMI cable, which passes HDMI ATC testing and supports HDMI CEC(Consumer Electronics Control); Compliant with RoHS standard

Model	RCW-H9036
Type	HDMI
Length	10 feet
Connectors	2 High-Speed HDMI cable - V1.3a, Cat. 2 26AWG; OD: 8.5mm
Color	Black/Red
Specifications	2 Gold-Plated HDMI Connectors with durable metal shielding (M - M); Black PVC wrapped with Mesh

HDMI / Switch

FEATURES

SPECIFICATIONS



RME-002

Supports Digital video & audio by HDMI 1.1, 1.2 & 1.3 specification
Connects audio & video to HDMI compatible HDTV, LCD Monitors or Digital projectors
Switching: User could select anyone of the three or five HDMI inputs to the output
Signaling rates up to 2.25GBPS in support of UXGA and 1080P display
8-dB Receiver Equalization to compensate for 5 meters HDMI cable losses. Supports HDCP compliant devices
Discrete IR remote (included)

Model	RME-002
Type	HDMI Switch
Color	Black
Terminations	3 in 1 out
Specifications	PC: VGA/SVGA/XGA/SXGA/UXGA DTV/HDTV: 1080i/p, 720p, 480p, 576p Humidity: 5 to 90 % RH (no condensation) Dimensions: 8.86" x 1.38" x 5.12" Weight: 0.73 lbs. Power: 5V DC, 15 Watts (max.)

Headsets



RH-001

- In-line volume control
- Full-range stereo sound
- Ideal for Video Conferencing, Gaming, Music, and Movies

Model	RH-001
Frequency Response	20Hz-20KHz
Input Impedance	32 ohm
Sensitivity	102dB \pm 4dB
Connector	3.5mm
Microphone	
Frequency Response	50Hz-16KHz
Microphone	
Sensitivity	-60dB \pm 3dB



RH-40C

- In-line volume control
- Full-range stereo sound
- Superior Audio Performance
- Its comfortable headset allows long duration of use
- Ideal for Video Conferencing, Gaming, Music, and Movies

Model	RH-40C
Frequency Response	20Hz-20KHz
Input Impedance	32 ohm
Sensitivity	102dB \pm 4dB
Connector	3.5mm
Ear Coupling	Circumaural
Cord Length	6 Feet.
Microphone	
Frequency Response	50Hz-16KHz
Microphone	
Sensitivity	-60dB \pm 3dB



RHM-556

Special patented structure which folds the actual head-phone into a small foot ball saving your desk space or the drawers!
Featuring 40mm Special Mylar Cone speaker generates amazing surround sound with bass this small headphone gives you the whole new sound experience!
Ear shaped pads provides complete shielding for clearer, crispier sound or music to your expectations. Best of all, the Omnidirectional MIC is hidden right in the headphone housing, no more banding, twisting or turning around the MIC just simply hide it back to the headphone!

Model	RHM-556
Frequency Response	10Hz-25KHz
Input Impedance	50 ohm
Sensitivity	97dB \pm 3dB
Connector	3.5mm
Ear Coupling	Circumaural
Cord Length	9.8 Feet.
Microphone	
Frequency Response	70Hz-20KHz
Microphone	
Sensitivity	-38dB \pm 3dB

TV Brackets

FEATURES

SPECIFICATIONS



RMS-A0030

Enables a VESA 100 Mount to accept a VESA 200 or 100x200 display

Model	RMS-A0030
Type	VESA Adapter
Color	Silver
Dimensions	3.3"x1.8"x9"
Color	Black/Red
Weight	1 lbs
VESA Compatible	100 x 100 to 100 x 200 or 200 x 200



RMS-MS2740

Tilt/Swivel LCD Monitor Wall Mount
Solid aluminum alloy construction
Integrated bubble level
Profile: 7.2 - 16.2 cm (2.8 - 6.4")
Mount Pattern: 100 x 100 mm (max)

Model	RMS-MS2740
TV Size Capacity	13" - 27"
TV Weight Capacity	Max. load 40 lbs
Profile Range	2.8 - 6.4"
Tilt Range	+15° to -15°
Swivel Range	90° left to 90° right
Mounting Pattern	VESA 75, VESA 100
Color	Silver
Dimension	7"x7"x2.4"
Weight	1.5 lbs



RMS-MT5010

Universal design to fit most 37" to 50" flat-panel screens
Heavy-gauge steel construction with powder-coated finish
Lockable design to ensure the safety of your display (lock not included)
Tilts up and down for better viewing angle
Integrated bubble level
Cable management
Quick and easy installation
Hardware for wood stud or concrete installation
Tilts up and down

Model	RMS-MT5010
TV Size Capacity	37" - 50"
TV Weight Capacity	Max. load 132 lbs
Profile Range	3.6"
Tilt Range	+15° to -15°
Swivel Range	n/a
Mounting Pattern	675 mm x 500 mm max
Color	Black
Dimension	33.3"x13"x3.7"
Weight	19 lbs



RMS-MT3710

Universal design to fit most 23" to 37" flat-panel screens
Heavy-gauge steel construction with powder-coated finish
Lockable design to ensure the safety of your display (lock not included)
Tilts up and down for better viewing angle
Integrated bubble level
Cable management
Quick and easy installation
Hardware for wood stud or concrete installation

Model	RMS-MT3710
TV Size Capacity	23" - 37"
TV Weight Capacity	Max. load 88 lbs
Profile Range	3.5"
Tilt Range	+15° to -15°
Swivel Range	n/a
Mounting Pattern	445 mm x 320 mm max
Color	Black
Dimension	24.3"x11.7"x3.4"
Weight	13 lbs



RMS-MT2790

Designed to fit most 13" to 27" flat-panel screens
Tilt and swivel ensure the optimum viewing angle
Solid aluminum alloy construction
Integrated bubble level
Cable management
Quick and easy installation
VESA 75 and 100 compatible
One-touch tilt adjustment -- no knobs to loosen
Fully rotatable (landscape to portrait)
Hardware for wood stud or concrete installation

Model	RMS-MT2790
TV Size Capacity	13" - 27"
TV Weight Capacity	Max. load 44 lbs
Profile Range	3.7"
Tilt Range	+13.8° to -13.8°
Swivel Range	35° left to 35° right
Mounting Pattern	VESA 75, VESA 100
Color	Silver
Dimension	7"x5"x3.6"
Weight	1.8 lbs

TV Brackets

FEATURES

SPECIFICATIONS



RMS-MT2710

Designed to fit most 13" to 27" flat-panel screens
 Tilts up and down for better viewing angle
 Solid aluminum alloy construction
 Integrated bubble level
 Cable management
 Quick and easy installation
 VESA 75 and 100 compatible
 Hardware for wood stud or concrete installation

Model	RMS-MT2710
TV Size Capacity	13" - 27"
TV Weight Capacity	Max. load 44 lbs
Profile Range	2.8"
Tilt Range	+15° to -15°
Swivel Range	n/a
Mounting Pattern	VESA 75, VESA 100
Color	Silver
Dimension	7.3"x5"x2.8"
Weight	1.5 lbs



RMS-MF2720

Designed to fit most 13" to 27" flat-panel screens
 Ultra-slim design maximizes the sleek look of flat panel screens
 Solid steel construction
 Quick and easy installation
 VESA 75 and 100 compatible
 Hardware for wood stud or concrete installation
 Safety screws included
 Powder-coated finish

Model	RMS-MF2720
TV Size Capacity	13" - 27"
TV Weight Capacity	Max. load 55 lbs
Profile Range	0.6"
Tilt Range	n/a
Swivel Range	n/a
Mounting Pattern	VESA 75, VESA 100
Color	Black
Dimension	6.3"x5.2"x0.8"
Weight	1.3 lbs



RMS-MA2740

Designed to fit most 13" to 27" flat-panel screens
 Extend, retract, tilt and swivel your TV for optimum viewing angle
 Solid aluminum alloy construction
 Integrated bubble level
 Cable management
 Quick and easy installation
 VESA 75 and 100 compatible
 Hardware for wood stud or concrete installation

Model	RMS-MA2740
TV Size Capacity	13" - 27"
TV Weight Capacity	Max. load 40 lbs
Profile Range	2.8" - 9.9"
Tilt Range	+15° to -15°
Swivel Range	90° left to 90° right
Mounting Pattern	VESA 75, VESA 100
Color	Silver
Dimension	8.1"x6.9"x2.4"
Weight	2.43 lbs



RMS-A871

Easy installation and strong combination both
 Adjustable screw position for TV backside mount
 TV backside screw range: 75X75, 100X100, 200X100, 200X200mm
 TV backside screw size: M4, M5, M6
 Backward & forward tilting angle: -5° ~ 15°
 Left & right leveling angle: -10° ~ 10°
 Between TV backside and Wall distance: 68 - 464mm (2.6 - 18")
 Cable management with metal wire

Model	RMS-A871
Type	TV Wall Bracket
Loading	66lbs. (~37" TV weight without stand)
Weight	7.7 lbs



RMS-A650

Features Easy to install (with animation user instruction)
 Fits most large flat panel plasma and LCD TVs
 Adjustable screw position for TV backside mount
 Include different size screws for your TV hole
 Solid steel construction
 Pivot upwards & downwards: 26 degrees

Model	RMS-A650
Color	Black
Dimension	790x195x320 mm
Compatibility	TV size range: 30"~70" TV backside horizontal screw range: 4~69cm(2"~27") TV backside vertical screw range: 6~50cm(2"~19") Support up to 176lbs or 80kgs (90" TV weight)

TV Brackets

FEATURES

SPECIFICATIONS



RMS-A171

Adjustable screw in height range: 1510/1825/2140mm (59"/71.8"/84")
Cannular pole is used to insert cable
Pole diameter: 35mm (1.3")

Model	RMS-A171
TV Size Capacity	Up to 42"
TV Weight Capacity	Max. load 110 lbs.
Color	Black
Mount Style	Ceiling
Movable	360 degree display Swivel left & right: 20 degree Pivot downwards: 45 degree



RMS-MA5010

Full-motion LCD/Plasma TV Wall Mount
Steel and aluminum construction
Integrated bubble level
Lockable for added security (lock not included)
Profile: 5.0" - 16.0"
Mount Pattern: 800 x 500 mm (max)

Model	RMS-MA5010
TV Size Capacity	37" - 50"
TV Weight Capacity	Max. load 132 lbs.
Color	Black
Mount Style	Wall
Movable	Tilt: 15° down Pan: 90°



RMS-MT4020

Universal Tilt LCD/Plasma TV Wall Mount
Sturdy steel construction
Lockable safety bar for added security (lock not included)
Profile: 6.3 cm (2.5")
Mount Pattern: 500 x 320 mm (max)

Model	RMS-MT4020
Name	Tilt Wall Mount
TV Size Capacity	23" - 37"
TV Weight Capacity	Max. load 88 lbs.
Color	Black
Mount Style	Wall
Movable	Tilt: 15° down



RMS-MA3210

Full-motion LCD Wall Mount
Sturdy steel construction
Profile: 10.8- 35 cm (4.3 - 13.8")
Mount Pattern: 200 x 200 mm (max)

Movable: Tilt: 15° up/down, Pan: 180°

Model	RMS-MA3210
Name	Tilt/Swivel Wall Mount
Mount Style	Wall
Color	Silver
TV Size Capacity	17" - 32"
TV Weight Capacity	Max. load 55 lbs.
Color	Silver
Cable Management	Cable Management

ATX

FEATURES

SPECIFICATIONS



RBR1000-M

Over Temperature/Current/Voltage/Power Protection, Under Voltage Protection, and Short Circuit Protection provide maximum safety to your critical system components. Supports ATX12V v2.3 & EPS12V standards. Supports both Intel and AMD Systems. Four 12V rails provide independent reliable power. Active power Factor Correction(PFC) provides clean and reliable power to your system. Universal AC input 90~264V automatically scans and detects the correct voltage. Modular Cable Design.

Model	RBR1000-M
Type	ATX12V v2.3/ EPS12V
Max. Power	Continuous 1000W @ 40°C
Input Voltage	100 - 240 V
Input Current	13A
Efficiency	Up to 85% efficiency
Main Connector	20+4Pin
+12V Rails	4
Output	+3.3V@28A,+5V@30A,+12V1@20A, +12V2@20A,+12V3@30A,+12V4@30A,
MTBF	>100,000 Hours



RBR850-M

Over Temperature/Current/Voltage/Power Protection, Under Voltage Protection, and Short Circuit Protection provide maximum safety to your critical system components. Supports ATX12V v2.3 & EPS12V standards. Supports both Intel and AMD Systems. Four 12V rails provide independent reliable power. Active power Factor Correction(PFC) provides clean and reliable power to your system. Universal AC input 90~264V automatically scans and detects the correct voltage. Modular Cable Design.

Model	RBR850-M
Type	ATX12V v2.3/ EPS12V
Max. Power	Continuous 850W @ 40°C
Input Voltage	100 - 240 V
Input Current	10A
Efficiency	Up to 85% efficiency
Main Connector	20+4Pin
+12V Rails	4
Output	+3.3V@28A,+5V@30A,+12V1@20A, +12V2@20A,+12V3@30A,+12V4@30A
MTBF	>100,000 Hours



RBR750-M

Over Temperature/Current/Voltage/Power Protection, Under Voltage Protection, and Short Circuit Protection provide maximum safety to your critical system components. Supports ATX12V v2.3 & EPS12V standards. Supports both Intel and AMD Systems. Four 12V rails provide independent reliable power. Active power Factor Correction(PFC) provides clean and reliable power to your system. Universal AC input 90~264V automatically scans and detects the correct voltage. Modular Cable Design.

Model	RBR750-M
Type	ATX12V v2.3/ EPS12V
Max. Power	Continuous 750W @ 40°C
Input Voltage	100 - 240 V
Input Current	10A
Efficiency	Up to 85% efficiency
Main Connector	20+4Pin
+12V Rails	4
Output	+3.3V@28A,+5V@30A,+12V1@18A, +12V2@18A,+12V3@18A,+12V4@18A
MTBF	>100,000 Hours



RBR1000-M

Over Temperature/Current/Voltage/Power Protection, Under Voltage Protection, and Short Circuit Protection provide maximum safety to your critical system components. Supports ATX12V v2.3 & EPS12V standards. Supports both Intel and AMD Systems. Four 12V rails provide independent reliable power. Active power Factor Correction(PFC) provides clean and reliable power to your system. Universal AC input 90~264V automatically scans and detects the correct voltage. Modular Cable Design.

Model	RBR1000-M
Type	ATX12V v2.3/ EPS12V
Max. Power	Continuous 1000W @ 40°C
Input Voltage	100 - 240 V
Input Current	13A
Efficiency	Up to 85% efficiency
Main Connector	20+4Pin
+12V Rails	4
Output	+3.3V@28A,+5V@30A,+12V1@20A, +12V2@20A,+12V3@30A,+12V4@30A,
MTBF	>100,000 Hours



RBR850-M

Over Temperature/Current/Voltage/Power Protection, Under Voltage Protection, and Short Circuit Protection provide maximum safety to your critical system components. Supports ATX12V v2.3 & EPS12V standards. Supports both Intel and AMD Systems. Four 12V rails provide independent reliable power. Active power Factor Correction(PFC) provides clean and reliable power to your system. Universal AC input 90~264V automatically scans and detects the correct voltage. Modular Cable Design.

Model	RBR850-M
Type	ATX12V v2.3/ EPS12V
Max. Power	Continuous 850W @ 40°C
Input Voltage	100 - 240 V
Input Current	10A
Efficiency	Up to 85% efficiency
Main Connector	20+4Pin
+12V Rails	4
Output	+3.3V@28A,+5V@30A,+12V1@20A, +12V2@20A,+12V3@30A,+12V4@30A
MTBF	>100,000 Hours

ATX

FEATURES

SPECIFICATIONS



RBR750-M

Over Temperature/Current/Voltage/Power Protection, Under Voltage Protection, and Short Circuit Protection provide maximum safety to your critical system components
 Supports ATX12V v2.3 & EPS12V standards
 Supports both Intel and AMD Systems
 Four 12V rails provide independent reliable power
 Active power Factor Correction(PFC) provides clean and reliable power to your system
 Universal AC input 90~264V automatically scans and detects the correct voltage
 Modular Cable Design

Model	RBR750-M
Type	ATX12V v2.3/ EPS12V
Max. Power	Continuous 750W @ 40°C
Input Voltage	100 - 240 V
Input Current	10A
Efficiency	Up to 85% efficiency
Main Connector	20+4Pin
+12V Rails	4
Output	+3.3V@28A, +5V@30A, +12V1@18A, +12V2@18A, +12V3@18A, +12V4@18A
MTBF	>100,000 Hours



RV300

Over temperature, over current, and over voltage protection circuits. Switching power supply
 Connectors:
 1 x Main connector (20+4Pin)
 1 x 12V (P4)
 6 x peripheral
 2 x SATA
 2 x Floppy
 Approvals: CE, cUL, CSA, CB, TUV, FCC, NEMKO, DEMKO, SEMKO, TC

Model	RV300
Type	ATX12V
Max. Power	300W
Input Voltage	115/ 230 V
Input Current	10A @ 115V, 6A @ 230V
Efficiency	70% min. under max. range load
Main Connector	20+4Pin
+12V Rails	Single
Output	+3.3V@28A, +5V@30A, -5V@0.3A, +12V@15A, -12V@0.8A, +5VSB@2A
MTBF	Single



RV350

Over temperature
 Over current and over voltage protection circuits
 Connectors:
 1 x Main connector (20Pin)
 1 x AUX Power
 1 x 12V (P4)
 6 x peripheral
 2 x SATA
 2 x Floppy
 Approvals: CSA, CB, TUV, FCC, UL

Model	RV350
Type	ATX 1.3
Max. Power	350W
Input Voltage	115/ 230 V
Input Current	8/4A
Efficiency	60% min. under max. range load
Main Connector	20Pin
+12V Rails	Single
Output	+3.3V@28A, +5V@35A, +12V@15A, -5V@0.5A, -12V@0.8A, +5VSB@2.5A
MTBF	100k hours at max, normal line and 25°C



RP500

Black Chrome Mirror Finish, over temperature, over current, and over voltage protection circuits
 Switching power supply
 Connectors:
 1x 20+4-Pin Main Connector
 1x 4+4-Pin ATX12V/EPS12V Connector
 1x 6-Pin PCI-E Connector
 6x 4-Pin Peripheral Connector
 4x 5-Pin SATA Connector
 2x 4-Pin Floppy Connector
 Approvals: CSA, CB, TUV, FCC, UL

Model	RP500
Type	ATX12V v1.3/ EPS12V
Max. Power	500W
Input Voltage	115/ 230 V
Input Current	10A/5.5A
Efficiency	> 70%
Main Connector	24Pin
+12V Rails	Single
Output	+3.3V@30A, +5V@45A, +12V@26A, -5V@0.5A, -12V@1A, +5VSB@2.5A
MTBF	100k hours at max, normal line and 25°C



RP550

Black Chrome Mirror Finish, over current, and over voltage protection circuits, Switching power supply
 Connectors:
 1x 20+4-Pin Main Connector
 1x 4+4-Pin ATX12V/EPS12V Connector
 1x 6-Pin PCI-E Connector
 6x 4-Pin Peripheral Connector
 4x 5-Pin SATA Connector
 2x 4-Pin Floppy Connector
 Approvals: CSA, CB, TUV, FCC, UL

Model	RP550
Type	ATX V1.3/ EPS12V
Max. Power	550W
Input Voltage	115/ 230 V
Input Current	10A/5.5A
Efficiency	60% min. under max. range load
Main Connector	24Pin
+12V Rails	Single
Output	+3.3V@30A, +5V@50A, +12V@35A, -5V@0.5A, -12V@1A, +5VSB@2.5A
MTBF	100k hours at max, normal line and 25°C

ATX

FEATURES

SPECIFICATIONS



RP500-2

Black Chrome Mirror Finish, over temperature/current/voltage protection circuits
Connectors:
1 x 20+4Pin Main Connector
1 x 4Pin ATX12V Connector
1 x 8Pin EPS12V Connector
1 x 6Pin PCI-Express Connector
2 x 5Pin SATA Connector
8 x 4Pin Peripheral Connector
2 x 4Pin Floppy Connector
Approvals: CSA, UL, TUV, FCC

Model	RP500-2
Type	ATX12V v2.01
Max. Power	500W
Input Voltage	115/ 230 V
Input Current	10/ 5.5A
Efficiency	> 72% min. under max. range load
Main Connector	20+4Pin
+12V Rails	Single
Output	+3.3V@30A, +5V@45A, +12V1@18A, +12V2@16A, -12V@1A, +5VSB@2.5A
MTBF	100k hours at 25°C, max. load, nominal in.



RP550-2

Black Chrome Mirror Finish, over temperature/current/voltage protection circuits
Connectors:
1 x 20+4Pin Main Connector
1 x 4Pin ATX12V Connector
1 x 8Pin EPS12V Connector
1 x 6Pin PCI-Express Connector
2 x 5Pin SATA Connector
8 x 4Pin Peripheral Connector
2 x 4Pin Floppy Connector
Approvals: CSA, UL, TUV, FCC

Model	RP550-2
Type	ATX12V v2.01
Max. Power	550W
Input Voltage	115/ 230 V
Input Current	10A/ 5.5A
Efficiency	> 72%
Main Connector	20+4Pin
+12V Rails	2
Output	+3.3V@30A, +5V@50A, +12V1@18A, +12V2@18A, -12V@1A, +5VSB@2.5A
MTBF	100k hours at 25°C, max. load, nominal in.



RD400-2-DB

Smart Temperature Sensor, over temperature/current/voltage protection circuits
Connectors:
1x 20+4 pin Main Connector
1x 4 pin ATX12V Connector
1x 8 pin EPS12V Connector
1x 6 pin PCI-Express Connector
6x 4 pin Peripheral Connector (Quick-release)
2x 5 pin SATA Connector
2x 4 pin Floppy Connector
Approvals: UL, CSA, TUV, FCC

Model	RD400-2-DB
Type	ATX V2.2
Max. Power	400W
Input Voltage	115/ 230 V
Input Current	10A @ 115V, 6A @ 230V
Main Connector	20+4Pin
+12V Rails	2
Output	+3.3V@20A, +5V@14A, +12V1@14A, +12V2@13A, -12V@0.3A, +5VSB@2.5A
MTBF	100k hours at max. load, normal line and 25°C



RD450-2-DB

Over temperature/current/voltage protection circuits
Connectors:
1 x 20+4Pin Main Connector
1 x 4Pin ATX12V Connector
1 x 8Pin EPS12V Connector
1 x 6Pin PCI-Express Connector
6 x 4Pin Peripheral Connector (Quick-release)
2 x 5Pin SATA Connector
2 x 4Pin Floppy Connector
Approvals: CSA, UL, TUV, FCC

Model	RD450-2-DB
Type	ATX V2.2
Max. Power	450W
Input Voltage	115V (90-132V) / 230V (180-253V)
Input Current	10A @ 115V, 6A @ 230V
Main Connector	20+4Pin
+12V Rails	2
Output	+3.3V@22A, +5V@15A, +12V1@14A, +12V2@16A, -12V@0.3A, +5VSB@2.5A
MTBF	100k hours at max. load, normal line and 25°C



RV350-2

over temperature, over current and over voltage protection circuits
Connectors:
1 x Main connector with 20+4-pin
1 x 12V (P4)
6 x peripheral Quick release connectors
2 x SATA
2 x Floppy
Approvals: UL, CSA, TUV, FCC

Model	RV350-2
Type	ATX 2.2
Max. Power	350W
Input Voltage	115/ 230 V
Input Current	8/ 4A
Main Connector	20+4Pin
+12V Rails	2
Output	+3.3V@20A, +5V@12A, +12V1@10A, +12V2@13A, -12V@0.3A, +5VSB@2.5A

ATX

FEATURES

SPECIFICATIONS



RP550V2-D-SL

Over Voltage/Current/Power Protection circuits
Connectors:
1 x 20+4Pin Main Connector
1 x 4/8Pin +12V Connector (ATX12V/EPS12V)
2 x 6Pin PCI-Express Connector
4 x 5Pin SATA Connector
6 x 4Pin Peripheral Connector
2 x 4Pin Floppy Connector
Approvals: CSA, UL, TUV, FCC

Model	RP550V2-D-SL
Type	ATX12V v2.01
Max. Power	550W
Input Voltage	115/ 230 V
Input Current	10A/ 5.5A
Main Connector	20+4Pin
+12V Rails	2
Output	+3.3V@30A,+5V@50A,+12V1@18A,+12V2@18A,-12V@1A,+5 VSB@2.5A
MTBF	100k hours at max. load, normal line and 25°C



RP550V2-S-SL

Black Mirror Effect Housing, Over temperature protection circuit.Over current protection circuit. Over voltage protection circuits
Connectors:
1 x Main connector (20+4Pin)
1 x 4/8Pin ATX12V & EPS12V Connector
4 x SATA
2 x PCI-E
6 x peripheral(Molex Easy-release connector applied)
2 x Floppy
Approvals: CSA, CB, TUV, FCC, UL

Model	RP550V2-S-SL
Type	ATX12V v2.01
Max. Power	550W
Input Voltage	115/ 230 V
Input Current	12A @ 115V, 6A @ 230V
Main Connector	20+4Pin
+12V Rails	2
Output	+3.3V@30A, +5V@50A, +12V1@18A, +12V2@18A, -12V@1A, +5VSB@2.5A
MTBF	>100,000 Hours



RP600V2-S-SL

Black Shiny Finish. Over Current/Voltage/Power Protection, Under Voltage Protection, and Short Circuit Protection.
Connectors:
1x 20+4-pin Main Connector
1x 4+4-pin ATX12V/EPS12V Connector
1x 6-pin PCI-Express Connector
1x 6+2-pin PCI-Express Connector
4x 5-pin SATA Connector
6x 4-pin Peripheral Connector
2x 4-pin Floppy Connector
Approvals: CSA,UL,TUV, FCC

Model	RP600V2-S-SL
Type	ATX12V v2.01
Max. Power	600W
Input Voltage	115/ 230 V
Input Current	12A/ 6A
Main Connector	20+4Pin
+12V Rails	2
Output	+3.3@30A,+5V@55A,+12V1@19A,+12V2@19A,-12V@1A,+5V SB@2.5A
MTBF	100k hours at 25°C, max. load, nominal input



RD500-2DB

Over temperature/current/voltage protection circuits
Connectors:
1 x 20+4Pin Main Connector
1 x 4Pin ATX12V Connector
1 x 8Pin EPS12V Connector
2 x 6Pin PCI-Express Connector
6 x 4Pin Peripheral Connector (Quick-release)
2 x 5Pin SATA Connector
2 x 4Pin Floppy Connector
Approvals: CSA, UL, TUV, FCC

Model	RD500-2DB
Type	ATX12V
Max. Power	500W
Input Voltage	115/ 230 V
Input Current	10A / 6A
Main Connector	20+4Pin
+12V Rails	2
Output	+3.3V@22A,+5V@16A,+12V1@15A,+12V2@16A,-12V@0.8A, +5VSB@2.5A
MTBF	100k hours at max. load, normal line and 25°C



RP600V2-S-SL-S

Over temperature/current/voltage protection circuits
Connectors:
1 x Main Connector (20+4Pin)
1 x 4/8Pin +12V Connector (ATX12V/EPS12V)
2 x PCI-E Connector (6Pin)
4 x SATA Connector
6 x Peripheral Connector
2 x Floppy Connector
Approvals: CSA, UL, TUV, FCC

Model	RP600V2-S-SL-S
Type	ATX12V v2.01
Max. Power	600W
Input Voltage	115/ 230 V
Input Current	12A @ 115V, 6A @ 230V
Main Connector	20+4Pin
+12V Rails	Yes
Output	+3.3V@30A, +5V@55A, +12V1@19A, +12V2@19A, -12V@1A, +5VSB@2.5A
MTBF	100k hours at 25°C, max. load, nominal input

ATX

FEATURES

SPECIFICATIONS



RX750-S-B

Over temperature/current/voltage protection circuits

Connectors:

- 1 x Main Connector (20+4Pin)
 - 1 x 4/8Pin +12V Connector (ATX12V/EPS12V)
 - 2 x PCI-E Connector (6Pin)
 - 4 x SATA Connector
 - 6 x Peripheral Connector
 - 2 x Floppy Connector
- Approvals: TUV, FCC, UL, CE, RoHS

Model	RX750-S-B
Type	ATX12V v2.2 & EPS12V v2.91
Max. Power	750W
Input Voltage	100 - 240 V
Input Current	15A/ 7.5A
Main Connector	20+4Pin
+12V Rails	4
Output	+3.3V@24A,+5V@30A,+12V1@20A,+12V2@20A,+12V3@20A, +12V4@20A,-12V@0.5A,+5VSB@3A
MTBF	100k hours at 25°C, max. load, nominal in.



RX750-D-B

Black Chrome Mirror Finish, over temperature/current/voltage protection circuits

Connectors: 1 x 20+4Pin Main Connector

- 1 x 4Pin ATX12V Connector
 - 1 x 8Pin EPS12V Connector
 - 4 x 6Pin PCI-Express Connector
 - 6 x 4Pin Peripheral Connector
 - 6 x 5Pin SATA Connector
 - 2 x 4Pin Floppy Connector
 - 1 x PCI-E 6pin to 8pin Adapter
- Approvals: UL,FCC,CSA,CB,CE,TUV,ROHS

Model	RX750-D-B
Type	ATX12V v2.2 & EPS12V v2.91
Max. Power	750W
Input Voltage	100 - 240 V
Input Current	15A/ 7.5A
Main Connector	20+4Pin
+12V Rails	Four +12V Rails
Output	+3.3V@24A,+5V@30A,+12V1@20A,+12V2@20A,+12V3@20A, +12V4@20A,-12V@0.5A,+5VSB@3A
MTBF	100k hours at 25°C, max. load, nominal in.



RX850-S-B

Black Chrome Mirror Finish. over temperature/current/voltage protection circuits

Connectors: 1 x 20+4Pin Main Connector

- 1 x 4Pin ATX12V Connector
 - 1 x 8Pin EPS12V Connector
 - 4 x 6Pin PCI-Express Connector
 - 6 x 4Pin Peripheral Connector
 - 6 x 5Pin SATA Connector
 - 2 x 4Pin Floppy Connector
 - 1 x PCI-E Pin to 8Pin Adapter
- Approvals: UL,FCC,CSA,CB,CE,TUV,ROHS

Model	RX850-D-B
Type	ATX12V v2.2 & EPS12V v2.91
Max. Power	850W
Input Voltage	100 - 240 V
Input Current	15A/ 7.5A
Main Connector	20+4Pin
+12V Rails	Four +12V Rails
Output	+3.3V@24A,+5V@30A,+12V1@20A,+12V2@20A,+12V3@20A, +12V4@20A,-12V@0.5A,+5VSB@3A
MTBF	100k hours at 25°C, max. load, nominal in.



RX850-S-B

Black Chrome Mirror Finish. Over temperature/current/voltage protection circuits

Connectors: 1 x 20+4Pin Main Connector

- 1 x 4Pin ATX12V Connector
 - 1 x 8Pin EPS12V Connector
 - 4 x 6Pin PCI-Express Connector
 - 6 x 4Pin Peripheral Connector
 - 6 x 5Pin SATA Connector
 - 2 x 4Pin Floppy Connector
 - 1 x PCI-E 6pin to 8pin Adapter
- Approvals: TUV, FCC, UL, CE, ROHS

Model	RX850-S-B
Type	ATX12V v2.2 & EPS12V v2.91
Max. Power	850W
Input Voltage	100 - 240 V
Input Current	15A/ 7.5A
Main Connector	20+4Pin
+12V Rails	Four +12V Rails
Output	+3.3V@24A,+5V@30A,+12V1@20A,+12V2@20A, +12V3@20A, +12V4@20A,-12V@0.5A,+5VSB@3A
MTBF	100k hours at 25°C, max. load, nominal in.



RD400-2-SB

Over temperature, over current and over voltage protection circuits

Connectors:

- 1 x Main connector (20+4Pin)
 - 1 x 12V (P4)
 - 1 x 12V (8Pin)
 - 6 x peripheral Quick release connectors
 - 2 x SATA
 - 2 x Floppy
 - 1 x PCI-E
- Approvals: UL, CSA, TUV, FCC

Model	RD400-2-SB
Type	ATX V2.2
Max. Power	400W
Input Voltage	115/ 230 V
Input Current	10A @ 115V, 6A @ 230V
Main Connector	20+4Pin
+12V Rails	2
Output	+3.3V@20A, +5V@14A, +12V1@14A, +12V2@13A,-12V@0.3A, +5VSB@2.5A
MTBF	100k hours at max. load, normal line and 25°C

ATX

FEATURES

SPECIFICATIONS



RD450-2-SB

Over current and over voltage protection circuits
Connectors:
1 x Main connector (20+4Pin)
1 x 12V (P4)
1 x 12V (8Pin)
6 x peripheral Quick release connectors
2 x SATA
2 x Floppy
1 x PCI-E
Approvals:
UL, CSA, TUV, FCC

Model	RD450-2-SB
Type	ATX V2.2
Max. Power	450W
Input Voltage	115/ 230 V
Input Current	10A @ 115V, 6A @ 230V
Main Connector	20+4Pin
+12V Rails	2
Output	+3.3V@22A, +5V@15A, +12V1@14A, +12V2@16A, -12V@0.3A, +5VSB@2.5A



RD500-2SB

Connectors:
1 x Main connector (20+4Pin)
1 x 12V (P4)
1 x 12V (8Pin)
6 x peripheral Quick release connectors
2 x SATA
2 x Floppy
1 x PCI-E
Approvals: V UL, CSA, TUV, FCC

Model	RD500-2SB
Type	ATX12V v2.2
Max. Power	500W
Input Voltage	115/ 230 V
Input Current	15A/ 7.5A
Main Connector	10A @ 115V, 6A @ 230V
+12V Rails	2
Output	+3.3V@22A, +5V@16A, +12V1@15A, +12V2@16A, -12V@0.8A, +5VSB@2.5A
MTBF	>100,000 Hours



RD550N-2DB-SL-BK

Over temperature, over current, and over voltage protection circuits
Connectors:
1 x Main connector (20+4Pin)
1 x 12V (P4)
1 x 12V (8Pin)
4 x peripheral Quick release connectors
4 x SATA
2 x Floppy
2 x PCI-E
Approvals: CSA, UL, TUV

Model	RD550N-2DB-SL-BK
Type	ATX Form Factor 12V V2.2 / SSI standard EPS 12V
Max. Power	550W
Input Voltage	Auto Switching (90-264V)
Input Current	10A @ 115V, 6A @ 230V
Main Connector	20+4Pin
+12V Rails	2
Output	+3.3V@24A, +5V@24A, +12V1@20A, +12V2@18A, -12V@0.5A, +5VSB@2.5A
MTBF	100k hours at max., normal line and 25°C



RD550N-2DC-SL-SLV

Over temperature, over current, and over voltage protection circuits
Connectors:
1 x Main connector (20+4Pin)
1 x 12V (P4)
1 x 12V (8Pin)
7 x peripheral Quick release connectors
2 x SATA
2 x Floppy
2 x PCI-E
Approvals: CSA, UL, TUV

Model	RD550N-2DC-SL-SLV
Type	ATX Form Factor 12V V2.2 / SSI standard EPS 12V
Max. Power	550W
Input Voltage	Auto Switching (90-264V)
Input Current	10A @ 115V, 6A @ 230V
Main Connector	20+4Pin
+12V Rails	2
Output	+3.3V@24A, +5V@24A, +12V1@20A, +12V2@18A, -12V@0.5A, +5VSB@2A
MTBF	100k hours at max., normal line and 25°C



RX950-S-B

Connectors:
1 x 20+4Pin Main Connector
1 x 4Pin ATX12V Connector
1 x 8Pin EPS12V Connector
2 x 8Pin PCI-Express Connector
2 x 6Pin PCI-Express Connector
6 x 4Pin Peripheral Connector
6 x 5Pin SATA Connector
2 x 4Pin Floppy Connector
2 x PCI-E 8pin to 6pin Adapter
Approvals: TUV, FCC, UL, CE, ROHS

Model	RX950-S-B
Type	ATX 12V v2.2 & EPS 12V v2.91
Max. Power	950W
Input Voltage	100 - 240 V
Input Current	15.0A / 7.5A
Main Connector	20+4Pin
+12V Rails	4
Output	+3.3V@24A, +5V@30A, +12V1@20A, +12V2@20A, +12V3@20A, +12V4@20A, -12V@0.5A, +5VSB@3A
MTBF	100k hours at 25°C, max. load, nominal in.

ATX

FEATURES

SPECIFICATIONS



RX950-D-B

Connectors:
 1 x 20+4Pin Main Connector
 1 x 4Pin ATX12V Connector
 1 x 8Pin EPS12V Connector
 2 x 8Pin PCI-Express Connector
 2 x 6Pin PCI-Express Connector
 6 x 4Pin Peripheral Connector
 6 x 5Pin SATA Connector
 2 x 4Pin Floppy Connector
 2 x PCI-E 8pin to 6pin Adapter
 Approvals: TUV, FCC, UL, CE, ROHS

Model	RX950-D-B
Type	ATX12V v2.2 & EPS12V v2.91
Max. Power	950W
Input Voltage	100 - 240 V
Input Current	15A/ 7.5A
Main Connector	20+4Pin
+12V Rails	4
MTBF	100k hours at 25°C, max., nominal input



RX630-S-B

Over Temperature/Current/Voltage/Power Protection
 Connectors:
 1x 20+4-Pin Main Connector
 1x 4+4-Pin ATX12V/EPS12V Connector
 1x 6-Pin PCI-E Connector
 1x 6+2-pin PCI-E Connector
 6x 4-Pin Peripheral Connector
 4x 5-Pin SATA Connector
 1x 4-Pin Floppy Connector
 Approvals: TUV, FCC, UL, CE, ROHS

Model	RX630-S-B
Type	ATX12V v2.2 & EPS12V v2.91
Max. Power	630W
Input Voltage	90 - 264 V
Input Current	10A/ 5A
Main Connector	20+4Pin
+12V Rails	Four +12V Rails
Output	+3.3V@24A, +5V@24A, +12V1@20A, +12V2@20A, +12V3@20A, +12V4@20A, -12V@0.5A, +5VSB@2.5A
MTBF	100k hours at 25°C, max. load, nominal in.



RD600N-2SB-SL-BK

Over temperature, over current, and over voltage protection circuits
 Connectors:
 1 x Main connector (20+4Pin)
 1 x 12V (P4)
 1 x 12V (8Pin)
 4 x peripheral Quick release connectors
 4 x SATA
 2 x Floppy
 2 x PCI-E
 Approvals: UL, FCC

Model	RD600N-2SB-SL-BK
Type	ATX12V / EPS12V
Max. Power	600W
Input Voltage	90 - 264 V
Input Current	10A @ 115V, 6A @ 230V
Main Connector	20+4Pin
+12V Rails	2
Output	+3.3V@24A, +5V@30A, +12V1@22A, +12V2@22A, -12V@0.5A, +5VSB@2.5A
MTBF	>100,000 Hours



RD550N-2SB-SL-BK

Over temperature, over current, and over voltage protection circuits
 Connectors:
 1 x Main connector (20+4Pin)
 1 x 12V (P4)
 1 x 12V (8Pin)
 4 x peripheral Quick release connectors
 4 x SATA
 2 x Floppy
 2 x PCI-E
 Approvals: CSA, UL, TUV

Model	RD550N-2SB-SL-BK
Type	ATX12V / EPS12V
Max. Power	550W
Input Voltage	90 - 264 V
Input Current	10A @ 115V, 6A @ 230V
Main Connector	20+4Pin
+12V Rails	2
Output	+3.3V@24A, +5V@30A, +12V1@22A, +12V2@22A, -12V@0.5A, +5VSB@2.5A
MTBF	>100,000 Hours



RG430-2

Over Temperature/Current/Voltage/Power Protection, Under Voltage Protection
 Connectors:
 1 x 20+4Pin Main Connector
 1 x 4+4Pin ATX12V/EPS12V Connector
 1 x 6Pin PCI-E Connector
 6 x 4Pin Peripheral Connector
 4 x 5Pin SATA Connector
 1 x 4Pin Floppy Connector
 Approvals: TUV, FCC, UL, CE, ROHS

Model	RG430-2
Type	ATX12V v2.3 & EPS12V v2.91
Max. Power	430W
Input Voltage	100 - 240 V
Input Current	10A @ 115V, 5A @ 230V
Main Connector	20+4Pin
+12V Rails	4
Output	+3.3V@24A, +5V@24A, +12V1@20A, +12V2@20A, +12V3@20A, +12V4@20A, -12V@0.5A, +5VSB@2.5A
MTBF	>100,000 Hours

ATX

FEATURES

SPECIFICATIONS



RG530-2

Over Temperature/Current/Voltage/Power Protection

Connectors:

- 1 x 20+4Pin Main Connector
- 1 x 4+4Pin ATX12V/EPS12V Connector
- 1 x 6Pin PCI-E Connector
- 1 x 6+2Pin PCI-E Connector
- 6 x 4Pin Peripheral Connector
- 4 x 5Pin SATA Connector
- 1 x 4Pin Floppy Connector

Approvals: TUV, FCC, UL, CE, ROHS

Model	RG530-2
Type	ATX12V v2.3 & EPS12V v2.91
Max. Power	530W
Input Voltage	100 - 240 V
Input Current	10A @ 115V, 5A @ 230V
Main Connector	20+4Pin
+12V Rails	4
Output	+3.3V@24A, +5V@24A, +12V1@20A, +12V2@20A, +12V3@20A, +12V4@20A, -12V@0.5A, +5VSB@2.5A
MTBF	>100,000 Hours



RG630-2

Over Temperature/Current/Voltage/Power Protection.

Connectors:

- 1 x 20+4Pin Main Connector
- 1 x 4+4Pin ATX12V/EPS12V Connector
- 1 x 6Pin PCI-E Connector
- 1 x 6+2Pin PCI-E Connector
- 6 x 4Pin Peripheral Connector
- 4 x 5Pin SATA Connector
- 1 x 4Pin Floppy Connector

Approvals:

UL, FCC, CE, CB, ROHS

Model	RG630-2
Type	ATX12V v2.3
Max. Power	630W
Input Voltage	100 - 240 V
Input Current	10A @ 115V, 5A @ 230V
Main Connector	20+4Pin
+12V Rails	4
Output	+3.3V@24A, +5V@24A, +12V1@20A, +12V2@20A, +12V3@20A, +12V4@20A, -12V@0.5A, +5VSB@2.5A
MTBF	>100,000 Hours

/ Power Supply / SFX



RV200

Over Temperature/Current/Voltage/Power Protection.

Connectors:

- 1 x 20+4Pin Main Connector
- 1 x 4+4Pin ATX12V/EPS12V Connector
- 1 x 6Pin PCI-E Connector
- 1 x 6+2Pin PCI-E Connector
- 6 x 4Pin Peripheral Connector
- 4 x 5Pin SATA Connector
- 1 x 4Pin Floppy Connector

Approvals:

UL, FCC, CE, CB, ROHS

Model	RV200
Type	SFX
Max. Power	200W
Input Voltage	115/ 230 V
Input Current	5A/3A
Main Connector	20Pin
+12V Rails	Single
Output	+3.3V@17A, +5V@12A, -5V@0.3A, +12V@13A, -12V@0.3A, +5VSB@2A
MTBF	>50,000 Hours

Input Device



Keyboard

FEATURES

SPECIFICATIONS



RK-100

Standard compact size Keyboard
Lasering print keycaps
Language: Universal Language
Membrane type

Model	RK-100
Keyboard Interface	USB
Design Style	Standard
Palm Rest	Detachable
Normal Keys	107
Keyboard Color	Black
Mouse Included	No
Operating System Supported	Windows 98/ ME/ 2000/ XP



RK-101

Standard compact size Keyboard
Lasering print keycaps
Language: Universal Language
Membrane type

Model	RK-101
Keyboard Interface	PS/2
Design Style	Standard
Palm Rest	Detachable
Normal Keys	107
Keyboard Color	Black
Mouse Included	No
Operating System Supported	Windows 98/ ME/ 2000/ XP



RK-7310

Ultra Responsive to the user's touch; effectively reducing typing stress. Patented precision Scissor-Key structure; slim and responsive. Full-size Keyboard provides comfort, flexibility, and durability. Slim, stylish and ergo curve design to match Web PCs/LCD PCs. 7 hot keys for enhanced multimedia experience.

Model	RK-7310
Keyboard Interface	USB
Design Style	Super Slim
Palm Rest	N/A
Normal Keys	104
Function Keys	7
Keyboard Color	Black
Mouse Included	No
Operating System Supported	Windows 98SE/ ME/ NT 4.0/ 2000/ XP/ Vista



RK-7300

Ultra Responsive to the user's touch; effectively reducing typing stress. Skidproof rubber rim on both sides. Full-size Keyboard provides comfort, flexibility, and durability. Unique Curved Design that is ideally inclined for typing comfort. 7 built-in hot keys for enhanced multimedia experience. Plug-and-play.

Model	RK-7300
Keyboard Interface	USB
Design Style	Super Slim
Palm Rest	N/A
Normal Keys	105
Function Keys	7
Keyboard Color	Black
Mouse Included	No
Operating System Supported	Windows 98SE/ ME/ NT 4.0/ 2000/ XP/ Vista



RK-577

New and improved WKC key structure enhances typing comfort and precision operation
Quick and positive response and super quiet design.
Easy data entry on the standard-sized 19mm key pitch
Standard keystroke of 3.0mm
Modem-simplicity design philosophy
Standard keypad plus two extra USB ports for accessories like mice, keyboards, presenters and webcams.
Plug and Play

Model	RK-577
Keyboard Interface	USB 2.0
Design Style	Slim Mini
Normal Keys	19
Keyboard Color	Black
Mouse Included	No
Operating System Supported	Windows 98/ ME/ 2000/ XP/ Vista

Input Device

Keyboard

FEATURES



SPECIFICATIONS



RKM-800RF

Wireless connection with advanced 2.4 GHz cordless technology and an operating distance of up to 15M.
Slim profile saves valuable workspace.
Sturdy metal back plate provides added strength.
Sleek design compliments today's PCs.
Dongle stored design in the keyboard body.
Precision 800dpi optical performance tracks your movements accurately.

Model	RKM-800RF
Keyboard Interface	USB
Design Style	Slim
Normal Keys	104
Keyboard Color	Black
Mouse Included	Yes
Type	2.4 GHz Cordless
Mouse Included	Yes
Mouse Specs.	USB, Optical, 3 Buttons, 1x Wheel
Operating System Supported	Windows ME/2000/XP/Vista

/ Input Device / Mouse



RM-8500

Works at full 360° up to 10 meters better range and less interference with 2.4GHz RF technology.
Multi-channel design supports 8,388,608IDs for improved performance and an operating distance of up to 10M.
800 / 1600 DPI Switchable Laser Resolutions
On/off switch to maximizes battery life. Super small size for nano dongle receiver. Two user settable sensor sensitivity settings - 800 and 1,600 DPI resolutions Laser technology provides better tracking power than LED optical mice
Unique and ergonomic shape for maximum comfort and also has easy to hold rubber coated side grips.

Model	RM-8500
Wireless Type	Wireless
Interface	USB
Hand Orientation	Both Hands
Tracking Method	Laser
Buttons	5
Scrolling Capability	1 x Wheel
Color	Black
Maximum dpi	Laser (800/1600 DPI)
Operating System Supported	Windows 98/Me/2000/XP, Mac



RM-2210

Classic Mouse with the modern optical technology
The simple and clean design comes with the advanced optical technology.

Plug and Play
Get it out of the box and plug into the computer.
The RM-2210 is ready to use. There is no software required.

Model	RM-2210
Wireless Type	Wired
Interface	USB
Hand Orientation	Both Hands
Tracking Method	Optical
Buttons	3
Scrolling Capability	1 x Wheel
Color	Black
Maximum dpi	800 dpi
Operating System Supported	Windows 98/Me/2000/XP, Mac



RM-2210P

Classic Mouse with the modern optical technology
The simple and clean design comes with the advanced optical technology.

Plug and Play
Get it out of the box and plug into the computer.
The RM-2210P is ready to use. There is no software required.

Model	RM-2210P
Wireless Type	Wired
Interface	PS/2
Hand Orientation	Both Hands
Tracking Method	Optical
Buttons	3
Scrolling Capability	1 x Wheel
Color	Black
Operating System Supported	Windows 98/Me/2000/XP, Mac



RM-C2P

Classic Mouse with the modern optical technology
The simple and clean design comes with the advanced optical technology.

Plug and Play
Get it out of the box and plug into the computer.
The RM-C2P is ready to use. There is no software required.

Model	RM-C2P
Hand Orientation	Both Hands
Interface	PS/2
Tracking Method	Optical
Buttons	3
Scrolling Capability	1 x Wheel
Color	Black
Maximum dpi	800 dpi
Operating System Supported	Windows 95/98/2000/ME/XP/VISTA, and NT

Input Device



Mouse

FEATURES

SPECIFICATIONS



RM-C2U

Sensor sensitivity switching to 1,600 and 800 dpi laser technology ultra-precise laser tracking on most polished surfaces.
Ultra precision and smooth control.
ST Micro Laser Sensor
9600 fps Image Processing
1.3m Cable Length
Unique shape for comfortable operation
Page Forward/Backward function for fast control of Internet web pages.
Plug-n-Play and Hot Pluggable.

Model	RM-C2U
Hand Orientation	Both Hands
Interface	USB
Tracking Method	Optical
Buttons	3
Scrolling Capability	1 x Wheel
Color	Black
Maximum dpi	800 dpi
Operating System Supported	Windows 98SE / ME/ 2000/ XP/ Vista/ XP Media Center Edition 2004



RM-1600L

Sensor sensitivity switching to 1,600 and 800 dpi laser technology ultra-precise laser tracking on most polished surfaces. Ultra precision and smooth control.
ST Micro Laser Sensor
9600 fps Image Processing
1.3m Cable Length
Unique shape for comfortable operation
Page Forward/Backward function for fast control of Internet web pages. Plug-n-Play and Hot Pluggable.
Certifications: FCC, CE, RoHS
Dimension: 4.72" (L) x 2.95" (W) x 1.73" (H)

Model	RM-1600L
Wireless Type	Wired
Hand Orientation	Right
Interface	USB
Tracking Method	Laser
Buttons	5
Scrolling Capability	1 x Wheel
Color	Black
Maximum dpi	1600 dpi
Operating System Supported	Windows 98SE / ME/ 2000/ XP/ Vista/ XP



RM-6500

Hidden USB receiver
Power saving
Professional for notebook use
Light & small for easy portable

Model	RM-6500
Wireless Type	RF Wireless
Hand Orientation	Both Hands
Interface	USB
Tracking Method	Optical
Buttons	3
Scrolling Capability	1 x Wheel
Color	Black/Grey
Maximum dpi	800 dpi

/ Input Device / KVM SWITCHES



RKV-2P

2-port Slim Desktop PS/2 KVM switch with Audio&Mic
Audio and Microphone switching for uninterrupted multimedia experience across multi-platforms
Simultaneous/independent PC and Audio/Mic Switching (User-programmable)
Hot-plugging PCs for maintenance without powering down the KVM Switch or PCs

Model	RKV-2P
Type	D-Sub
PC Connectors	2 x HDB 15-pin female (integrated with PS/2 interface) 2 x USB Type Mini B (audio&mic)
Console Connectors	1 x PS/2 Keyboard 6-pin Mini Din female 1 x PS/2 Mouse 6 pin Mini Din female 1x HDB 15-pin female 1 x 3.5mm audio in/out jack x 3.5mm mic in/out jack

For complete specs go to: www.rosewill.com



RKV-2U

2-port Slim Palmtop KVM Switch with Audio&Mic and 2 x detachable USB KVM & 2 x Audio/Mic Cables
USB console support for USB keyboard and mouse
Audio and Microphone switching for uninterrupted multimedia experience across multi-platforms.
USB 1.1 Specification compliant

Model	RKV-2U
Type	D-Sub
PC Connectors	2 x USB Type A 2 x HDB 15-pin male 2 x audio/mic connector [USB Mini B]
Console Connectors	2 x USB Type A (Keyboard & Mouse) 1x HDB 15-pin female 1 x 3.5mm audio jack 1 x 3.5mm mic jack

Computer Connect. 2 Ports

For complete specs go to: www.rosewill.com

Input Device

Switches



FEATURES

SPECIFICATIONS



RKV-2U

One console (monitor, USB keyboard and USB mouse) controls 2 computers
Remote switch for convenient switching
Multiplatform support: compatible with all operation platforms PC (Windows, linux and most others), Mac and Sun.
Compact design, built in all-in-one cables

Model	RKV-2UC
Type	D-Sub
PC Connectors	USB Keyboard: 2 × Type-A (M) (Black) USB Mouse: 2 × Type-A (M) (Black) VGA: 2 × HDB-15 (M) (Blue)
Console Connectors	Keyboard: 1 × Type-A (F) (Iron) Mouse: 1 × Type-A (F) (Iron) VGA: 1 × HDB-15 (F) (Blue)
Computer Connect.	2 Ports

For complete specs go to: www.rosewill.com



RKV-4UC

One console (monitor, USB keyboard and USB mouse) controls 4 computers
Remote switch for convenient switching
Multiplatform support: compatible with all operation platforms PC (Windows, linux and most others), Mac and Sun.
Compact design, built in all-in-one cables

Model	RKV-4UC
PC Connectors	USB Keyboard: 4 × Type-A (M) (Black) USB Mouse: 4 × Type-A (M) (Black) VGA: 4 × HDB-15 (M) (Blue) Mic: 4 × Stereo Jack (M) (Pink) Spk: 4 × Stereo Jack (M) (Green)
Console Connectors	Keyboard: 1 × Type-A (F) (Iron) Mouse: 1 × Type-A (F) (Iron) VGA: 1 × HDB-15 (F) (Blue) Mic: 1 × Stereo Jack (F) (Pink)

For complete specs go to: www.rosewill.com

/ Input Device / Webcam



RCM-3201V

UVC webcam: Plug and Play
Premium and unique design. Build in microphone
Multi-Swivel design: with Ultra-wide Angle
360 degree rotary for any horizontal directions
90 degree frontward and backward directions
Flexible "Snake Tube" stand: for notebook/LCD monitor/Desktop
Option: the extra CD driver for Video & Frame effects
Face tracking: keep your face in the center of the video frame. Still image: up to 2560 x 2048 pixels (5M pixels)
Special video effects. Special frame effects

Model	RCM-3201V
Interface	USB 2.0
Image Sensor	CMOS
Max. Image Resol.	Still image capture 5M pixels (Software enhanced)
Effective Pixels	True 1.3 MP
Video Capture Resol.	1.3 MP
Frame Rate	Up to 30 fps @ 640 x 480
Operating Systems Supported	Windows XP SP2/ Vista above MAC 10.4.8 above

/ Input Device / Add-on Card



RC-100

Low-Profile
Complies with OHCI 1.0, USB 1.1
Complies with EHCI
PCI Local Bus 2.2 32 bit, 33MHz, 3.3V specifications
Supports up to 127 devices
Supports devices hot swap and wake - up
Supports all USB compliant peripherals
Internal connections for connection to front bay use

Model	RC-100
Type	PCI to USB Card
External USB Ports	2x USB Ports
Internal USB Ports	On board connectors for connection to USB front bay use
Standard	USB 2.0
Data Transfer Rate	480/12/1.5 Mbps
Operating Systems Supported	Win98/98se/ME/2K/XP/Vista 32/64bit
Specifications	Chipset: VIA VT6212L



RC-101

Complies with OHCI 1.0, USB 2.0
Complies with EHCI
PCI Local Bus 2.2 specifications
Supports up to 127 devices
Supports devices hot swap and wake - up
Supports all USB compliant peripherals

Model	RC-101
Type	PCI to USB Card
External USB Ports	4x USB Ports
Internal USB Ports	1x USB Port
Standard	USB 2.0
Data Transfer Rate	480/12/1.5 Mbps
Operating Systems Supported	Windows 98/ 98SE/ME/2000/2003/XP/ Vista 32/64bit
Specifications	Chipset: NEC 720101

Add-on Card

FEATURES

SPECIFICATIONS



RC-300

Supports up to 16550 Fast Uart serial port
Easy Plug and Play installation
Automatically selects IRQ & IO address
Supports IRQ sharing
Built in 16C550 compatible UART with 16byte transmit-receive FIFO
Serial transmission rate up to 1MB/Sec.
Multi – card capability – allow for upgrade with additional serial or parallel cards
Low profile version available

Model	RC-300
Type	PCI to Serial Port Card
External Ports	1 x 9 pins serial connectors
Data Transfer Rate	1 Mbytes/sec
Operating Systems Supported	Windows 98se/ME/2K/XP/Vista 32/64bit/DOS



RC-301

Supports up to 2x 16550 Fast Uart serial port
Easy Plug and Play installation
Automatically selects IRQ & IO address
Supports IRQ sharing
Built in 16C550 compatible UART with 16byte transmit-receive FIFO
Multi – card capability – allow for upgrade with additional serial or parallel cards
For 5V PCI slot only

Model	RC-301
Type	PCI to Serial Port Card
External Ports	2 x 9 pins serial connectors
Data Transfer Rate	1 Mbytes/sec
Operating Systems Supported	Win95/98/NT4.0/2k/XP/XP64 /DOS/Vista 32/64bit / Linux
Specifications	Chipset: MOSCHIP MCS9835CV



RC-302

Low-Profile
Support Standard Parallel Port (SPP), Enhanced Parallel Port (EPP) & Enhanced Capability Port (ECP)
16 Byte FIFO
Easy Plug and Play installation
Automatically selects IRQ & IO address
Supports IRQ sharing
Multi – card capability – allow for upgrade with additional serial or parallel cards
For 5V PCI slot only

Model	RC-302
Type	PCI to Parallel Port Card
External Ports	1 x 25 pins parallel connectors
Data Transfer Rate	up to 1.5Mb/Sec
Operating Systems Supported	Win95/98/NT4.0/2k/XP/XP64 /DOS/Vista 32/64bit / Linux
Specifications	Chipset: MOSCHIP MCS9805CV



RC-303

This PCI I/O card is a dual UART with 1284 printer interface port controller with PCI bus interface and uses an all-in-one solution from NeMos Technology, which provides superior performance and unmatched data transfer rates. The most advanced feature is it uses of a single interrupt, which is set automatically by the host system and share among all on-board I/O ports and supports printer interface as well as PS2, EPP & ECP modes.

Model	RC-303
Type	PCI to Parallel / Serial Port Card
External Ports	1 x 25 pins parallel connector 2 x 9 pins serial connectors
Data Transfer Rate	1Mbytes/s (serial port) 1.5Mbytes/s (parallel port)
Operating Systems Supported	Win95/98/NT4.0/2k/XP/XP64 /DOS/Vista 32/64bit / Linux



RC-304

Support Standard Parallel Port (SPP), Enhanced Parallel Port (EPP) & Enhanced Capability Port (ECP)
Data transfer rate support up to 1.5MB/Sec.
16 Byte FIFO
Easy Plug and Play installation
Automatically selects IRQ & IO address
Supports IRQ sharing
Multi card capability allow for upgrade with additional serial or parallel cards
For 5V PCI slot only

Model	RC-304
Type	PCI to Parallel Port Card
External Ports	2 x 25 pins parallel connector
Data Transfer Rate	up to 1.5MB/Sec.
Specifications	Chipset: MOSCHIP MCS9815CV Bus Interface: PCI bus 32 bit
Operating Systems Supported	Win95/98/NT4.0/2k/XP/XP64 /DOS/Vista 32/64bit / Linux

Add-on Card

FEATURES

SPECIFICATIONS



RC-304-E

Compliant with PCI Express Base Specification 1.0a
Supports Standard Parallel Port(SPP),
Enhanced Parallel Port(EPP) & Enhanced Capability Port(ECP)
Data transfer rate up to 1.5MB/Sec.

Model	RC-304-E
Type	PCI Express to Parallel Port
External Ports	2 x Parallel Ports
Data Transfer Rate	up to 1.5MB/Sec.
Operating Systems Supported	Windows 2000/XP/Server 2003



RC-301-E

Supports 2 x UART serial port
Build in 16C550 compatible UART with 16 byte transmit-receive FIFO
Data transfer rate up to 115200bps

Model	RC-301-E
Type	PCI Express to Serial Port Card
External Ports	2 x Serial Ports
Data Transfer Rate	up to 115200bps
Operating Systems Supported	Windows 2000/XP/Server 2003



RC-500

Compliant with PCI local bus specification 2.3
Compliant with PC card standard release 8.1 specification
Works with various types of 16 or 32-bit CardBus PC Cards
Advanced Configuration and Power Interface (ACPI)
Specification 2.0 Compliant
Bridge function between PCI bus and CardBus
Supports PC Card or CardBus with Hot Insertion and Removal
Plug and play without any driver needed under Windows system.

Model	RC-500
Type	PCI to PCMCIA Card
External Ports	2 x Serial Ports
Operating Systems Supported	Windows 2000/XP/Server 2003 / Vista 32&64bit



RC-103

Complies with OHCI 1.0, USB 2.0
Complies with EHCI
PCI Local Bus 2.2 specifications
Data transfer rate support from 1.5M, 12M, 480Mbps
Supports up to 127 devices
Supports devices hot swap and wake - up
Supports all USB compliant peripherals
Supported: Windows 98/ 98SE/ME/2000/2003 and XP

Model	RC-103
Type	PCI to USB Card
External USB Ports	4x USB Ports
Internal USB Ports	1x USB Port
Standard	USB 2.0
Data Transfer Rate	480/12/1.5 Mbps
Operating Systems Supported	Windows 2000/XP/Server 2003 / Vista 32&64bit



RC-501

Low-Profile
Compliant with IEEE 1394 OHCI Specification Revision 1.0
Compliant with IEEE 1394-1395 and compatible with 1394A
PCI Local Bus 2.2 specifications
Data transfer rate support from 100/200/400Mbps
Links up to 63 FireWire devices
Supports Plug & Play specification
No driver needed in Windows and Mac

Model	RC-501
Type	PCI to 1394 Card
External 1394 Ports	2x 1394 Ports
Internal 1394 Ports	1x 1394 Port
Standard	1394A
Data Transfer Rate	400/200/100 Mbps
Specifications	Chipset: VIA 6307 Bus Interface: PCI bus 32 bit
Operating Systems Supported	Windows 98/ 98SE/ ME/ 2000/ XP/ Vista 32&64bit

Input Device



Add-on Card

FEATURES

SPECIFICATIONS



RC-502

Low-Profile
Compliant with IEEE 1394 OHCI Specification Revision 1.0
Compliant with IEEE 1394-1395 and compatible with 1394A
PCI Local Bus 2.2 specifications
Data transfer rate support from 100/200/400Mbps
Links up to 63 FireWire devices
No driver needed in Windows and Mac
Supports Plug & Play specification
Supports cable powered mode with a power provider

Model	RC-502
Type	PCI to 1394 Card
External 1394 Ports	3x 1394 Ports
Internal 1394 Ports	1x 1394 Port
Standard	11394A
Data Transfer Rate	400/200/100 Mbps
Specifications	Chipset: NEC uPD72874 Bus Interface: PCI bus 32 bit
Operating Systems Supported	Windows 98/ 98SE/ ME/ 2000/ XP/ Vista 32&64bit



RC-503

Compliant with PCI Express Specification 1.0a
Provide four 4 external Type A USB 2.0 (480Mbps) and one internal Type A USB 2.0 (480Mbps) ports into your system
Hot-swapping feature allows you to connect/disconnect devices without first turning system off
Compliant with USB specification rev. 2.0
Supports high-speed (480Mbps), full-speed (12Mbps), and low-speed(1.5Mbps) data transfer modes for simultaneous operation of multiple USB 2.0/1.1 devices
Works with a various type of USB devices including hubs, removable drives, digital cameras, scanner, CD-RWs, DVD-ROMs, PC video cameras, printers, and more.

Model	RC-503
Type	PCI Express to USB Card
External USB Ports	4x USB Ports
Internal USB Ports	1x USB Port
Data Transfer Rate	480/12/1.5 Mbps
Chipset	NEC 720101
Operating Systems Supported	Windows 2000, XP/2003 32/64 bit, Vista 32/64 bit



RC-504

Compliant with PCI Express Base Specification 1.1
Compliant with IEEE 1394-1995, 1394a-2000 and OHCI 1.1 Standards. PCI Express 1-lane(x1) FireWire adapters works with PCI Express slots with different lane width
Installs in any available PCI Express slot and supports data transfer rates up to 400Mbps
Provide two external FireWire 400 (1394a) 6-pin ports and one internal FireWire 400 (1394a) 6-pin port – sharing with first external FireWire 400 port
Support DV camcorders, hard disk, removable drives, scanner, digital cameras and other FireWire audio/video devices

Model	RC-504
Type	PCI Express to 1394 Card
External 1394 Ports	2 x 1394a Ports
Internal 1394 Ports	1 x 1394a Port
Standard	1394A
Data Transfer Rate	400/200/100 Mbps
Operating Systems Supported	Windows 2000, XP/2003 32/64-bit, Vista 32/64-bit

/ Input Device / Headphone



RH-189

Petite ear buds hide you in the crowd, anywhere you go!
Total portability brings you a whole new aspect of on the go music. Slick and trendy design of the whole new RH-189 with titanium mylar cone and aluminum housing generates soft music and the best of all; its clarity will take your mind flying in the sky.

Model	RH-189
Frequency Response	10Hz-22KHz
Input Impedance	16 ohms \pm 15%
Sensitivity	106dB \pm 3dB
Connector	3.5mm
Ear Coupling	Canal
Cord Length	3.9 feet
Weight	0.71 oz.



RH-205

Fancy some music while exercising? How about the clip-on earphone that is designed light weighted, vogue from the out side and virtue sound effect on the in side which puts your music listening experience like floating in between clouds.

Model	RH-205
Frequency Response	10Hz-22KHz
Input Impedance	60ohms \pm 15%
Sensitivity	110dB \pm 3dB
Connector	3.5mm Gold-Plated
Ear Coupling	Supra-aural
Cord Length	4.9 feet.
Weight	1.41 oz.

Notebook Bag

FEATURES

SPECIFICATIONS



RBG-1701BP

Constructed with durable 1680D Ballistic Nylon;
Separate, padded laptop compartment fits most notebooks with 17" wide screens;
Sufficient organized storage—one large compartment for folders and books, front zippered pocket, business card holder, pen loops, key clip, side mesh water pockets, cell phone holder, MP3/CD player pocket with headphone line out jack, etc; Padded Ergonomic shoulder straps and specially designed back cushion to allow air circulation;
Separate pocket for laptop AC adapter storage;
Detachable cellular phone pocket on shoulder strap.

Model	RBG-1701BP
Case Type	Backpack
Material	1680D Nylon
Color	Black/Silver
Fit Most Screen Size	17"
Capacity	12.6" x (15.35"~16.55") x 2.1"
Dimensions	15.5" x 21" x 9" (fully expanded)
Weight	4.4 lbs.



RBG-15401BP

Lightweight design while constructed with durable 1680D nylon. Padded Ergonomic shoulder straps and specially designed back cushion to allow air circulation;
Plenty of organized storage:
-padded laptop compartment fits laptops with screen size up to 15.4";-main compartment for books, magazines or files with pen loops, card holder and two mesh pockets;
-front top pocket for your cellphone, iPod, MP3 player or CD player with a line-out porthole for your headphone;
-front bottom pocket with a key clip and two separated mesh pockets for your slim digital camera and portable external hard drive.

Model	RBG-15401BP
Case Type	Backpack
Material	1680D Nylon
Color	Black
Fit Most Screen Size	15.4"
Capacity	11.4" x 13-14.6" x 1.6"
Dimensions	18.9" x 14.6" x 8.0"
Weight	2.8 lbs.



RBG-13301MS

Fits most netbooks and portable laptops up to 13.3"
Slim and lightweight design with multiple storage pockets
Interior workstation features a business card holder, a key clip, pen loops, a line-out porthole and multiple pockets for your iPod, MP3 player, cell phone, power adapter, etc
Removable interior sleeve offers great protection and flexibility to store your netbook or small-size laptop
Detachable shoulder pad and adjustable strap length provides comfortable carrying experience

Model	RBG-13301MS
Case Type	Shoulder / Carrying Case
Material	1680D Nylon
Color	Black/Red
Fit Most Screen Size	13.3"
Capacity	12.6" x 9.65" x 1.38"
Dimensions	14.2" x 11.8" x 3.54"
Weight	1.75 lbs.



RBG-13301SV

Durable, soft and water resistant Neoprene (5 mm thickness) helps to protect your laptop
L-shape zipper provides you easy access from either top or side of the sleeve
Extra pouch enables you to better manage AC adapter or other laptop accessories

Model	RBG-13301SV
Case Type	Sleeve
Material	Neoprene
Color	Black/Red
Fit Most Screen Size	13.3"
Capacity	12.6" x 9.5" x 1.36"
Dimensions	13.4" x 10.3" x 0.78"
Weight	0.79 lbs.



RBG-14101SV

Durable, soft and water resistant Neoprene (5 mm thickness) helps to protect your laptop
L-shape zipper provides you easy access from either top or side of the sleeve
Extra pouch enables you to better manage AC adapter or other laptop accessories

Model	RBG-14101SV
Case Type	Sleeve
Material	Neoprene
Color	Black/Red
Fit Most Screen Size	14.1"
Capacity	13.4" x 10.1" x 1.47"
Dimensions	14.9" x 11.6" x 0.78"
Weight	0.9 lbs.

Notebook Accessories



Notebook Bag

FEATURES

SPECIFICATIONS



RBG-15401SV

Durable, soft and water resistant Neoprene (5 mm thickness) helps to protect your laptop
L-shape zipper provides you easy access from either top or side of the sleeve
Extra pouch enables you to better manage AC adapter or other laptop accessories

Model	RBG-15401SV
Case Type	Sleeve
Material	Neoprene
Color	Black/Red
Fit Most Screen Size	15.4"
Capacity	14.5" x 11" x 1.55"
Dimensions	15.5" x 12" x 0.78"
Weight	1.17 lbs.



RBG-17001SV

Durable, soft and water resistant Neoprene (5 mm thickness) helps to protect your laptop
L-shape zipper provides you easy access from either top or side of the sleeve
Extra pouch enables you to better manage AC adapter or other laptop accessories

Model	RBG-17001SV
Case Type	Sleeve
Material	Neoprene
Color	Black/Red
Fit Most Screen Size	17"
Capacity	16.1" x 11.8" x 1.74"
Dimensions	17.4" x 13.4" x 0.78"
Weight	1.32 lbs.

/ Notebook Accessories / Notebook Cooling



RNA-61601

Dual 60mm quiet fans for superior heat dissipation
Fan on/off switch function
Adjustable fan speed
Blue LED for power status
Lightweight and portable cooling solution
retractable design for ideal portability
Embedded with 3 USB ports
Finest Aluminum Faceplate
Built-in cable storage

Model	RNA-61601
Accessory Type	Cooler
Specifications	Outline Dimensions(close): 12.0" x 1.3" x 6.7" (305 x 32 x 170mm); Outline Dimensions(Retracted): 12.0" x 1.3" x 10.9" (305 x 32 x 278mm); Fan Dimensions: 60 x 60 x 10mm. Bearing Type: Sleeve. Speed Range: 2500±10%, Rated Voltage: +5V, Rated Current: 500MA, Power Consumption: 2.5W Air Flow: 20CFM, Noise Level: 23dBA Power by:USB Y type cable, Weight: 1.3 lbs. (0.59 kg) Cooling Pad Material: ABS+ALUMINUM



RNA-7600W

Finest Aluminum Faceplate
Dual Silent Fan, Quiet & Cool
Built-in 4-Port USB2.0 Hub
Additional power adapter to ensure sufficient power supply for external USB devices

Model	RNA-7600W
Accessory Type	Cooler
Specifications	Application: 15.4" - 17" Notebook, Outline Dimensions: 15.75" x 11.03" x 2.05" (400 x 280 x 52mm), Fan Dimensions: 2.76" x 2.76" x 0.60" (70 x 70 x 15mm (2pcs)), Bearing Type: Sleeve Bearing Speed Range: 2,300 R.P.M ± 10%, Rated Voltage: 5V Rated Current: 1.0A, Power Consumption: 5.0 Watt, Air Flow: 12.4 CFM (Each Fan), Noise Level: 20 dBA, Power by USB or by power adapter, Weight: 2.53 lbs. Cooling Pad Material: Aluminum CE Standard



RNA-3000

Fan Speed Adjustment
Built-in Cable Storage
Aluminum Faceplate
Hidden Rubber Pad
USB Power

Model	RNA-3000
Accessory Type	Cooler
Specifications	Application: 7" - 14.1" Notebooks, Outline Dimension: 11.81" x 10.31" x 0.79" (300 x 262 x 20 mm), Fan Dimension: 2.76" x 2.76" x 0.39" (70 x 70 x 10 mm), Bearing Type: Ball bearing, Speed Range: 1800 ~ 2500 rpm, Rated Voltage: 5.0V, Rated Current: 0.5A, Power Consumption: 2.5 Watt, Air Flow: 15.8CFM (each fan), Noise Level: 26dBA, Weight: 1.44 lbs. Cooling Pad Material: ABS

Notebook Cooling

FEATURES

SPECIFICATIONS



RNA-03BK

Suitable for 15.4" widescreen notebooks or below
Strong, ventilated body adds style to your Notebook
Lightweight material for easy portability
Efficiently reduces operating temperature and noise
Two new design 1200 RPM ultra-quiet fans with on/off switch
Ergonomic design provides comfortable keyboard operation
Powered directly from a USB port
Additional USB port enables device connection (i.e. mouse)
Non slip pads on the bottom ensure stable operation

Model RNA-03BK
Accessory Type Cooler
Specifications
Material: ABS
Outline dimension: 350 x 305 x 45mm
Fan dimension: 70 x 70 x 15mm
Fan speed: 1200 R.P.M
Bearing type: Sleeve Bearing
Voltage rating: DC 5V
Weight: 600g



RNA-5000

Suitable for 15.4" widescreen notebooks or below
Strong, ventilated body adds style to your Notebook
Lightweight material for easy portability
Efficiently reduces operating temperature and noise
Two new design 1200 RPM ultra-quiet fans with on/off switch
Ergonomic design provides comfortable keyboard operation
Powered directly from a USB port
Additional USB port enables device connection (i.e. mouse)
Non slip pads on the bottom ensure stable operation

Model RNA-5000
Accessory Type Cooler
Specifications
Application: 12" - 15.4" Notebook
Bearing Type: Sleeve Bearing, Speed Range: 2300rpm
Rated Voltage: 5V, Rated Current: 0.13A
Power Consumption: 0.7W, Air Flow: 16 CFM
Noise Level: 20dBA, Power by USB (Cable 38cm)
Weight: 1.29 lbs. Cooling Pad Material: ABS
Outline Dimensions: 12.60" x 11.82" x 0.99" (320 x 300 x 25mm)
Fan Dimensions: 2.76" x 2.76" x 0.60" (70 x 70 x 15mm)



RNA-6000

Ergonomic Functionality
360° Swivel Base
Aesthetic Fan Grill
Quiet Operation
USB Power Supply
Complete Hidden Mechanical Design

Model RNA-6000
Accessory Type Cooler
Specifications
Dimensions: 11.82" x 10.87" x 0.91" (300 x 276 x 23 mm)
Adjustment: 20 ~ 50 Degree, 6 Levels
Application: 11.1" ~ 15.4" Notebooks
Voltage: DC 12V, Current 0.14A
Power Consumption: 0.7W, Power Supply: USB Cable
Fan Speed: 2000 R. P. M., Noise: 21.26 dBA
Weight: 1.77 lbs. (800g)

/ Notebook Accessories / Notebook Holder



RNA-A510

Pivot upwards & downwards: 180 degrees
Swivel left & right: 180 degrees
Laptop swivel: 180 degrees
360 degrees display side-to-side rotation
Desk thickness up to 2.95" (75mm)
Horizontal moving distance: 12.4" (315mm)
Vertical moving distance: 11.22" (285mm)

Model RNA-A510
Accessory Type Holder
Specifications
Laptop platform: 14" x 11.22"
Laptop weight (max): 15.4 lbs.
Material: Metal
Color: Black
Cable management



RMS-A520

Perfect laptop holder for any vehicle - car, truck, jeep, bus
Easy to install
Can be removed quickly and folded flat for storage
Superior stability and flexibility with 4 pivots
Made of 100% recycled aluminum for light-weight and durability
Single knob for easy vertical and horizontal positioning (unique patent for versatile laptop tray)
9-way direction positioning by 4 knobs and 3 locks
Includes 3 types of hooks to fix arm under vehicle seat
Includes 2 magic stickers to mount laptop

Model RMS-A520
Accessory Type Holder
Specifications
Optional LCD Bracket meets VESA standards (75x75mm and 100x100mm)
Laptop Holder height: 621mm~921mm (24"~36");
Tray Dimension: 320mm x 230mm (12.6" x 9.1")
Weight: 3.97 lbs. (arm 2.65 lbs. + tray 1.32 lbs.)
Max. load: 33 lbs.

Notebook Stand

FEATURES

SPECIFICATIONS



RNA-A512

Pivot upwards & downwards: 180 degrees
Original upwards & downwards: 90 degrees
Laptop swivel: 180 degrees
Self-rotation: 360 degrees
Horizontal moving distance: 7.2" (183mm)
Vertical moving distance: 10.78" (274mm)

Model RNA-A512
Accessory Type Stand
Specifications
Laptop platform: 14" x 11.22"
Laptop weight (max): 33 lbs.
Material: Metal
Color: Black
Cable management

/ Notebook Accessories / Notebook Adapter



RNA-U100W

Input power: 110~240 voltage, auto-switch
Easy to change voltage by using Numeric LED indicator
Different voltage to suit most brand name notebook currently in the market. Automatic reset to the lowest voltage (+15V) after current interruption to ensure safety for your systems. One mold design on voltage changer for dust free, safety and high-tech design
Big numeric LED indicator clearly indicate voltage
Including new changeable connector's design to ensure no worries on plugging into wrong positive and negative plugs to suit most brand name notebook currently in the market

Model RNA-U100W
AC Adapter Voltage 15V/16V/18V/19V/20V/21V/24V
AC Adapter Output Power 100w
Dimension 5.26" x 2.25" x 1.23"
Weight 1.1 lbs.

/ Notebook Accessories / PCMCIA Card



RC-600

Chipset: Via 6212
4 built-in type A USB 2.0 connections
Fully backwards compatible to USB 1.1
Support 500mA power to each USB port
Supports up to 127 downstream USB devices
Supports 32-bit CardBus PC Card Type II slot
Hot Swappable – Plug-n-Play
USB 1.1 and USB 2.0 compliant
Switching power adapter (Optional): DC 5V, 2A
Polarity: Outside negative voltage(-) & Inside positive voltage(+) 3.5mm power jack

Model RC-600
Type USB PCMCIA Card
Standards USB 2.0
Data Rates 480 Mbps
USB 4 x USB 2.0
Interface 32-bit CardBus Type II
Operating Systems Supported Supported Windows 98SE, ME, 2000 and XP, Vista 32/64bit



RC-601

Chipset: Ned uPD720102
Compliant with USB 2.0 EHCI
Compliant with USB 1.1 OHCI
Supports up to 127 devices
Supports devices hot swap and wake-up
Switching power adapter(Optional): DC 5V, 1A
Polarity: Outside negative voltage(-) & Inside positive voltage(+) 3.5mm power jack

Model RC-601
Type USB PCMCIA Card
Standards USB 2.0
Data Rates 480/12/1.5 Mbps
USB 2 x USB Type A ports, 1 x DC Jack
Interface 32-bit CardBus Type II
Operating Systems Supported Windows 98SE, ME, 2000 and XP



RC-602

Chipset: Via 6306L
Supports all common camcorders, disk drives, printers and scanners with 1394a interface
Supports up to 63 devices, Supports devices hot swap
Supports maximum transfer rate at 400Mbps
MS Windows compatible including DV and SBP-2 drivers
MS Windows compatible including DV and SBP-2 drivers
Switching power adapter (Optional): DC 12V, 3A
Polarity: Outside negative voltage(-) & Inside positive voltage(+) 3.5mm power jack

Model RC-602
Type IEEE 1394 PCMCIA Card
Standards IEEE 1394
Data Rates 400/200/100 Mbps
1394 3 x IEEE 1394
Interface 32-bit CardBus Type II
Operating Systems Supported Windows 98, 98SE, ME, 2000 and XP & MAC OS 8.6

PCMCIA Card

FEATURES

SPECIFICATIONS



RC-603

Chipset: Via 6212 + Via 6307, Compliant with 1394a Open Host Controller, Compliant with Interface (OHCI) specification revision 1.1, Supports all common camcorders, disk drives, printers and scanners with 1394a interface Supports up to 63 1394a devices, Supports devices hot swap, Supports maximum transfer rate at 1394a 400Mbps MS Windows compatible including DV and SBP-2 drivers Compliant with USB 2.0 EHCI, Compliant with USB 1.1 OHCI, Supports up to 127 USB devices, Supports devices hot swap and wake-up Supports maximum transfer rate at USB 2.0 480Mbps, Switching power adapter(Optional): DC 12V

Model	RC-603
Type	USB / IEEE 1394 PCMCIA Card
Standards	USB 2.0 / IEEE 1394
USB	2 x USB 2.0
1394	2 x IEEE 1394
Interface	PCMCIA Cardbus
Operating Systems Supported	Windows 98SE, ME, 2000 and XP



RC-604

Chipset: Silicon Image Sil3512
Connect up to 2 SATA devices
Supports Serial ATA data transfer rate up to 1.5Gbps
Supports PIO and DMA modes
Hot swappable

Model	RC-604
Type	SATA PCMCIA Card
Other Ports	2 x eSATA
1394	3 x IEEE 1394
Interface	32-bit CardBus Type II
Operating Systems Supported	Windows 98SE/ ME/2000/XP & Linux



RC-605

Chipset: Silicon Image Sil3132
Serial ATA generation 2 transfer rate of 3.0Gbps
Adds two eSATA (external Serial ATA) ports
Fully compliant with ExpressCard Specification 1.0
ExpressCard/34 Form Factor Module
Adds two eSATA (external Serial ATA) ports
Supports Native Command Queuing (NCQ), Non-zero offsets NCQ, and Out-of-order data delivery NCQ
Supports Hot Plugging on Extend Serial ATA port

Model	RC-605
Type	SATAII ExpressCard
Data Rates	3 Gbps
Other Ports	2 x SATA
Interface	ExpressCard slot
Operating Systems Supported	Windows 98, 98SE, ME, 2000 and XP & MAC OS 8.6



RC-610

Chipset: Genesys GL827
Compliant with Express/34 module specification
Compliant with USB Storage Class specification
Supports various card type
Read/write directly – SD, SDHC, MMC, HS-MMC, MS, HS MS, MS PRO and MS Rom cards
Read/write through adapter – Mini SD, Micro SD, T-Flash, RS MMC, MMC Micro, MMC Mobile, MS Duo, MS PRO Duo and MS PRO Micro cards
No driver installation is required
Hot-swapping features allow you to attach/detach without powering down your system

Model	RC-610
Type	ExpressCard Reader
Operating Systems Supported	Supports Windows 2000/XP /Server 2003/Vista



RC-611

Chipset: NEC uPD720114
Fully compliant with ExpressCard Specification 1.0
ExpressCard/34 Form Factor Module
Hot-swapping feature allows to connect or disconnect devices without powering down system
Fully supports EHCI and OHCI Compliant standards
Compliant with Universal Serial Bus specification revision 2.0
Provides four external USB2.0 high speed port

Model	RC-611
Type	USB ExpressCard
Standards	USB 2.0
Data Rates	480/12/1.5 Mbps
USB	4 x USB 2.0
Operating Systems Supported	Support Windows 2000 / XP / Server 2003 / Vista

PCMCIA Card

FEATURES

SPECIFICATIONS



RC-614

Chipset: Prolific PL2305
Fully compliant with ExpressCard Specification 1.0
ExpressCard/34 Form Factor Module
No IRQ, DMA, I/O Address resources required
Hot swappable
Easy plug & play
Single Printer Port Interface

Model	RC-614
Type	Paralle Port ExpressCard
Interface	ExpressCard slot
Operating Systems Supported	Supports Windows 2000, XP/2003 32 /64 bit, Vista 32/64 bit

/ Express Card



RC-608

TI XIO2000AZHH. - Connect any CardBus card onto ExpressCard 34/54 card slot, Supports ExpressCard 34 and ExpressCard 54 form factor, Supports 1-lane 2.5Gbps PCI Express. Compliant with PCI Express Specification, revision 1.0a - Compliant with PC Card Standard 7.1
PC 98/99 compliant, Great for connecting Cardbus devices onto Notebook computers that are only equipped with ExpressCard slot, Supports Type I and Type II CardBus Cards
PC Card 32-bit Cardbus fully compliant. (Does not support 16-bit PCMCIA card.)
Hot-plug capability supported through ExpressCard connector

Model	RC-608
Type	ExpressCard to PCMCIA Card
Other Ports	CardBus slot
Interface	ExpressCard slot
Operating Systems Supported	Windows 2000, XP, 2003, Vista with no drivers necessary
System Requirements	ExpressCard-enabled system with an available ExpressCard slot Windows 2000/XP/Server 2003/Vista

/ Notebook Accessories / External CD/DVD Drive



ROD-EX001

High efficient power saving modes no power adapter required
SMART-X Smart Monitoring & Adjusting Read-speed Technology for eXtraction
SMART-BURN Smart Monitoring & Adapting Recording Technology for Burning
Buffer under run free
Support Over-Burn and Raw mode copy
Light Weight: 0.84 lbs.

Model	ROD-EX001
Type	Slim DVD Burner
Performance	DVD-ROM Access Time: 130ms CD-ROM Access Time: 110ms Cache: 2MB
WRITE Speed	DVD+R: 8X, DVD+RW: 8X, DVD-R: 8X, DVD-RW: 6X, CD-R: 24X, CD-RW: 24X DVD-RAM: 5X
Load Type	Tray
Interface	USB 2.0

/ Notebook Accessories / Travel Kit



RNA-E3009

Travel Nylon Bag--Easy to carry all parts in one pocket;
Mini retractable optical mouse--800dpi;
Retractable 3.5mm connector web phone--length: 1300mm±50mm;
4-Port USB2.0 Hub--Compact & lightweight design with data transfer speed up to 480mbps; plug & play.

Model	RNA-E3009
Accessory Type	Accessory Kit
Specifications	1. USB Retractable Mouse (3D USB optical mouse 800dpi) 2. Web Phone Kit (Retractable Plug: 3.5mmx2; length: 1300mm±50mm) 3. 4-Port USB2.0 Hub 4. Travel Nylon Bag



RNA-E3010

Rosewill RNA-E3010 aims to enhance your mobile digital life by providing you various laptop essentials as listed below in a convenient travel case. Moreover, this laptop kit is especially an ideal complement to the recent popular Notebooks.

1. Travel PU Bag--Easy to carry all parts in one pocket;
2. Mini retractable optical mouse--800dpi;
3. Retractable 3.5mm connector web phone--length: 1300mm±50mm;
4. USB2.0 Cardreader

Model	RNA-E3010
Accessory Type	Accessory Kit
Specifications	1. USB Retractable Mouse (3D USB optical mouse 800dpi) 2. Web Phone Kit (Retractable Plug: 3.5mmx2; length: 1300mm±50mm) 3. 24 in 1 USB 2.0 Cardreader 4. 4-Port USB2.0 Hub 5. USB LED light (Usb1.1; length: 370mm±10mm) 6. Travel Bag (Easy To Carry)

Travel Kits

FEATURES

SPECIFICATIONS



RNA-E3009

1. Travel Nylon Bag--Easy to carry all parts in one pocket;
2. Mini retractable optical mouse--800dpi;
3. Retractable 3.5mm connector web phone--length: 1300mm±50mm;
4. USB2.0 Cardreader

Model	RNA-E3009
Accessory Type	Accessory Kit
Specifications	<ol style="list-style-type: none"> 1. USB Retractable Mouse (3D USB optical mouse 800dpi) 2. Web Phone Kit (Retractable Plug:3.5mmx2; length: 1300mm±50mm) 3. 24 in 1 USB 2.0 Cardreader 4. Travel Nylon Bag

Monitor Accessories

/ Mounting Kits



RMS-A882

Movable:
 360 degrees display side-to-side rotation
 Tilting any directions: 30 degrees
 Horizontal wide length 27.56" (700mm)
 Vertical moving up & down height 14.96" - 19.29" (380 - 490mm)

Model	RMS-A882
Material:	Metal
Name	2 Horizontal Screens Stand
Mount Style	Table
Color	Black
TV Weight Capacity	Max. load 33 lbs.
VESA Compatible	75x75/100x100mm
Cable Management	Yes
Dimensions	Height: 35.7", Width: 14.77", Depth: 4.92"



RMS-A500T

Movable:
 Pivot upwards & downwards: 180 degrees
 Original upwards & downwards: 90 degrees
 LCD monitor swivel: 180 degrees
 Self-rotation: 360 degrees
 Horizontal moving distance: 7.2" (183mm)
 Vertical moving distance: 10.79" (274mm)

Model	RMS-A500T
Name	LCD Table Stand
Mount Style	Table
Color	Black
TV Weight Capacity	Max. load 44 lbs.
VESA Compatible	75x75/100x100mm
Cable Management	Yes
Dimensions	Height: 14.57", Width: 6.69", Depth: 14.76"
Weight	13.23 lbs.



RMS-FC888P

Movable:
 Pivot upwards & downwards: 180 degrees
 Swivel left & right: 180 degrees
 LCD monitor swivel left & right: 180 degrees
 360 degrees display side-to-side rotation
 Horizontal moving distance: 12.24" (311mm)
 Vertical moving distance: 11.22" (285mm)

Model	RMS-FC888P
Name	Swivel arm on Desktop for LCD(C-Clamp)
Material:	Metal with plastic cover
Mount Style	Table
Color	Black
TV Weight Capacity	Max. load 15.4 lbs.
VESA Compatible	75x75 / 100x100mm
Cable Management	Yes
Dimensions	Height: 23.62", Width: 5.5", Depth: 3.94"
Weight	7.72 lbs.

/ Monitor Accessories / Cleaning Kits



RCN-SC106

Integrated spray applicator with fluid reservoir handle conveniently applies the optimal amount of solution to target surface.
 Cushioned micro-fiber pad evenly distributes the pressure exerted by users when buffing surface.
 Super cleaning liquid contains no alcohol, ammonia, or cfc's
 Environmentally friendly, clear 100% natural, sterile

Model	RCN-SC106
Type	Screen, Monitor, LCD, TV cleaner
Color	green
Accessories	A hanger for easy storage
Specifications	<p>Black spray applicator with replaceable micro-fiber pad is specially designed to buff delicate Plasma/LCD screens.</p> <p>100 ml powerful cleaning solution removes dust, dirt, smudges and oily fingerprints.</p>

Cleaning Kits

FEATURES

SPECIFICATIONS



RCN-SC206

A smaller version cleaning tool more suited to smaller LCD monitors and televisions
Convenient Integrated fluid reservoir handle with spray nozzle fused
A cushioned surface micro fiber pads evenly distributes the pressure exerted by users
Super cleaning liquid contains no alcohol, ammonia, or cfc's
Environmentally friendly, clear 100% natural, sterile

Model	RCN-SC206
Type	LCD screen cleaner
Color	Green
Accessories	A hanger for easy storage

Specifications

A specially designed micro fiber pad for delicate Plasma/LCD screen. 100 ml powerful cleaning solution removes dust, dirt, smudges and oily fingerprints.



RCN-SC206RP

The replacement Pad for RCN-SC206. Super-soft LCD screen cleaner replacement pads ensure superior cleaning and protection for delicate LCD screens. These pads have a specially developed foam backing to ensure pressure is evenly dispersed along the screen surface and a micro-fiber face that is the softest available for buffing and polishing modern LCD panels with optical surface coatings.
Replace your pad regularly to avoid any risk of damage to your LCD screen caused by embedded dirt and dust particles on the cleaner surface. Replacement is quick, easy and fully explained in the refill pack instructions.

Model	RCN-SC206RP
Dimensions	7.2 cm *9.5 cm
Content	3 pcs/bag



RCN-SC106RP

The replacement Pad for RCN-SC106. Super-soft LCD screen cleaner replacement pads ensure superior cleaning and protection for delicate LCD screens. These pads have a specially developed foam backing to ensure pressure is evenly dispersed along the screen surface and a micro-fiber face that is the softest available for buffing and polishing modern LCD panels with optical surface coatings.
Replace your pad regularly to avoid any risk of damage to your LCD screen caused by embedded dirt and dust particles on the cleaner surface. Replacement is quick, easy and fully explained in the refill pack instructions.

Model	RCN-SC106RP
Dimensions	8.5 cm *14.1 cm
Content	8.5 cm *14.1 cm



RCN-SCL100

Super cleaning liquid contains no alcohol, ammonia, or CFC's.
Environmentally friendly, clear 100% natural, sterile
100 ml powerful cleaning solution removes dust, dirt, smudges and oily fingerprints.

Model	RCN-SCL100
Type	Cleaner

Wired Networking

FEATURES

SPECIFICATIONS



RNX-56AG

Agere Software base Modem Design
Windows Vista Ready!
Wake-on-ring and Caller ID support.
Designed for Microsoft Windows (WHQL)
Support Telephone Answering Machine (TAM) and Voice Mail Operations
High Performance, Low Power Consumption, with Fully Plug-&-Play Installation
Auto-detect Data, Fax, Voice Modes
OS Support: Windows 98SE/ ME/ 2000/ 2003/ XP/ Vista32&64bit.

Model	RNX-56AG
Chipset	Agere
Max Transmiss. Rate	56Kbps
Max Fax Speed	Agere
Chipset	14.4 kbps

Standards:

Software 56K Fax modem Design compression
High compression throughput due to parallel access directly to the host PC
FAX modem capabilities:



RNX-56CX

Windows Vista Ready
Designed for Microsoft Windows (WHQL)
High quality Conexant design, Support Telephone Answering Machine (TAM) and Voice Mail Operations, High Performance, Low Power Consumption, with Fully Plug-&-Play Installation, Auto-detect Data, Fax, Voice Modes
OS Support: Windows 98SE/ ME/ 2000/ XP/ Vista32&64bit
Modem Speaker onboard design, Downstream speed up to 56,000bps; upstream up to 48Kbps, Full speakerphone function, Support Fax group 3; Class 1, V.80 & H.324 Video Conferencing

Model	RNX-56CX
Interface	PCI Bus (Plug & Play)
Cable Interface	2 x RJ11 ports
Chipset	Conexant
Max DTE Rate	115.2 kbps
Max Transmiss. Rate	56Kbps
Max Fax Speed	14.4 kbps

Standards:

FAX modem capabilities:
Fax mode with send and receive rates up to 14.4Kbps



RNX-56CX

Windows Vista Ready!
Designed for Microsoft Windows (WHQL)
High quality Conexant design
Support Telephone Answering Machine (TAM) and Voice Mail Operations
High Performance, Low Power Consumption, with Fully Plug-&-Play Installation
Auto-detect Data, Fax, Voice Modes
OS Support: Windows 98SE/ ME/ 2000/ XP/ Vista32&64bit
Modem Speaker onboard design

Model	RNX-56CX
Interface	PCI Bus (Plug & Play)
Cable Interface	2 x RJ11 ports
Chipset	Conexant
Max Transmiss. Rate	56Kbps
Max Fax Speed	14.4 kbps
Max Data Rate	115.2 kbps

Standards:

FAX modem capabilities:
Fax mode with send and receive rates up to 14.4Kbps.



RC-400

Supports Full Duplex flow control (IEEE 802.3x)– Four LED indicators- Auto-Negotiation with Next page capability- Supports pair swap/polarity/skew correction- Crossover Detection & Auto-Correction- Wake-on-LAN and remote wake-up support- Microsoft® NDIS5 Checksum Offload (IP, TCP, UDP) and largesend offload support- Supports IEEE 802.1Q VLAN tagging- 8K Transmit FIFO and 64K Receive FIFO support- Supports power down/link down power saving- Truly 4 layers PCB- Metal & durable LAN connector, RTL8169S chipset with independence heatsink

Model	RC-400
Standards	IEEE802.3, IEEE802.3u, IEEE802.3z
Speed	10/ 100/ 1000Mbps
Connectors	1 x RJ45
Interface	PCI 2.2 Integrated PCI DMA engines
BUS	32-bit PCI 2.2
LEDs	4 LED indicators for 10Link/Activity(red), 100Link/Activity(yellow), 1000Link/Activity(green) and Full Duplex(blue)

RC-400 can only work in PCI 3.3V or 3.3V/5V universal motherboard, RC-400 can't work in 5V PCI only motherboard



RC-402

IEEE802.3u 100BASE-TX and IEEE802.3 10BASE-T compliant. Support for IEEE802.3x flow control
IEEE802.3u Auto-negotiation support for 10BASE-T and 100BASE-TX, ACPI and PCI power management Ver. 1.1 compliant. Supports ODI, NDIS, Windows 95/98/98SE/ ME/2000/XP/NT 4.0/Vista 32/64bit, UNIX and Linux
Support PC99 Wake On LAN
Provides two independent long FIFOs with 2K bytes each for transmission and receiving
Supports ODI, NDIS, WinXP 32/64bit/98SE/ME/2K UNIX and Linux

Model	RC-402
Standards	IEEE802.3, IEEE802.3u, IEEE802.3x
Speed	10/ 100Mbps
Connectors	1 x RJ45
Interface	PCI
Wake on LAN	Yes
Chipset	RTL8100C

Wired Networking

FEATURES

SPECIFICATIONS



RC-401-EX

Compliant with PCI Express Specification, revision 1.0a
1-lane 2.5Gbps PCI Express host interface
Low Profile PCI Form Factor. RJ-45 Port offer high speed transmission over CAT 5 UTP cable. Auto-Negotiation with Next page capability, Supports pair swap/polarity/skew correction. Crossover Detection & Auto-Correction
Microsoft NDIS5 Checksum Offload (IP, TCP, UDP) and largesend offload support. Supports Full Duplex flow control (IEEE 802.3x). Supports IEEE 802.1Q VLAN tagging 8K Transmit FIFO and 64K Receive FIFO support Fully RoHS compliant. Supports W/Vista & Mac OS X v10.4

Model	RC-401-EX
Interface	PCI-Express
Speed	10/ 100/ 1000Mbps
Connectors	1 x RJ45
LEDs	LEDs indicate for various network activities
Drivers	Windows 98/2000/Server 2003/XP/ Vista 32/64bit
Standards	IEEE 802.3 (10Base-T Ethernet) IEEE 802.3u (100Base-TX Fast Ethernet) IEEE 802.3z (1000Base-T Gigabit Ether.)



RC-400-LX

Supports for IEEE802.3x Full Duplex flow control
Supports IEEE 802.1Q Virtual LAN (VLAN) Tag
Compliant to PC97, PC98, PC99 and PC2001 standards
Support ACPI and PCI power management

OS Supports: Supports ODI, NDIS, Windows 98/98SE/ ME/2000/XP/NT 4.0, UNIX and Linux

Model	RC-400-LX
Interface	PCI V2.2, 32/64-bit, 33/66MHz
Speed	10/ 100/ 1000Mbps
Connectors	1 x RJ45
Wake On LAN	Yes



RC-411

Designed to meet PCI Express Base Specification Revision 1.0a
Single-lane (or x1) PCI Express throughput supports rates of 2.5Gbps
Compliant with 10/100/1000 IEEE 802.3 specification
Automatic MDI/MDIX crossover at all speed
Support Wake On Lan(WOL) power management (optional)
Feature full duplex mode that doubles the network connection speed
Support Windows 2000, XP, Server 2003 and Vista operating system

Model	RC-411
Interface	PCI-Express
Speed	10/ 100/ 1000Mbps
Connectors	1 x RJ45
LEDs	LEDs indicate the status of data transmission
Wake On LAN	Yes



RC-401-Dual-EX

The adapter provides two RJ-45 Ports fully compliant with IEEE 802.3 (10Base-T Ethernet), IEEE 802.3u (100Base-TX Fast Ethernet), IEEE 802.3z (1000Base-T Gigabit Ethernet) networking of transfer rate up to 1000 Mbps. RSS Hash Calculation and QoS (IEEE 802.1p) support for client and server application. Fully compliant with IEEE 802.3 (10Base-T Ethernet), IEEE 802.3u (100Base-TX Fast Ethernet), IEEE 802.3z (1000Base-T Gigabit Ethernet) Compliant with PCI Express Specification, revision 1.0a 4-lane 10Gbps PCI Express host interface. Low Profile PCI Form Factor

Model	RC-401-Dual-EX
Standards	IEEE802.3, IEEE802.3u, IEEE802.3z
Speed	10/ 100/ 1000Mbps
Connectors	2 x RJ45
Interface	PCI-e x4
On-board Memory	Configurable 96 KB deep buffer for ea./link
Wake On LAN	Yes
LEDs	2 LEDs per port to indicate for various network activities (1000 and LNK/ACT)



RC-409X

RC-409X is Rosewill first Green Power Saving Giga switch. It is designed by innovative eco-friendly technology which can reduces power consumption and heat. Extended your product life and reduces your electric bill every month. Full duplex operation up to 2000Mbps Combined switching capacity of up to 10Gbps, non-blocking switching architecture Per-Port color LEDs Excellent switching architecture by combining dynamic memory allocation with store-and-forward switching Allowing two or more units to be cascaded together 802.3x Flow Control, 802.1P priority queuing

Model	RC-409X
Standards	IEEE802.3, IEEE802.3u, IEEE802.3ab
Jumbo Frames	12KB
Ports	5 x RJ45
Speed	10/100/1000Mbps
MAC Address Table	1K
Buffer Memory	832Kbits
Switching Method	Store and Forward
Protocols	CSMA/CD
LEDs	Power, Link/Act
Dimensions	7.8" x 4.5" x 1.2"

Wired Networking

FEATURES

SPECIFICATIONS



RNX-56USB

Conexant Hardware base Modem Design
Windows Vista Ready!
This modem supports V.92/V.90 receiving data up to 56Kbps with V.44 data compression, V.17 Fax to 14.4Kbps, Telephone Answering Machine (TAM) and full speed (12 MHz) USB interface operation.
USB interface; Conexant solution
Windows Plug-n-Play
V.92 protocol support and quick connect
Downstream speed up to 56Kbps
Upstream speed up to 48Kbps

Model	RNX-56USB
Interface	USB
Cable Interface	RJ11 port
Chipset	Conexant CX93010 + CX20548 (SmartDAA)
Max Transmiss. Rate	56Kbps
Max Fax Speed	14.4 kbps
Standards:	
Fax modem capabilities	
Fax mode with send and receive rates up to 14.4Kbps	



RC-405

Full/Half-Duplex capability on every TX port
Supports TP interface Auto MDIX function for auto TX/RX swap
Automatic Source MAC Address Learning and Aging
Broadcast Storming Filter function
IEEE802.3x flow control for Full-duplex
Back Pressure function for Half-duplex operation
Runt and CRC Filtering eliminates erroneous packets to optimize the network bandwidth
Support to handle up to 1522 bytes packet
LED indicators for simple diagnostics and management

Model	RC-405
Standards	IEEE802.3, IEEE802.3u, IEEE802.3x
Speed	10/100Mbps
MAC Address Table	1K
Switching Method	Store and Forward
Cabling	Category 3/4/5 UTP/STP
LEDs	System – Power LED Individual port – link/activity LEDs
Power	Input Power Requirement: 120VAC, 60Hz
Dimensions	5.2" x 2.8" x 1.1"



RC-406

Non-blocking Performance Improves Access to Network Resources. All Ports Support Auto-negotiation and Auto-MDI/ MDI-X to Facilitate Installation and Troubleshooting
Full Wire Speed Store-and-Forward Technology Instantly Eliminates Bad Packets. Automatic Source Address Learning and Aging. Built-in High Efficiency SRAM for Packet Buffer. Support IEEE 802.3x Flow-control for Full-duplex and Back-pressure Flow-Control for Half-duplex
Delicate Plastic Palm Size with an External Power Adapter
Easy-to-Understand LEDs Display Real-time Traffic Status to Monitor and Diagnose the Network

Model	RC-406
Standards	IEEE802.3, IEEE802.3u, IEEE802.3x
Ports	8 x RJ45
MAC Address Table	1K
Switching Method	Store and Forward
LEDs	System – Power LED Individual port – link/activity LEDs
Dimensions	5.2" x 2.8" x 1.1"
Power	Input Power Requirement: 120VAC, 60Hz
Cabling	100Base-TX – UTP/STP category 5 cable 10Base-T – UTP/STP category 3 or 5 cab.



RC-410

8K MAC Address Table
8/16-bit CPU Interface, and 4-wire Serial CPU Interface
On-chip 8051 CPU
Jumbo Frame Support
Full Duplex Flow Control (IEEE Std 802.3x) and Half Duplex Back pressure
Multicast and Broadcast Storm Control
Flexible Link Aggregation Compliant to IEEE 802.3ad

Model	RC-410
Standards	IEEE802.3, IEEE802.3u, IEEE802.3ab, IEEE802.3x
Ports	8 x RJ45
MAC Address Table	8K
Speed	Speed
Buffer Memory	144 KB On-chip Frame Buffer
VLAN Support	No



RC-412

Bridging capability for 100Mbps and 10Mbps segments
Provides Store-and-Forward Switching Architecture
Supports Auto MDI/MDI-X. Supports IEEE802.3x Flow-Control Full-Duplex operation
Supports Back-Pressure Flow-Control Half-Duplex operation. The 16-Port NWay Switch is designed to for the needs of small enterprise and home networks. Its easy installation can boost network performance just in a couple of minutes. With its Auto-Negotiation capability, all ports can be configured to its optimum speed of 10/20Mbps or 100/200Mbps automatically.

Model	RC-412
Standards	IEEE802.3, IEEE802.3u, IEEE 802.3x
Ports	16 x RJ45
Speed	10/100Mbps
MAC Address Table	1K
LEDs	POWER, LINK/ACT

Wired Networking

FEATURES

SPECIFICATIONS



RC-410X

RC-410X is one of Rosewill Green Power Saving Giga switch series. It is designed by innovative eco-friendly technology which can reduce power consumption and heat. Extended your product life and reduces your electric bill every month. Full duplex operation up to 2000Mbps. Combined switching capacity of up to 10Gbps, non-blocking switching architecture. Excellent switching architecture by combining dynamic memory allocation with store-and-forward switching. Allowing two or more units to be cascaded together. Fan-less design. Auto MDI/MDI-X crossover. Auto-negotiation.

Model	RC-410X
Standards	IEEE802.3, IEEE802.3u, IEEE802.3ab
Jumbo Frames	Yes
Ports	8 x RJ45
MAC Address Table	8K
Buffer Memory	832 Kbits SRAM buffer memory
Switching Method	Store and Forward
LEDs	Power LAN / Activity/Link
Power	AC-DC 7.5V / 1A External
Dimensions	7.75" x 4.48" x 1.2"

/ Networking / Wireless Networking



RNX-G300EX

FCC ID: VYTLP-7185
Detachable 2 dBi antenna with 100cm long length cable provides convenience to locate the antenna.
High security protection: 64/128bit WEP WPA WPA2 802.1x, 802.11i, AES, TKIP.
System Requirements:
W98SE/Me/2000/XP/ Vista 32 and 64 bit MAC 10.3/ 10.4/ 10.52

Model	RNX-G300EX
Standards	IEEE 802.11b/g
Data Rates	Up to 54Mbps
Security	64/128bit WEP WPA WPA2 802.1x, 802.11i, AES, TKIP
WPA/WPA2	WPA2
Interface	32bit PCI2.2
Antenna	External detachable dipole antenna (Connector: RP-SMA connector, Cable Length: 100 cm)



RNX-G300LX

FCC ID: VYTLP-7185
Detachable 2 dBi antenna.
High security protection: 64/128bit WEP WPA WPA2 802.1x, 802.11i, AES, TKIP.
High quality Ralink wireless b/g solution
Media Access Protocol CSMA/CA (Collision Avoidance) with ACK
Operating Temperature 0~55° ambient temperature
Storage Temperature -20~70° ambient temperature
Operating & Storage Humidity 90% maximum

Model	RNX-G300LX
Standards	IEEE 802.11b/g
Data Rates	Up to 54Mbps
Security	64/128bit WEP WPA WPA2 802.1x, 802.11i, AES, TKIP
WPA/WPA2	WPA2
Interface	32bit PCI2.2
Channels	11 CH (US, Canada),
Antenna	External 2 dBi detachable dipole antenna
Transmitted Power	11g: 14dBm (Max.), 11b: 18dBm (Max.)
Modulation	PBCC, CCK, DQPSK, DBPSK, OFDM



RNX-N1

The easiest way to upgrade your system into wireless N network. Connect your PC/NB to a wireless network in minutes using high speed USB2.0 interface.
12x speed and 4x coverage over wireless G.
802.11b/g/n 2.0 provide further coverage, less dead spot and higher throughput. MIMO technology throughput up to 300 Mbps for Ralink 2T2R solution. Supports MIMO technology with 2 Built-in Internal Printed Antennas.
Easy setup with Wi-Fi Protected Setup (WPS).
Security support WPA/WPA2 (AES, 64,128-WEP with shared-key authentication).

Model	RNX-N1
Standards	IEEE 802.3/3u, IEEE 802.11b/g, IEEE802.11n Draft 2
Data Rates	Up to 300Mbps
Interface	USB 2.0
Frequency Band	RNX-N1
LEDs	Power, Link
Antenna	Configuration: 2T2R Mode
Security	WPA/WPA2 (AES, 64,128-WEP with shared-key authentication) Cisco CCS V1.0, V2.0 and V3.0 compliant



RNX-N1MAC

The easiest way to upgrade your system into wireless N network. Connect your PC/NB to a wireless network in minutes by high speed USB2.0 interface.
12x the speed and 4x the coverage over wireless G.
802.11b/g/n 2.0 provide further coverage, less dead spot and higher throughput. MIMO technology throughput up to 300 Mbps for Ralink 2T2R solution. Supports MIMO technology with 2 Built-in Internal Printed Antennas.
Easy setup with Wi-Fi Protected Setup (WPS).
Security support WPA/WPA2 (AES, 64,128-WEP with shared-key authentication).

Model	RNX-N1MAC
Standards	IEEE 802.3/3u, IEEE 802.11b/g, IEEE802.11n Draft 2
Data Rates	Up to 300Mbps
Interface	USB 2.0
Channels	11 (US, Canada), 13 (EU), 14 (Japan)
LEDs	Power, Link
Antenna	2 Built-in Internal Printed Antennas
Security	WPA/WPA2 (AES, 64,128-WEP with shared-key authentication) Cisco CCS V1.0, V2.0 and V3.0 compliant

Wireless Networking

FEATURES

SPECIFICATIONS



RNX-N2X

Two high gain Omni directional 2 dBi antenna for the best wireless signal. Unique design to get the best signal and speed out of your NB. The easiest way to upgrade your system into wireless N network Connect your PC/NB to a wireless network in minutes using high speed USB2.0 interface. 12x speed and 4x coverage over wireless G. 802.11b/g/n 2.0 provide further coverage, less dead spot and higher throughput. MIMO technology throughput up to 300 Mbps for Ralink 2T2R solution. Supports MIMO technology with 2 external 2 dBi SMA Antennas Easy setup with Wi-Fi Protected Setup (WPS).

Model	RNX-N2X
Standards	IEEE 802.3/3u, IEEE 802.11b/g, IEEE802.11n Draft 2
Data Rates	Up to 300Mbps
Interface	USB 2.0
Channels	11 (US, Canada), 13 (EU), 14 (Japan)
LEDs	Link
Antenna	2 external 2 dBi SMA Antennas
Security	WPA/WPA2 (AES, 64,128-WEP with shared-key authentication) Cisco CCS V1.0, V2.0 and V3.0 compliant



RNX-N4

Stream Engine Inside. Automatically detects media applications and gives them priority on the network. Stream Engine uses hardware and software to improve the quality of media for your network without any configuration. x4 built-in high performance Vitesse chipset 10/100/1000Mbps Gigabit Switch Ports (Auto-Crossover) x3 high gain Omni directional 2 dBi antenna connecting for the best wireless signal. Cool blue LED indicator shows the status of your network. Quick hardware button for WPS setup to enhance the security.

Model	RNX-N4
Standards	IEEE 802.11b/g, IEEE 802.11n Draft
Ports	1 x 10/100/1000M WAN; 4 x 10/100/1000M LAN
Interface	Ethernet Port
VPN support	IPSec, L2TP, & PPTP VPN pass-through
Antenna	3 external 2 dBi SMA Antennas
Frequency Band	2.4GHz - 2.484GHz
Data Rates	Up to 300Mbps
Modulation	OFDM: BPSK, QPSK, 16-QAM, 64-QAM DBPSK, DQPSK, CCK



RNX-N100

The easiest way to upgrade your system into wireless N network. Connect your PC/NB to a wireless network in minutes using high speed USB2.0 interface. 8x the speed and 4x the coverage over wireless G. 802.11b/g/n 2.0 provide further coverage, less dead spot and higher throughput. MIMO technology throughput up to 150 Mbps for Ralink 1T2R solution. Supports MIMO technology with Built-in 2 Internal Printed Antennas Easy setup with Wi-Fi Protected Setup (WPS). Security support WPA/WPA2 (AES, 64,128-WEP with shared-key authentication).

Model	RNX-N100
Standards	IEEE 802.11b/g, IEEE 802.11n Draft
Data Rates	Up to 150Mbps
Interface	USB 2.0
Frequency Band	2.4GHz - 2.484GHz
Channels	11 (US, Canada), 13 (ETSI), 14 (Japan)
LEDs	Power, Link
Antenna	1T2R Mode
Dimensions	3.0" x 0.9" x 0.4"



RNX-N300

The easiest way to upgrade your system into wireless N network. Connect your PC to a wireless network in minutes. 8x the speed and 4x the coverage over wireless G. 802.11b/g/n 2.0 provide further coverage, less dead spot and higher throughput. MIMO technology throughput up to 150 Mbps for Ralink 1T2R solution. Easy setup with Wi-Fi Protected Setup (WPS). Security support WPA/WPA2 (AES, 64,128-WEP with shared-key authentication). Support Cisco CCS V1.0, V2.0 and V3.0 compliant WPS.

Model	RNX-N300
Standards	IEEE 802.11b/g, IEEE 802.11n Draft
Data Rates	Up to 150Mbps
Interface	PCI
Frequency Band	2.4GHz - 2.484GHz
Channels	11 (US, Canada), 13 (ETSI), 14 (Japan)
LEDs	Link/Activity
Antenna	2dBi Dipole Antenna (2.4GHz)
Security	WPA/WPA2 (AES, 64,128-WEP with shared-key authentication) Cisco CCS V1.0, V2.0 and V3.0 compliant WPS



RNX-N4PS

12x speed and 6x coverage over wireless G. x4 built-in 10/100Mbps Fast Ethernet Switch Ports (Auto-Crossover) x3 high gain Omni directional 2 dBi antenna connecting for the best wireless signal. Green Power saving technology to save more power. Green LED indicator shows the status of your network. Quick hardware button for WPS setup to enhance the security. Easy setup with Wi-Fi Protected Setup (WPS). Security support WPA/WPA2 (AES, 64,128-WEP with shared-key authentication). 802.11b/g/n 2.0 provide further coverage, less dead spot and higher throughput.

Model	RNX-N4PS
Standards	IEEE 802.3/3u, IEEE 802.11b/g, IEEE802.11n Draft 2
Interface	Ethernet Port
VPN support	IPSec, L2TP, and PPTP VPN passthrough
Dimensions	6.6" x 4.3" x 1.0"
Channels	11 (US, Canada), 13 (ETSI), 14 (Japan)
Frequency Band	2.4GHz - 2.484GHz
Data Rates	Up to 300Mbps
Ports	4 x 10/100M

Wireless Networking

FEATURES

SPECIFICATIONS



RNX-G40

All-in-one Internet-sharing AP Router, 4-port 10/100 Ethernet Switch, and 54Mbps Wireless-G (802.11b/g) Access Point. Shares a single Internet connection and other resources with Ethernet wired and Wireless-G and -B devices.. High security: TKIP and AES encryption, wireless MAC address filtering. Supports Inter-Access Point Protocol (IAPP). Supports Wireless Distribution System (WDS) Supports firewall security with port filtering, IP filtering, MAC filtering, port forwarding, trigger port and DMZ hosting functions. Supports PPTP Client on Ethernet WAN interface. Supports UPnP for automatic Internet access.

Model	RNX-G40
Standards	IEEE 802.11b/g
Device Management	Web-Based
WPA/WPA2	WPA2
Ports	1 x 10/100M WAN; 4 x 10/100M LAN
Data Rates	Up to 54Mbps
Modulation	CCK, DBPSK, DQPSK, OFDM
Frequency Band	2.4GHz - 2.4835GHz
Security	64 bit/ 128 bit WEP, WPA, WPA2, port filtering, IP filtering, MAC filtering, port forwarding and DMZ hosting, TKIP



RNX-EasyN1

Supports 802.11b/g/n 1T1R architecture with fully forward compatible with IEEE802.11n draft 4.0 and IEEE 802.11b/g standard. The easiest way to upgrade your system into wireless N network. Connect your PC/NB to a wireless network in minutes using high speed USB2.0 interface. 802.11b/g/n 4.0 provide further coverage, less dead spot and higher throughput. Easy setup with Wi-Fi Protected Setup (WPS). Security support WPA/WPA2 (AES, 64,128-WEP with shared-key authentication). Wireless Multimedia Enhancements Quality of Service support (QoS) / enhanced power saving for Dynamic Networking

Model	RNX-EasyN1
Standards	IEEE 802.11b/g/n
Data Rates	Up to 150Mbps
Interface	USB 2.0
Frequency Band	2.4GHz - 2.484GHz
Channels	11 (US, Canada) 13(Europe)
LEDs	Link/Activity
Antenna	Printed ANT
Security	WPA/WPA2 (AES, 64,128-WEP with shared-key authentication) WPS PIN, PBC, QoS-WMM



RNX-EasyN4

RNX-EasyN4 is a 2T2R Wireless Single chip 11N Broad-band Router that delivers up to 12x faster speeds and 4x extended coverage than 802.11g devices. supports home network with superior throughput and performance and unparalleled wireless range. With easy to use on the WPS function, it helps users to connect to wireless device with just one push button. supports home network with superior throughput and performance and unparalleled wireless range. With easy to use on the WPS function, it helps users to connect to wireless device with just one push button.

Model	RNX-EasyN4
Standards	IEEE 802.11b/g/n (ver2.0)
Data Rates	Up to 300Mbps
Interface	Ethernet Port
Frequency Band	2.4GHz - 2.484GHz
Antenna	Fixed 2 dBi Antenna x2
Ports	1 x 10/100M WAN; 4 x 10/100M LAN
Security	64/128 bit WEP Encryption WPA Personal (WPA Enterprise (WPA-EAP using TKIP) Wi-Fi Protection Setup (WPS)



RNX-A5

Works with Virtually Any 2.4GHz 802.11b/g Compliant Devices with a SMA Connector Powerful Signal Reception Antenna in All Directions. You can connect RNX-A5 with Wireless PCI card or wireless router to increase the wireless signal. Please make sure your antenna connector is SMA instead of TNC. This product can only be used to connect SMA type device. It can't be used with TNC interface

Model	RNX-A5
Type	Antenna
Specifications	S.W.R.: <= 2.0 @ 2400~2500 MHz Antenna Gain: 5 ± 0.7 dBi (Depends on Product Mechanical Environment) Impedance: 50 Ohm Material of Radiator: Cu (Plated) Connector Type: 50 Ohm SMA Male Reverse



RNX-A8

Works with Virtually Any 2.4GHz 802.11b/g Compliant Devices with a SMA Connector Powerful Signal Reception Antenna in All Directions. Works with Virtually Any 2.4GHz 802.11b/g Compliant Devices with a SMA Connector. You can connect RNX-A8 with Wireless PCI card or wireless router to increase the wireless signal. Please make sure your antenna connector is SMA instead of TNC. This product can only be used to connect SMA type device. It can't be used with TNC interface

Model	RNX-A8
Type	Antenna
Specifications	8dBi 2.4GHz

Wireless Networking

FEATURES

SPECIFICATIONS



RNX-A8-EX

Works with Virtually Any 2.4GHz 802.11b/g Compliant Devices with a SMA Connector
Powerful Signal Reception Antenna in All Directions. Works with Virtually Any 2.4GHz 802.11b/g Compliant Devices with a SMA Connector. You can connect RNX-A8-EX with Wireless PCI card or wireless router to increase the wireless signal. Magnetic Base with Extension Cable and Mounting Kit for Flexible Placement.
Please make sure your antenna connector is SMA instead of TNC. This product can only be used to connect SMA type device. It can't be used with TNC interface

Model	RNX-A8-EX
Type	Antenna
Specifications	2.4GHz 8dBi



RNX-A5-EX

Low loss extended Cable allows versatile placement for optimal coverage
Compatible with Rosewill TridentX series N desktop adapter and router
2.4 GHz indoor high gain antenna Increase the performance for 3x3/ 2x3 802.11N device.
5 dBi Omni directional antenna with magnetic base SMA connector. NOT for TNC interface device.

Model	RNX-A5-EX
Type	Antenna
Specifications	Frequency Range: 2.4.5GHz Gain(excluding cable loss): 5.0dBi, VSWR: 1.92 : 1 Max. Polarization: Linear; Vertical, Radiation pattern: Omni-directional Impedance: 50ohms, Connector: Reverse SMA Plug Cable Loss: 2.1dB Max. Cable Type: RG-174 Coaxial Cable Length: 100CM, Operating Temp: -10°C ~ + 60°C Upper Fixed Base: PU/PC, Bottom Fixed Base: PBT Color: Black, Weight: 0.53lbs



RNX-A7B

7ft RP-SMA to RJ-SMA Extension Cable. Great for extending the length of your wireless device to your Hi-Gain Antenna.

Model	RNX-A7B
Type	Cable
Specifications	Compatible Hi-Gain Rosewill RNX-A5/A8 series Antennas: Ultra-Low-Loss cables - 55.4db/100M @ 2500MHz Impedance – 50 Ohms 802.11 a/b/g Compatible Connector Type: RP-SMA Male to Female Length: 7.0 feet, Jacket Color: Black



RNX-A7W

7ft RP-SMA to RJ-SMA Extension Cable. Great for extending the length of your wireless device to your Hi-Gain Antenna.

Model	RNX-A7W
Type	Cable
Specifications	Compatible Hi-Gain Rosewill RNX-A5/A8 series Antennas: Ultra-Low-Loss cables - 55.4db/100M @ 2500MHz. Impedance – 50 Ohms 802.11 a/b/g Compatible Connector Type: RP-SMA Male to Female Length: 7.0 feet Jacket Color: White



RNX-A10-D

For all 2.4GHz design, such as AP, Router, etc.
For IEEE 802.11b/g 2.4GHz
High Gain
Easy installation
Paste or Wall Mount Available

Model	RNX-A10-D
Type	Antenna
Specifications	Frequency Range (Hz) : 2.4~2.5G Impedance (O) : 50 V.S.W.R. (?) : 2 Gain (dBi) : 10 Polarization ; Vertical, Linear HPBW @ 3dB : V:53°/H:49° Radiation :Directional RF Connector : SMA Jack

Wireless Networking

FEATURES

SPECIFICATIONS



RNX-A8

Works with Virtually Any 2.4GHz 802.11b/g Compliant Devices with a SMA Connector
 Powerful Signal Reception Antenna in All Directions. Works with Virtually Any 2.4GHz 802.11b/g Compliant Devices with a SMA Connector. You can connect RNX-A8 with Wireless PCI card or wireless router to increase the wireless signal.
 Please make sure your antenna connector is SMA instead of TNC. This product can only be used to connect SMA type device. It can't be used with TNC interface

Model	RNX-A8
Type	Antenna
Specifications	8dBi 2.4GHz



RNX-A13-D

For all 2.4GHz design, such as AP, Router, etc.
 High Gain
 4 in 1 Mounting kits-Desktop, Suction, Magnetic and Wall Mount
 Easy installation

Model	RNX-A13-D
Type	Antenna
Specifications	Frequency Range (Hz) : 2.4~2.5G
Impedance (O) :	50
V.S.W.R. (=) :	2
Gain (dBi) :	13
Polarization :	Vertical, Linear
HPBW @ 3dB : V:32°/H:34°	
Radiation :	Directional
Cable :	RG316
Cable Length (mm) :	300, RF Connector : Reverse SMA Plug



RNX-A12-D

For all 2.4GHz design, such as AP, Router, etc.
 High Gain
 Easy installation
 Stand or Wall Corner Mount available

Model	RNX-A12-D
Type	Antenna
Specifications	Frequency Range (Hz) : 2.4~2.5G
Impedance (O) :	50
V.S.W.R. (=) :	2
Gain (dBi) :	12
Polarization :	Vertical, Linear
Radiation :	Directional
Cable :	J100
Cable Length (mm) :	300
RF Connector :	Reverse SMA Plug



RNX-A8-D

For all 2.4GHz design, such as AP, Router, etc.
 High Gain
 Easy installation
 Stand or Wall Mount available

Model	RNX-A8-D
Type	Antenna
Specifications	Frequency Range (Hz) : 2.4~2.5G
Impedance (O) :	50
V.S.W.R. (=) :	2
Gain (dBi) :	8
Polarization :	Vertical, Linear
HPBW @ 3dB : V:60°/H:100°	
Radiation :	Directional
Cable :	J100
Cable Length (mm) :	300, RF Connector :Reverse SMA Plug

Remanufactured Toner

FEATURES

SPECIFICATIONS



RTC-C7115A

Reliable and Quality
Rosewill's replacement toner cartridges are 100% guaranteed to work as well or better than the original.

Significant Savings
You can be certain of that you're getting reliable print at a lower cost. We offer consumers and businesses up to a 50 percent savings.

Environmental Benefits
If you choose Rosewill's replacement toner cartridges, you will help to protect our environment by keeping reusable materials out of landfills.

Model	RTC-C7115A
Compatibility	HP LaserJet 1000 Series, 1200 Series, 1220 Series, 3300 Series, 3310 Series, 3320 Series, 3330 Series, and 3380 Series Printers
Color	Black
Approximate page yield	2,500 Standard Pages



RTC-Q2612A

Reliable and Quality
Rosewill's replacement toner cartridges are 100% guaranteed to work as well or better than the original.

Significant Savings
You can be certain of that you're getting reliable print at a lower cost. We offer consumers and businesses up to a 50 percent savings.

Environmental Benefits
If you choose Rosewill's replacement toner cartridges, you will help to protect our environment by keeping reusable materials out of landfills.

Model	RTC-Q2612A
Compatibility	HP LaserJet 1010, 1012, 1015, 3015, 3020, 3030, 3050, 3052, 3055 AIO, and M1319F MFP Series Printers
Color	Black
Approximate page yield	2,000 Standard Pages



RTC-Q2613X

Reliable and Quality
Rosewill's replacement toner cartridges are 100% guaranteed to work as well or better than the original.

Significant Savings
You can be certain of that you're getting reliable print at a lower cost. We offer consumers and businesses up to a 50 percent savings.

Environmental Benefits
If you choose Rosewill's replacement toner cartridges, you will help to protect our environment by keeping reusable materials out of landfills.

Model	RTC-Q2613X
Compatibility	HP LaserJet 1300 Series Printers
Color	Black
Approximate page yield	4,000 Standard Pages



RTC-Q5949X

Reliable and Quality
Rosewill's replacement toner cartridges are 100% guaranteed to work as well or better than the original.

Significant Savings
You can be certain of that you're getting reliable print at a lower cost. We offer consumers and businesses up to a 50 percent savings.

Environmental Benefits
If you choose Rosewill's replacement toner cartridges, you will help to protect our environment by keeping reusable materials out of landfills.

Model	RTC-Q5949X
Compatibility	HP LaserJet 1320, 3390, and 3392 Series Printers
Color	Black
Approximate page yield	6,000 Standard Pages



RTC-C7115X

Reliable and Quality
Rosewill's replacement toner cartridges are 100% guaranteed to work as well or better than the original.

Significant Savings
You can be certain of that you're getting reliable print at a lower cost. We offer consumers and businesses up to a 50 percent savings.

Environmental Benefits
If you choose Rosewill's replacement toner cartridges, you will help to protect our environment by keeping reusable materials out of landfills.

Model	RTC-C7115X
Compatibility	HP LaserJet 1000, 1200, 1220, 3300, 3310, 3320, 3330, and 3380 Series Printers
Color	Black
Approximate page yield	3,500 Standard Pages

Remanufactured Toner

FEATURES

SPECIFICATIONS



RTC-C4092A

Reliable and Quality
Rosewill's replacement toner cartridges are 100% guaranteed to work as well or better than the original.

Significant Savings
You can be certain of that you're getting reliable print at a lower cost. We offer consumers and businesses up to a 50 percent savings.

Environmental Benefits
If you choose Rosewill's replacement toner cartridges, you will help to protect our environment by keeping reusable materials out of landfills.

Model	RTC-C4092A
Compatibility	HP LaserJet 1100 Series, 3200 Series Printers
Color	Black
Approximate page yield	2,500 Standard Pages



RTC-Q5949A

Reliable and Quality
Rosewill's replacement toner cartridges are 100% guaranteed to work as well or better than the original.

Significant Savings
You can be certain of that you're getting reliable print at a lower cost. We offer consumers and businesses up to a 50 percent savings.

Environmental Benefits
If you choose Rosewill's replacement toner cartridges, you will help to protect our environment by keeping reusable materials out of landfills.

Model	RTC-Q5949A
Compatibility	HP LaserJet 1320, 3390, and 3392 Series Printers
Color	Black
Approximate page yield	2,500 Standard Pages



RTC-C4096A

Reliable and Quality
Rosewill's replacement toner cartridges are 100% guaranteed to work as well or better than the original.

Significant Savings
You can be certain of that you're getting reliable print at a lower cost. We offer consumers and businesses up to a 50 percent savings.

Environmental Benefits
If you choose Rosewill's replacement toner cartridges, you will help to protect our environment by keeping reusable materials out of landfills.

Model	RTC-C4096A
Compatibility	HP LaserJet 2100 and 2200 Series Printers
Color	Black
Approximate page yield	5000 Standard Pages



RTC-Q2610A

Reliable and Quality
Rosewill's replacement toner cartridges are 100% guaranteed to work as well or better than the original.

Significant Savings
You can be certain of that you're getting reliable print at a lower cost. We offer consumers and businesses up to a 50 percent savings.

Environmental Benefits
If you choose Rosewill's replacement toner cartridges, you will help to protect our environment by keeping reusable materials out of landfills.

Model	RTC-Q2610A
Compatibility	HP LaserJet 2300 Series Printers
Color	Black
Approximate page yield	6000 Standard Pages



RTC-Q6511A

Reliable and Quality
Rosewill's replacement toner cartridges are 100% guaranteed to work as well or better than the original.

Significant Savings
You can be certain of that you're getting reliable print at a lower cost. We offer consumers and businesses up to a 50 percent savings.

Environmental Benefits
If you choose Rosewill's replacement toner cartridges, you will help to protect our environment by keeping reusable materials out of landfills.

Model	RTC-Q6511A
Compatibility	HP LaserJet 2420, 2420d, 2420dn, 2420n, 2430dtn, 2430t, 2430tn Series Printers
Color	Black
Approximate page yield	6000 Standard Pages

Remanufactured Toner

FEATURES

SPECIFICATIONS



RTC-Q3960A

Reliable and Quality
Rosewill's replacement toner cartridges are 100% guaranteed to work as well or better than the original.

Significant Savings
You can be certain of that you're getting reliable print at a lower cost. We offer consumers and businesses up to a 50 percent savings.

Environmental Benefits
If you choose Rosewill's replacement toner cartridges, you will help to protect our environment by keeping reusable materials out of landfills.

Model	RTC-Q3960A
Compatibility	HP Color LaserJet 2550 and 2800 Series Printers
Color	Black
Approximate page yield	5000 Pages



RTC-Q3961A

Reliable and Quality
Rosewill's replacement toner cartridges are 100% guaranteed to work as well or better than the original.

Significant Savings
You can be certain of that you're getting reliable print at a lower cost. We offer consumers and businesses up to a 50 percent savings.

Environmental Benefits
If you choose Rosewill's replacement toner cartridges, you will help to protect our environment by keeping reusable materials out of landfills.

Model	RTC-Q3961A
Compatibility	HP Color LaserJet 2550 and 2800 Series Printers
Color	Cyan
Approximate page yield	4000 Pages



RTC-Q3962A

Reliable and Quality
Rosewill's replacement toner cartridges are 100% guaranteed to work as well or better than the original.

Significant Savings
You can be certain of that you're getting reliable print at a lower cost. We offer consumers and businesses up to a 50 percent savings.

Environmental Benefits
If you choose Rosewill's replacement toner cartridges, you will help to protect our environment by keeping reusable materials out of landfills.

Model	RTC-Q3962A
Compatibility	HP Color LaserJet 2550 and 2800 Series Printers
Color	Yellow
Approximate page yield	4000 Pages



RTC-Q3963A

Reliable and Quality
Rosewill's replacement toner cartridges are 100% guaranteed to work as well or better than the original.

Significant Savings
You can be certain of that you're getting reliable print at a lower cost. We offer consumers and businesses up to a 50 percent savings.

Environmental Benefits
If you choose Rosewill's replacement toner cartridges, you will help to protect our environment by keeping reusable materials out of landfills.

Model	RTC-Q3963A
Compatibility	HP Color LaserJet 2550 and 2800 Series Printers
Color	Magenta
Approximate page yield	4000 Pages



RTC-ML-1710D3

Reliable and Quality
Rosewill's replacement toner cartridges are 100% guaranteed to work as well or better than the original.

Significant Savings
You can be certain of that you're getting reliable print at a lower cost. We offer consumers and businesses up to a 50 percent savings.

Environmental Benefits
If you choose Rosewill's replacement toner cartridges, you will help to protect our environment by keeping reusable materials out of landfills.

Model	RTC-ML-1710D3
Compatibility	Samsung ML 1510, 1710, 1740, and 1750 Series Printers
Color	Black
Approximate page yield	3000 Pages Standard Pages

Remanufactured Toner

FEATURES

SPECIFICATIONS



RTC-Q1338A

Reliable and Quality
Rosewill's replacement toner cartridges are 100% guaranteed to work as well or better than the original.

Significant Savings
You can be certain of that you're getting reliable print at a lower cost. We offer consumers and businesses up to a 50 percent savings.

Environmental Benefits
If you choose Rosewill's replacement toner cartridges, you will help to protect our environment by keeping reusable materials out of landfills.

Model	RTC-Q1338A
Compatibility	HP LaserJet 4200 Series Printers
Color	Black
Approximate page yield	12,000 Standard Pages



RTC-Q1339A

Replacement Toner Cartridge for HP Q1339A

Reliable and Quality
Rosewill's replacement toner cartridges are 100% guaranteed to work as well or better than the original.

Significant Savings
You can be certain of that you're getting reliable print at a lower cost. We offer consumers and businesses up to a 50 percent savings.

Environmental Benefits
If you choose Rosewill's replacement toner cartridges, you will help to protect our environment by keeping reusable materials out of landfills.

Model	RTC-Q1339A
Compatibility	HP LaserJet 4300 Series Printers
Color	Black
Approximate page yield	18,000 Standard Pages



RTC-Q5942X

Reliable and Quality
Rosewill's replacement toner cartridges are 100% guaranteed to work as well or better than the original.

Significant Savings
You can be certain of that you're getting reliable print at a lower cost. We offer consumers and businesses up to a 50 percent savings.

Environmental Benefits
If you choose Rosewill's replacement toner cartridges, you will help to protect our environment by keeping reusable materials out of landfills.

Model	RTC-Q5942X
Compatibility	HP LaserJet 4240, 4250, and 4350 Series Printers
Color	Black
Approximate page yield	20,000 Standard Pages



RTC-C4182X

Reliable and Quality
Rosewill's replacement toner cartridges are 100% guaranteed to work as well or better than the original.

Significant Savings
You can be certain of that you're getting reliable print at a lower cost. We offer consumers and businesses up to a 50 percent savings.

Environmental Benefits
If you choose Rosewill's replacement toner cartridges, you will help to protect our environment by keeping reusable materials out of landfills.

Model	RTC-C4182X
Compatibility	HP LaserJet 8100 and 8150 Series Printers
Color	Black
Approximate page yield	20,000 Standard Pages



RTC-C9720A

Reliable and Quality
Rosewill's replacement toner cartridges are 100% guaranteed to work as well or better than the original.

- Significant Savings
You can be certain of that you're getting reliable print at a lower cost. We offer consumers and businesses up to a 50 percent savings.

- Environmental Benefits
If you choose Rosewill's replacement toner cartridges, you will help to protect our environment by keeping reusable materials out of landfills.

Model	RTC-C9720A
Compatibility	HP Color LaserJet 4600 and 4650 series printers
Color	Black
Approximate page yield	9000 Standard Pages

Remanufactured Toner

FEATURES

SPECIFICATIONS



RTC-C9721A

Reliable and Quality
Rosewill's replacement toner cartridges are 100% guaranteed to work as well or better than the original.

- Significant Savings

You can be certain of that you're getting reliable print at a lower cost. We offer consumers and businesses up to a 50 percent savings.

- Environmental Benefits

If you choose Rosewill's replacement toner cartridges, you will help to protect our environment by keeping reusable materials out of landfills

Model	RTC-C9721A
Compatibility	HP Color LaserJet 4600 and 4650 series printers
Color	Cyan
Approximate page yield	8000 Standard Pages



RTC-C9722A

Reliable and Quality
Rosewill's replacement toner cartridges are 100% guaranteed to work as well or better than the original.

- Significant Savings

You can be certain of that you're getting reliable print at a lower cost. We offer consumers and businesses up to a 50 percent savings.

- Environmental Benefits

If you choose Rosewill's replacement toner cartridges, you will help to protect our environment by keeping reusable materials out of landfills

Model	RTC-C9722A
Compatibility	HP Color LaserJet 4600 and 4650 series printers
Color	Yellow
Approximate page yield	8000 Standard Pages



RTC-C9723A

Reliable and Quality
Rosewill's replacement toner cartridges are 100% guaranteed to work as well or better than the original.

- Significant Savings

You can be certain of that you're getting reliable print at a lower cost. We offer consumers and businesses up to a 50 percent savings.

- Environmental Benefits

If you choose Rosewill's replacement toner cartridges, you will help to protect our environment by keeping reusable materials out of landfills

Model	RTC-C9723A
Compatibility	HP Color LaserJet 4600 and 4650 series printers
Color	Magenta
Approximate page yield	8000 Standard Pages



RTC-Q6511X

Reliable and Quality
Rosewill's replacement toner cartridges are 100% guaranteed to work as well or better than the original.

- Significant Savings

You can be certain of that you're getting reliable print at a lower cost. We offer consumers and businesses up to a 50 percent savings.

- Environmental Benefits

If you choose Rosewill's replacement toner cartridges, you will help to protect our environment by keeping reusable materials out of landfills

Model	RTC-Q6511X
Compatibility	HP LaserJet 2420, 2420d, 2420dn, 2420n, 2430dtn, 2430t, 2430tn Series Printers
Color	Black
Approximate page yield	12000 Pages



RTC-C4127X

Reliable and Quality
Rosewill's replacement toner cartridges are 100% guaranteed to work as well or better than the original.

- Significant Savings

You can be certain of that you're getting reliable print at a lower cost. We offer consumers and businesses up to a 50 percent savings.

- Environmental Benefits

If you choose Rosewill's replacement toner cartridges, you will help to protect our environment by keeping reusable materials out of landfills

Model	RTC-C4127X
Compatibility	HP LaserJet 4000 and 4050 Series Printers
Color	Black
Approximate page yield	10000 Pages

Remanufactured Toner

FEATURES

SPECIFICATIONS



RTC-C8061X

Reliable and Quality
Rosewill's replacement toner cartridges are 100% guaranteed to work as well or better than the original.

- Significant Savings

You can be certain of that you're getting reliable print at a lower cost. We offer consumers and businesses up to a 50 percent savings.

- Environmental Benefits

If you choose Rosewill's replacement toner cartridges, you will help to protect our environment by keeping reusable materials out of landfills

Model	RTC-C8061X
Compatibility	HP LaserJet 4100 Series Printers and 4101 MFP Printers
Color	Black
Approximate page yield	10000 Standard Pages



RTC-Q7553A

Reliable and Quality
Rosewill's replacement toner cartridges are 100% guaranteed to work as well or better than the original.

- Significant Savings

You can be certain of that you're getting reliable print at a lower cost. We offer consumers and businesses up to a 50 percent savings.

- Environmental Benefits

If you choose Rosewill's replacement toner cartridges, you will help to protect our environment by keeping reusable materials out of landfills

Model	RTC-Q7553A
Compatibility	HP LaserJet P2015 Series Printers
Color	Black
Approximate page yield	3000 Standard Pages



RTC-Q7551X

Reliable and Quality
Rosewill's replacement toner cartridges are 100% guaranteed to work as well or better than the original.

- Significant Savings

You can be certain of that you're getting reliable print at a lower cost. We offer consumers and businesses up to a 50 percent savings.

- Environmental Benefits

If you choose Rosewill's replacement toner cartridges, you will help to protect our environment by keeping reusable materials out of landfills

Model	RTC-Q7551X
Compatibility	HP LaserJet P3005, M3027 MFP, and M3035MFP Series Printers
Color	Black
Approximate page yield	13000 Pages



RTC-Q7551A

Reliable and Quality
Rosewill's replacement toner cartridges are 100% guaranteed to work as well or better than the original.

- Significant Savings

You can be certain of that you're getting reliable print at a lower cost. We offer consumers and businesses up to a 50 percent savings.

- Environmental Benefits

If you choose Rosewill's replacement toner cartridges, you will help to protect our environment by keeping reusable materials out of landfills

Model	RTC-Q7551A
Compatibility	HP LaserJet P3005, M3027 MFP, and M3035MFP Series Printers
Color	Black
Approximate page yield	6500 Pages



RTC-Q7553X

Reliable and Quality
Rosewill's replacement toner cartridges are 100% guaranteed to work as well or better than the original.

- Significant Savings

You can be certain of that you're getting reliable print at a lower cost. We offer consumers and businesses up to a 50 percent savings.

- Environmental Benefits

If you choose Rosewill's replacement toner cartridges, you will help to protect our environment by keeping reusable materials out of landfills

Model	RTC-Q7553X
Compatibility	HP LaserJet P2015 Series Printers
Color	Black
Approximate page yield	7000 Pages

Remanufactured Toner

FEATURES

SPECIFICATIONS



RTC-Q6470A

Reliable and Quality
Rosewill's replacement toner cartridges are 100% guaranteed to work as well or better than the original.

Significant Savings
You can be certain of that you're getting reliable print at a lower cost. We offer consumers and businesses up to a 50 percent savings.

Environmental Benefits
If you choose Rosewill's replacement toner cartridges, you will help to protect our environment by keeping reusable materials out of landfills.

Model	RTC-Q6470A
Compatibility	HP Color LaserJet 3600 and 3800 Series printers
Color	Black
Approximate page yield	6000 Pages



RTC-Q6471A

Reliable and Quality
Rosewill's replacement toner cartridges are 100% guaranteed to work as well or better than the original.

Significant Savings
You can be certain of that you're getting reliable print at a lower cost. We offer consumers and businesses up to a 50 percent savings.

Environmental Benefits
If you choose Rosewill's replacement toner cartridges, you will help to protect our environment by keeping reusable materials out of landfills.

Model	RTC-Q6471A
Compatibility	HP Color LaserJet 3600 Series printers
Color	Cyan
Approximate page yield	4000 Pages



RTC-Q6472A

Reliable and Quality
Rosewill's replacement toner cartridges are 100% guaranteed to work as well or better than the original.

Significant Savings
You can be certain of that you're getting reliable print at a lower cost. We offer consumers and businesses up to a 50 percent savings.

Environmental Benefits
If you choose Rosewill's replacement toner cartridges, you will help to protect our environment by keeping reusable materials out of landfills.

Model	RTC-Q6472A
Compatibility	HP Color LaserJet 3600 Series printers
Color	Yellow
Approximate page yield	4000 Pages



RTC-Q6473A

Reliable and Quality
Rosewill's replacement toner cartridges are 100% guaranteed to work as well or better than the original.

Significant Savings
You can be certain of that you're getting reliable print at a lower cost. We offer consumers and businesses up to a 50 percent savings.

Environmental Benefits
If you choose Rosewill's replacement toner cartridges, you will help to protect our environment by keeping reusable materials out of landfills.

Model	RTC-Q6473A
Compatibility	HP Color LaserJet 3600 Series printers
Color	Magenta
Approximate page yield	4000 Pages



RTC-Q2670A

Reliable and Quality
Rosewill's replacement toner cartridges are 100% guaranteed to work as well or better than the original.

Significant Savings
You can be certain of that you're getting reliable print at a lower cost. We offer consumers and businesses up to a 50 percent savings.

Environmental Benefits
If you choose Rosewill's replacement toner cartridges, you will help to protect our environment by keeping reusable materials out of landfills.

Model	RTC-Q2670A
Compatibility	HP Color LaserJet 3500, 3550 and 3700 Series printers
Color	Black
Approximate page yield	6000 Pages

Remanufactured Toner

FEATURES

SPECIFICATIONS



RTC-Q2671A

Reliable and Quality
Rosewill's replacement toner cartridges are 100% guaranteed to work as well or better than the original.

Significant Savings
You can be certain of that you're getting reliable print at a lower cost. We offer consumers and businesses up to a 50 percent savings.

Environmental Benefits
If you choose Rosewill's replacement toner cartridges, you will help to protect our environment by keeping reusable materials out of landfills.

Model	RTC-Q2671A
Compatibility	HP Color LaserJet 3500 and 3550 Series printers
Color	Cyan
Approximate page yield	4000 Pages



RTC-Q2672A

Reliable and Quality
Rosewill's replacement toner cartridges are 100% guaranteed to work as well or better than the original.

Significant Savings
You can be certain of that you're getting reliable print at a lower cost. We offer consumers and businesses up to a 50 percent savings.

Environmental Benefits
If you choose Rosewill's replacement toner cartridges, you will help to protect our environment by keeping reusable materials out of landfills.

Model	RTC-Q2672A
Compatibility	HP Color LaserJet 3500 and 3550 Series printers
Color	Yellow
Approximate page yield	4000 Pages



RTC-Q2673A

Reliable and Quality
Rosewill's replacement toner cartridges are 100% guaranteed to work as well or better than the original.

Significant Savings
You can be certain of that you're getting reliable print at a lower cost. We offer consumers and businesses up to a 50 percent savings.

Environmental Benefits
If you choose Rosewill's replacement toner cartridges, you will help to protect our environment by keeping reusable materials out of landfills.

Model	RTC-Q2673A
Compatibility	HP Color LaserJet 3500 and 3550 Series printers
Color	Magenta
Approximate page yield	4000 Pages



RTC-Q2681A

Reliable and Quality
Rosewill's replacement toner cartridges are 100% guaranteed to work as well or better than the original.

Significant Savings
You can be certain of that you're getting reliable print at a lower cost. We offer consumers and businesses up to a 50 percent savings.

Environmental Benefits
If you choose Rosewill's replacement toner cartridges, you will help to protect our environment by keeping reusable materials out of landfills.

Model	RTC-Q2681A
Compatibility	HP Color LaserJet 3700 Series printers
Color	Cyan
Approximate page yield	6000 Pages



RTC-Q2682A

Reliable and Quality
Rosewill's replacement toner cartridges are 100% guaranteed to work as well or better than the original.

Significant Savings
You can be certain of that you're getting reliable print at a lower cost. We offer consumers and businesses up to a 50 percent savings.

Environmental Benefits
If you choose Rosewill's replacement toner cartridges, you will help to protect our environment by keeping reusable materials out of landfills.

Model	RTC-Q2682A
Compatibility	HP Color LaserJet 3700 Series printers
Color	Yellow
Approximate page yield	6000 Pages

Remanufactured Toner

FEATURES

SPECIFICATIONS



RTC-Q2683A

Reliable and Quality
Rosewill's replacement toner cartridges are 100% guaranteed to work as well or better than the original.

Significant Savings
You can be certain of that you're getting reliable print at a lower cost. We offer consumers and businesses up to a 50 percent savings.

Environmental Benefits
If you choose Rosewill's replacement toner cartridges, you will help to protect our environment by keeping reusable materials out of landfills.

Model	RTC-Q2683A
Compatibility	HP Color LaserJet 3700 Series printers
Color	Magenta
Approximate page yield	6000 Pages



RTC-CB436A

Reliable and Quality
Rosewill's replacement toner cartridges are 100% guaranteed to work as well or better than the original.

Significant Savings
You can be certain of that you're getting reliable print at a lower cost. We offer consumers and businesses up to a 50 percent savings.

Environmental Benefits
If you choose Rosewill's replacement toner cartridges, you will help to protect our environment by keeping reusable materials out of landfills.

Model	RTC-CB436A
Compatibility	HP Laserjet M1522n, M1522nf, P1505, P1505n Series Printers
Color	Black
Approximate page yield	2000 Pages



RTC-CB435A

Reliable and Quality
Rosewill's replacement toner cartridges are 100% guaranteed to work as well or better than the original.

Significant Savings
You can be certain of that you're getting reliable print at a lower cost. We offer consumers and businesses up to a 50 percent savings.

Environmental Benefits
If you choose Rosewill's replacement toner cartridges, you will help to protect our environment by keeping reusable materials out of landfills.

Model	RTC-CB435A
Compatibility	HP Laserjet P1005 and P1006 Series Printers
Color	Black
Approximate page yield	1500 Pages



RTC-SCX-4521D3

Reliable and Quality
Rosewill's replacement toner cartridges are 100% guaranteed to work as well or better than the original.

Significant Savings
You can be certain of that you're getting reliable print at a lower cost. We offer consumers and businesses up to a 50 percent savings.

Environmental Benefits
If you choose Rosewill's replacement toner cartridges, you will help to protect our environment by keeping reusable materials out of landfills.

Model	RTC-SCX-4521D3
Compatibility	Samsung ML SCX 4321 and SCX 4521 Series Printers
Color	Black
Approximate page yield	3000 Pages



RTC-ML2010D3

Reliable and Quality
Rosewill's replacement toner cartridges are 100% guaranteed to work as well or better than the original.

Significant Savings
You can be certain of that you're getting reliable print at a lower cost. We offer consumers and businesses up to a 50 percent savings.

Environmental Benefits
If you choose Rosewill's replacement toner cartridges, you will help to protect our environment by keeping reusable materials out of landfills.

Model	RTC-ML2010D3
Compatibility	SAMSUNG ML-2010
Color	Black
Approximate page yield	3000 Pages

Remanufactured Toner

FEATURES

SPECIFICATIONS



RTC-TN570

Reliable and Quality:
Rosewill's replacement toner cartridges are 100% guaranteed to work as well or better than the original.

Significant Savings:
You can be certain of that you're getting reliable print at a lower cost. We offer consumers and businesses up to a 50 percent savings.

Environmental Benefits:
If you choose Rosewill's replacement toner cartridges, you will help to protect our environment by keeping reusable materials out of landfills.

Model	RTC-TN570
Compatibility	Brother DCP-8040, DCP-8045D, HL-5140, HL-5150D, HL-5150DLT, HL-5170DN, HL-5170DNLT, MFC-8120, MFC-8220, MFC-8440, MFC-8640D, MFC-8840D, MFC-8840DN Series Printers
Color	Black
Approximate page yield	6,700 Standard Pages



RTCA-Q7553A

Reliable and Quality:
Rosewill's replacement toner cartridges are 100% guaranteed to work as well or better than the original.

Significant Savings:
You can be certain of that you're getting reliable print at a lower cost. We offer consumers and businesses up to a 50 percent savings.

Environmental Benefits:
If you choose Rosewill's replacement toner cartridges, you will help to protect our environment by keeping reusable materials out of landfills.

Model	RTCA-Q7553A
Compatibility	LaserJet M2727nf MFP, P2014, P2015, P2015d, P2015dn, P2015n, P2015x series printer
Color	Black
Approximate page yield	3,000 Pages



RTC-CLP-Y300A

Reliable and Quality:
Rosewill's replacement toner cartridges are 100% guaranteed to work as well or better than the original.

Significant Savings:
You can be certain of that you're getting reliable print at a lower cost. We offer consumers and businesses up to a 50 percent savings.

Environmental Benefits:
If you choose Rosewill's replacement toner cartridges, you will help to protect our environment by keeping reusable materials out of landfills.

Model	RTC-CLP-Y300A
Compatibility	SAMSUNG CLP-300, CLP-300N, CLX-3160 series printer
Color	Yellow
Approximate page yield	1,000 Standard Pages



RTC-CLP-M300A

Reliable and Quality:
Rosewill's replacement toner cartridges are 100% guaranteed to work as well or better than the original.

Significant Savings:
You can be certain of that you're getting reliable print at a lower cost. We offer consumers and businesses up to a 50 percent savings.

Environmental Benefits:
If you choose Rosewill's replacement toner cartridges, you will help to protect our environment by keeping reusable materials out of landfills.

Model	RTC-CLP-M300A
Compatibility	SAMSUNG CLP-300, CLP-300N, CLX-3160 series printer
Color	Magenta
Approximate page yield	1,000 Standard Pages



RTC-CLP-C300A

Reliable and Quality:
Rosewill's replacement toner cartridges are 100% guaranteed to work as well or better than the original.

Significant Savings:
You can be certain of that you're getting reliable print at a lower cost. We offer consumers and businesses up to a 50 percent savings.

Environmental Benefits:
If you choose Rosewill's replacement toner cartridges, you will help to protect our environment by keeping reusable materials out of landfills.

Model	RTC-CLP-C300A
Compatibility	SAMSUNG CLP-300, CLP-300N, CLX-3160 series printer
Color	Cyan
Approximate page yield	1,000 Standard Pages

Remanufactured Toner

FEATURES

SPECIFICATIONS



RTC-CLP-K300A

Reliable and Quality:
Rosewill's replacement toner cartridges are 100% guaranteed to work as well or better than the original.

Significant Savings:
You can be certain of that you're getting reliable print at a lower cost. We offer consumers and businesses up to a 50 percent savings.

Environmental Benefits:
If you choose Rosewill's replacement toner cartridges, you will help to protect our environment by keeping reusable materials out of landfills.

Model	RTC-CLP-K300A
Compatibility	SAMSUNG CLP-300, CLP-300N, CLX-3160 series printer
Color	Black
Approximate page yield	2,000 Standard Pages



RTC-Q2624X

Reliable and Quality:
Rosewill's replacement toner cartridges are 100% guaranteed to work as well or better than the original.

Significant Savings:
You can be certain of that you're getting reliable print at a lower cost. We offer consumers and businesses up to a 50 percent savings.

Environmental Benefits:
If you choose Rosewill's replacement toner cartridges, you will help to protect our environment by keeping reusable materials out of landfills.

Model	RTC-Q2624X
Compatibility	HP LaserJet 1150 series printer
Color	Black
Approximate page yield	4,000 Standard Pages



RTC-Q6003A

Reliable and Quality:
Rosewill's replacement toner cartridges are 100% guaranteed to work as well or better than the original.

Significant Savings:
You can be certain of that you're getting reliable print at a lower cost. We offer consumers and businesses up to a 50 percent savings.

Environmental Benefits:
If you choose Rosewill's replacement toner cartridges, you will help to protect our environment by keeping reusable materials out of landfills.

Model	RTC-Q6003A
Compatibility	HP Color LaserJet 1600, 2600n, 2605dn, 2605dtn, CM1015MFP, CM1017MFP series printer
Color	Magenta
Approximate page yield	2,000 Standard Pages



RTC-Q6002A

Reliable and Quality:
Rosewill's replacement toner cartridges are 100% guaranteed to work as well or better than the original.

Significant Savings:
You can be certain of that you're getting reliable print at a lower cost. We offer consumers and businesses up to a 50 percent savings.

Environmental Benefits:
If you choose Rosewill's replacement toner cartridges, you will help to protect our environment by keeping reusable materials out of landfills.

Model	RTC-Q6002A
Compatibility	HP Color LaserJet 1600, 2600n, 2605dn, 2605dtn, CM1015MFP, CM1017MFP series printer
Color	Yellow
Approximate page yield	2,000 Standard Pages



RTC-Q6001A

Reliable and Quality:
Rosewill's replacement toner cartridges are 100% guaranteed to work as well or better than the original.

Significant Savings:
You can be certain of that you're getting reliable print at a lower cost. We offer consumers and businesses up to a 50 percent savings.

Environmental Benefits:
If you choose Rosewill's replacement toner cartridges, you will help to protect our environment by keeping reusable materials out of landfills.

Model	RTC-Q6001A
Compatibility	HP Color LaserJet 1600, 2600n, 2605dn, 2605dtn, CM1015MFP, CM1017MFP series printer
Color	Cyan
Approximate page yield	2,000 Standard Pages

Remanufactured Toner

FEATURES

SPECIFICATIONS



RTC-Q6000A

Reliable and Quality:
Rosewill's replacement toner cartridges are 100% guaranteed to work as well or better than the original.

Significant Savings:
You can be certain of that you're getting reliable print at a lower cost. We offer consumers and businesses up to a 50 percent savings.

Environmental Benefits:
If you choose Rosewill's replacement toner cartridges, you will help to protect our environment by keeping reusable materials out of landfills.

Model	RTC-Q6000A
Compatibility	HP Color LaserJet 1600, 2600n, 2605dn, 2605dtn, CM1015MFP, CM1017MFP series printer
Color	Black
Approximate page yield	2500 Standard Pages



RTC-X25

Reliable and Quality:
Rosewill's replacement toner cartridges are 100% guaranteed to work as well or better than the original.

Significant Savings:
You can be certain of that you're getting reliable print at a lower cost. We offer consumers and businesses up to a 50 percent savings.

Environmental Benefits:
If you choose Rosewill's replacement toner cartridges, you will help to protect our environment by keeping reusable materials out of landfills.

Model	RTC-X25
Compatibility	Canon imageCLASS MF3110, MF3111, MF5530, MF5550, MF5730, MF5750, MF5770 series printer
Color	Black
Approximate page yield	2500 Standard Pages



RTC-TN360

Reliable and Quality:
Rosewill's replacement toner cartridges are 100% guaranteed to work as well or better than the original.

Significant Savings:
You can be certain of that you're getting reliable print at a lower cost. We offer consumers and businesses up to a 50 percent savings.

Environmental Benefits:
If you choose Rosewill's replacement toner cartridges, you will help to protect our environment by keeping reusable materials out of landfills.

Model	RTC-TN360
Compatibility	Brother DCP-7040, HL-2140, 2170W, MFC-7440N, 7840W series printer
Color	Black
Approximate page yield	2600 Standard Pages



RTC-TN350

Reliable and Quality:
Rosewill's replacement toner cartridges are 100% guaranteed to work as well or better than the original.

Significant Savings:
You can be certain of that you're getting reliable print at a lower cost. We offer consumers and businesses up to a 50 percent savings.

Environmental Benefits:
If you choose Rosewill's replacement toner cartridges, you will help to protect our environment by keeping reusable materials out of landfills.

Model	RTC-TN350
Compatibility	Brother MFC-7220, 7225N, 7420, 7820, 7820N DCP-7020, HL-2030, 2040, 2070N, IntelliFax 2820, 2910, 2920 series printer-
Color	Black
Approximate page yield	2500 Standard Pages



RTC-DR350

Reliable and Quality:
Rosewill's replacement toner cartridges are 100% guaranteed to work as well or better than the original.

Significant Savings:
You can be certain of that you're getting reliable print at a lower cost. We offer consumers and businesses up to a 50 percent savings.

Environmental Benefits:
If you choose Rosewill's replacement toner cartridges, you will help to protect our environment by keeping reusable materials out of landfills.

Model	RTC-DR350
Compatibility	Brother MFC-7220, 7225N, 7420, 7820, 7820N, DCP-7020, HL-2030, 2040, 2070N, IntelliFax 2820, 2910, 2920 series printer
Color	Cyan
Approximate page yield	12000 Standard Pages

Remanufactured Toner

FEATURES

SPECIFICATIONS



RTCA-ML-2850B

Reliable and Quality:
Rosewill's replacement toner cartridges are 100% guaranteed to work as well or better than the original.

Significant Savings:
You can be certain of that you're getting reliable print at a lower cost. We offer consumers and businesses up to a 50 percent savings.

Environmental Benefits:
If you choose Rosewill's replacement toner cartridges, you will help to protect our environment by keeping reusable materials out of landfills.

Model	RTCA-ML-2850B
Compatibility	Samsung ML-2850D, ML-2851ND
Color	Black
Approximate page yield	5,000 Pages



RTCA-AL100TD

Reliable and Quality:
Rosewill's replacement toner cartridges are 100% guaranteed to work as well or better than the original.

Significant Savings:
You can be certain of that you're getting reliable print at a lower cost. We offer consumers and businesses up to a 50 percent savings.

Environmental Benefits:
If you choose Rosewill's replacement toner cartridges, you will help to protect our environment by keeping reusable materials out of landfills.

Model	RTCA-AL100TD
Compatibility	Sharp AL-1000 Printer
Color	Black
Approximate page yield	6,000 Pages



RTCA-Q7553X

Reliable and Quality:
Rosewill's replacement toner cartridges are 100% guaranteed to work as well or better than the original.

Significant Savings:
You can be certain of that you're getting reliable print at a lower cost. We offer consumers and businesses up to a 50 percent savings.

Environmental Benefits:
If you choose Rosewill's replacement toner cartridges, you will help to protect our environment by keeping reusable materials out of landfills.

Model	RTCA-Q7553X
Compatibility	HP LaserJet M2727nf MFP, P2014, P2015, P2015d, P2015dn, P2015n, P2015x
Color	Black
Approximate page yield	7,000 Pages



RTCA-C4129X

Reliable and Quality:
Rosewill's replacement toner cartridges are 100% guaranteed to work as well or better than the original.

Significant Savings:
You can be certain of that you're getting reliable print at a lower cost. We offer consumers and businesses up to a 50 percent savings.

Environmental Benefits:
If you choose Rosewill's replacement toner cartridges, you will help to protect our environment by keeping reusable materials out of landfills.

Model	RTCA-C4129X
Compatibility	HP LaserJet 5000, 5000GN, 5000N, 5100, 5100dtn, 5100tn, CANON FP-300 Micrographics, FP-400 Micrographics, GP-160F, ImageCLASS 2200, 2210, 2220, 2250, LBP-1610, 1620, 1810, 1820, 62X, 840, 850, 870, 880, 910
Color	Black
Approximate page yield	10,000 Standard Pages



RTCA-Q7582A

Reliable and Quality:
Rosewill's replacement toner cartridges are 100% guaranteed to work as well or better than the original.

Significant Savings:
You can be certain of that you're getting reliable print at a lower cost. We offer consumers and businesses up to a 50 percent savings.

Environmental Benefits:
If you choose Rosewill's replacement toner cartridges, you will help to protect our environment by keeping reusable materials out of landfills.

Model	RTCA-Q7582A
Compatibility	HP Color LaserJet 3800, 3800dn, 3800dtn, 3800n, CP3505, CP3505dn, CP3505n, CP3505x
Color	Yellow
Approximate page yield	6,000 Pages

Remanufactured Toner

FEATURES

SPECIFICATIONS



RTCA-Q7581A

Reliable and Quality:
Rosewill's replacement toner cartridges are 100% guaranteed to work as well or better than the original.

Significant Savings:
You can be certain of that you're getting reliable print at a lower cost. We offer consumers and businesses up to a 50 percent savings.

Environmental Benefits:
If you choose Rosewill's replacement toner cartridges, you will help to protect our environment by keeping reusable materials out of landfills.

Model	RTCA-Q7581A
Compatibility	HP Color LaserJet 3800, 3800dn, 3800dtn, 3800n, CP3505, CP3505dn, CP3505n, CP3505x
Color	Cyan
Approximate page yield	6,000 Pages



RTCA-CB542A

Reliable and Quality:
Rosewill's replacement toner cartridges are 100% guaranteed to work as well or better than the original.

Significant Savings:
You can be certain of that you're getting reliable print at a lower cost. We offer consumers and businesses up to a 50 percent savings.

Environmental Benefits:
If you choose Rosewill's replacement toner cartridges, you will help to protect our environment by keeping reusable materials out of landfills.

Model	RTCA-CB542A
Compatibility	HP Color LaserJet CP1515n, CP1518ni, CP1215, CM1312 MFP
Color	Yellow
Approximate page yield	1,400 Pages



RTCA-CB543A

Reliable and Quality:
Rosewill's replacement toner cartridges are 100% guaranteed to work as well or better than the original.

Significant Savings:
You can be certain of that you're getting reliable print at a lower cost. We offer consumers and businesses up to a 50 percent savings.

Environmental Benefits:
If you choose Rosewill's replacement toner cartridges, you will help to protect our environment by keeping reusable materials out of landfills.

Model	RTCA-CB543A
Compatibility	HP Color LaserJet CP1515n, CP1518ni, CP1215, CM1312 MFP
Color	Magenta
Approximate page yield	1,400 Pages



RTCA-CB541A

Reliable and Quality:
Rosewill's replacement toner cartridges are 100% guaranteed to work as well or better than the original.

Significant Savings:
You can be certain of that you're getting reliable print at a lower cost. We offer consumers and businesses up to a 50 percent savings.

Environmental Benefits:
If you choose Rosewill's replacement toner cartridges, you will help to protect our environment by keeping reusable materials out of landfills.

Model	RTCA-CB541A
Compatibility	HP Color LaserJet CP1515n, CP1518ni, CP1215, CM1312 MFP
Color	Cyan
Approximate page yield	1,400 Pages



RTCA-CB540A

Reliable and Quality:
Rosewill's replacement toner cartridges are 100% guaranteed to work as well or better than the original.

Significant Savings:
You can be certain of that you're getting reliable print at a lower cost. We offer consumers and businesses up to a 50 percent savings.

Environmental Benefits:
If you choose Rosewill's replacement toner cartridges, you will help to protect our environment by keeping reusable materials out of landfills.

Model	RTCA-CB540A
Compatibility	HP Color LaserJet CP1515n, CP1518ni, CP1215, CM1312 MFP
Color	Black
Approximate page yield	2,200 Pages

Remanufactured Toner

FEATURES

SPECIFICATIONS



RTCA-C106

Reliable and Quality:
Rosewill's replacement toner cartridges are 100% guaranteed to work as well or better than the original.

Significant Savings:
You can be certain of that you're getting reliable print at a lower cost. We offer consumers and businesses up to a 50 percent savings.

Environmental Benefits:
If you choose Rosewill's replacement toner cartridges, you will help to protect our environment by keeping reusable materials out of landfills.

Model	RTCA-C106
Compatibility	Canon imageCLASS MF6500, MF6530, MF6550, MF6560, MF6580, LaserBase MF6530, MF6540PL, MF6550PL, MF6560PL, MF6580
Color	Black
Approximate page yield	5,000 Pages



RTCA-S35

Reliable and Quality:
Rosewill's replacement toner cartridges are 100% guaranteed to work as well or better than the original.

Significant Savings:
You can be certain of that you're getting reliable print at a lower cost. We offer consumers and businesses up to a 50 percent savings.

Environmental Benefits:
If you choose Rosewill's replacement toner cartridges, you will help to protect our environment by keeping reusable materials out of landfills.

Model	RTCA-S35
Compatibility	Canon FAX L360, L380, L380S, L390, L400, FAXPHONE L170, imageCLASS D320, D340, 310, Laser Class 510, PC-D320, PC-D340
Color	Black
Approximate page yield	5,000 Pages



RTCA-L50

Reliable and Quality:
Rosewill's replacement toner cartridges are 100% guaranteed to work as well or better than the original.

Significant Savings:
You can be certain of that you're getting reliable print at a lower cost. We offer consumers and businesses up to a 50 percent savings.

Environmental Benefits:
If you choose Rosewill's replacement toner cartridges, you will help to protect our environment by keeping reusable materials out of landfills.

Model	RTCA-L50
Compatibility	Canon imageCLASS D660, D661, D680, D760, D761, D780, D860, D861, D880, PC-1060, 1061, 1080F
Color	Black
Approximate page yield	5,000 Pages



RTCA-E40

Reliable and Quality:
Rosewill's replacement toner cartridges are 100% guaranteed to work as well or better than the original.

Significant Savings:
You can be certain of that you're getting reliable print at a lower cost. We offer consumers and businesses up to a 50 percent savings.

Environmental Benefits:
If you choose Rosewill's replacement toner cartridges, you will help to protect our environment by keeping reusable materials out of landfills.

Model	RTCA-E40
Compatibility	Canon FC-200, 204, 220, 310, 330, 336, PC-140, 150, 160, 170, 300, 310, 320, 325, 330, 330L, 400, 420, 425, 428, 430, 530, 550, 710, 720, 730, 735, 740, 745, 760, 770, 775, 785, 790, 795, 860, 880, 890, 920, 921, 940, 941, 950, 980, 981
Color	Black
Approximate page yield	4,000 Standard Pages



RTCA-FX9

Reliable and Quality:
Rosewill's replacement toner cartridges are 100% guaranteed to work as well or better than the original.

Significant Savings:
You can be certain of that you're getting reliable print at a lower cost. We offer consumers and businesses up to a 50 percent savings.

Environmental Benefits:
If you choose Rosewill's replacement toner cartridges, you will help to protect our environment by keeping reusable materials out of landfills.

Model	RTCA-FX9
Compatibility	Canon FaxL100, Faxphone L120, imageCLASS MF4150, MF4690, I-Sensys 4120, 4140, 4150, Satera MF4130, MF4150, MF6570
Color	Black
Approximate page yield	2,000 Pages

Remanufactured Toner

FEATURES

SPECIFICATIONS



RTCA-TN580

Reliable and Quality:
Rosewill's replacement toner cartridges are 100% guaranteed to work as well or better than the original.

Significant Savings:
You can be certain of that you're getting reliable print at a lower cost. We offer consumers and businesses up to a 50 percent savings.

Environmental Benefits:
If you choose Rosewill's replacement toner cartridges, you will help to protect our environment by keeping reusable materials out of landfills.

Model	RTCA-TN580
Compatibility	Brother DCP-8020, DCP-8025D, DCP-8025DN, HL-1650, HL-1670N, HL-1850, HL-1870N, HL-5040, HL-5050, HL-5070n, MFC-8420, MFC-8820D, MFC-8820DN
Color	Black
Approximate page yield	7,000 Pages



RTCA-DR510

Reliable and Quality:
Rosewill's replacement toner cartridges are 100% guaranteed to work as well or better than the original.

Significant Savings:
You can be certain of that you're getting reliable print at a lower cost. We offer consumers and businesses up to a 50 percent savings.

Environmental Benefits:
If you choose Rosewill's replacement toner cartridges, you will help to protect our environment by keeping reusable materials out of landfills.

Model	RTCA-DR510
Compatibility	Brother MFC-8220, MFC-8440, MFC-8640D, MFC-8840D, MFC-8840DN, DCP-8040, DCP-8045D, HL-5130, HL-5140, HL-5150D, HL-5150DLT, HL-5170DN
Color	Black
Approximate page yield	20,000 Pages



RTCA-DR360

Reliable and Quality:
Rosewill's replacement toner cartridges are 100% guaranteed to work as well or better than the original.

Significant Savings:
You can be certain of that you're getting reliable print at a lower cost. We offer consumers and businesses up to a 50 percent savings.

Environmental Benefits:
If you choose Rosewill's replacement toner cartridges, you will help to protect our environment by keeping reusable materials out of landfills.

Model	RTCA-DR360
Compatibility	Brother HL-2140, HL-2150N, HL-2170W, MFC-7320, MFC-7440N, MFC-7840W, DCP-7030, DCP-7040
Color	Black
Approximate page yield	12,000 Pages



RTCA-Q7553A

Reliable and Quality:
Rosewill's replacement toner cartridges are 100% guaranteed to work as well or better than the original.

Significant Savings:
You can be certain of that you're getting reliable print at a lower cost. We offer consumers and businesses up to a 50 percent savings.

Environmental Benefits:
If you choose Rosewill's replacement toner cartridges, you will help to protect our environment by keeping reusable materials out of landfills.

Model	RTCA-Q7553A
Compatibility	LaserJet M2727nf MFP, P2014, P2015, P2015d, P2015dn, P2015n, P2015x series printer
Color	Black
Approximate page yield	3,000 Standard Pages



RTCA-ML-D1630A

Reliable and Quality:
Rosewill's replacement toner cartridges are 100% guaranteed to work as well or better than the original.

Significant Savings:
You can be certain of that you're getting reliable print at a lower cost. We offer consumers and businesses up to a 50 percent savings.

Environmental Benefits:
If you choose Rosewill's replacement toner cartridges, you will help to protect our environment by keeping reusable materials out of landfills.

Model	RTCA-ML-D1630A
Compatibility	Samsung ML-1630, ML-1631K, SCX-4500, SCX-4501K
Color	Black
Approximate page yield	2,000 Pages

Sub-System

FEATURES

SPECIFICATIONS



RSV-S5

Sil3726/ Sil3132R5 Software RAID Design
Form Factor: Compact Tower
Cooling Fan: 120mm silence cooling fan
Providing 5 bay SATA II 3G HDD huge storage space for your multi media data backup.
RAID 0/1/0+1/5 subsystem design protects your data from losing. e-SATA (300 MB/s transfer rate) connects RSV-S5 to your system. 5 times faster than USB 2.0 (60 MB/s) interface. 120 mm silence fan guarantees the best cooling performance. Full 220W power supply included.
Special tray in and out/ easy replacement design.

Model	RSV-S5
Drive	SATA 150 & 300
External I/O	eSATA 3Gbps (via Port Multiplier)
RAID Levels	RAID 0, 1, 10, 5 and JBOD
3.5" Drive Bays	5
Power Supply	Full 220W
OS Supported	Support Windows 2000, XP, Vista, W/Server 2003, Server 2008 and MAC 10.4/10.5 (MAC and Linux via Port Multiplier)



RSV-S8

Sil3726/ Sil3132R5 Software RAID Design
Form Factor: Compact Tower
Cooling Fan: 120mm silence cooling fan
Providing 8 bay SATA II 3G HDD huge storage space for your multi media data backup.
RAID 0/1/0+1/5 subsystem design protects your data from losing. e-SATA (300 MB/s transfer rate) connects RSV-S8 to your system. 5 times faster than USB 2.0 (60 MB/s) interface. 120 mm silence fan guarantees the best cooling performance. Full 300W power supply included.
Special tray in and out/ easy replacement design.

Model	RSV-S8
Drive	SATA 150 & 300
External I/O	eSATA 3Gbps (via Port Multiplier)
RAID Levels	RAID 0, 1, 10, 5 and JBOD
3.5" Drive Bays	8
Power Supply	Full 300W
OS Supported	Support Windows 2000, XP, Vista, W/Server 2003, Server 2008 and MAC 10.4/10.5 (Support MAC and Linux via Port Multiplier)



R2-RAID

Universal fitting for dual 3.5" SATA/II HDD
Back panel Power ON/OFF switch
Back panel Fan ON/ODD switch
eSATA Plug & Play with PCI express card
Ultra speed up to SATA II 3Gbps
Support SATA1.0 SATA2.0 specification
Embedded system: JBOD, BIG, Raid 0, Raid 1, SAFE33, SAFE55
System Integration: JBOD+RAID1(SAFE33/55)
Raid function used on USB2.0 and eSATA specification
SATA to USB2.0 and eSATA specification. 5cm internal fan

Model	R2-RAID
Drive	SATA II
External I/O	eSATA / USB2.0
RAID Levels	RAID 0/1/JBOD/BIG + RAID1
3.5" Drive Bays	2
Power Supply	AC input: 100-240 VAC DC output: 12V2A, 5V2A, 34W dual output
OS Supported	Windows 2000/Sever 2003/XP/ Vista 32/64bit, Mac OS 9.0 and later Linux with Kernel 2.4.1.0 or above